

SPRINT DELIVERY-2

Date	19 NOVEMBER 2022
Team ID	PNT2022TMID04753
Topic	SmartFarmer - IoT Enabled Smart Farming Application

5.Building Project

Connecting IoT Simulator to IBM Watson IoT Platform

Open link provided in above section 4.3

Give the credentials of your device in IBM Watson IoT Platform

Click on connect

My credentials given to simulator are:


OrgID: **157uf3** api: **a-157uf3f5rg4qxp3**

Device type: **abcd** token:

6ogMaaQHNWFEgOD8R?

Device ID : **7654321**

Device Token : **87654321**



You can see the received data in graphs by creating cards in Boards tab

- You will receive the simulator data in cloud
- You can see the received data in Recent Events under your device
- Data received in this format(json)

```
{
  "d": {
    "name": "abcd",
    "temperature": 17,
    "humidity": 76,
    "Moisture ": 25
  }
}
```

The screenshot shows the IBM Watson IoT Platform dashboard. The top navigation bar includes tabs for 'Browse', 'Action', 'Device Types', and 'Interfaces'. The 'Recent Events' tab is selected, displaying a table of recent events. The table has four columns: 'Event', 'Value', 'Format', and 'Last Received'. The events are from an 'IoTSensor' device, showing temperature and humidity data in JSON format. The 'Last Received' column indicates the events were received 'a few seconds ago'.


Event	Value	Format	Last Received
IoTSensor	{"temp":108,"Humid":64}	json	a few seconds ago
IoTSensor	{"temp":91,"Humid":93}	json	a few seconds ago
IoTSensor	{"temp":108,"Humid":83}	json	a few seconds ago

Items per page 50 | 1-2 of 2 items

1 of 1 page

Configuration of Node-Red to collect IBM cloud data

The node IBM IoT App In is added to Node-Red workflow. Then the appropriate device credentials obtained earlier are entered into the node to connect and fetch device telemetry to Node-Red.



Once it is connected Node-Red receives data from the device

Display the data using debug node for verification


Connect function node and write the Java script code to get each reading separately.

The Java script code for the function node is:


```
msg.payload=msg.payload.d.temperature return
```

```
msg;
```


Finally connect Gauge nodes from dashboard to see the data in UI



Data received from the cloud in Node-Red console



Nodes connected in following manner to get each reading separately



This is the Java script code I written for the function node to get Temperature separately.

Configuration of Node-Red to collect data from OpenWeather

The Node-Red also receive data from the OpenWeather API by HTTP GET request. An inject trigger is added to perform HTTP request for every certain interval. HTTP request node is configured with URL we saved before in section 4.4 The data we receive from OpenWeather after request is in below JSON

```
format:{"coord":{"lon":79.85,"lat":14.13},"weather":[{"id":803,"main":"Clouds",
"description":"brokenclouds","icon":"04n"}],"base":"stations","main":{"temp":307
59,"feels_like":305.5,"temp_min":307.59,"temp_max":307.59,"pressure":1002,"h
umidity":35,"sea_level":1002,"grnd_level":1000},"wind":{"speed":6.23,"deg":170}
,"clouds":{"all":68},"dt":1589991979,"sys":{"country":"IN","sunrise":1589933553,
"sunset":1589979720},"timezone":19800,"id":1270791,"name":"Gūdūr","cod":20
```

0}

In order to parse the JSON string we use Java script functions and get each parameters

```
var temperature = msg.payload.main.temp;  
temperature = temperature-273.15;          return  
{payload : temperature.toFixed(2)};
```

In the above Java script code we take temperature parameter into a new variable and convert it from kelvin to Celsius

Then we add Gauge and text nodes to represent data visually in UI

