# ▼ TEAM ID : PNT2022TMID04039

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
%matplotlib inline

Using TensorFlow backend.
```

#### Download Dataset and Load into Dataframe

```
df = pd.read_csv('../input/spam.csv',delimiter=',',encoding='latin-1')
df.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro	NaN	NaN	NaN

# ▼ Data Analysis


Drop the columns that are not required for the neural network.

```
v2 5572 non-null object
```

dtypes: object(2)
memory usage: 87.1+ KB

```
sns.countplot(df.v1)
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

Text(0.5,1,'Number of ham and spam messages')



```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)

X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

### ▼ Pre-Processing

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = sequence.pad_sequences(sequences,maxlen=max_len)
```

# ▼ Create Model and add Layers

```
def RNN():
    inputs = Input(name='inputs',shape=[max_len])
    layer = Embedding(max_words,50,input_length=max_len)(inputs)
    layer = LSTM(64)(layer)
    layer = Dense(256,name='FC1')(layer)
```

```
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
return model
```

### Compile the Model

```
model = RNN()
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

Layer (type)	Output Shape	Param #
inputs (InputLayer)	(None, 150)	0
embedding_1 (Embedding)	(None, 150, 50)	50000
lstm_1 (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation_1 (Activation)	(None, 256)	0
dropout_1 (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_2 (Activation)	(None, 1)	0
T 1 1 06 227		

Total params: 96,337 Trainable params: 96,337 Non-trainable params: 0

#### ▼ Fit the Model

#### Test the Model

Colab paid products - Cancel contracts here

