

SPRINT 4

Date	12 November 2022
Team ID	PNT2022TMID04650
Project Name	Smart Farmer – IOT Enabled Smart Farming Application

IOT ENABLED SMART FARMING APPLICATION SPRINT DELIVERY – 4

Receiving commands from IBM cloud using Python program

```
import time
```

```
import sys
```

```
import ibmiotf.application
```

```
import ibmiotf.device
```

```
import random
```

```
#Provide your IBM Watson Device Credentials
```

```
organization = " nicw4y"
```

```
deviceType = " NodeMCU"
```

```
deviceId = "12376"
```

```
authMethod = "token"
```

```
authToken = "harsha@23"
```

```
# Initialize GPIO
```

```
def myCommandCallback(cmd):
```

```
    print("Command received: %s" % cmd.data['command'])
```

```
    status=cmd.data['command']
```

```
    if status=="motoron": print ("motor is on")
```

```
    elif
```

```
    status == "motoroff": print("motor is off")
```

else :

print ("please send proper command")

try:

deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method": authMethod, "auth-token": authToken}

deviceCli = ibmiotf.device.Client(deviceOptions)

#.....

```
except Exception as e:
```

```
    print("Caught exception connecting device: %s" % str(e))
```

```
sys.exit()
```

```
# Connect and send a datapoint "hello" with value "world" into the cloud as an  
event of type "greeting" 10 times deviceCli.connect()
```

```
while True:
```

```
    #Get Sensor Data from DHT11
```

```
temp=random.randint(90,110)
```

```
Humid=random.randint(60,100)
```

```
Mois=random. Randint(20,120)
```

```
    data = { 'temp' : temp, 'Humid': Humid ,
```

```
    'Mois': Mois}
```

```
    #print data    def
```

```
myOnPublishCallback():
```

```
    print ("Published Temperature = %s C" % temp, "Humidity = %s %% " %  
Humid, "Moisture =%s deg c" % Mois "to IBM Watson")
```

```
    success = deviceCli.publishEvent("IoTSensor", "json", data, qos=0,  
on_publish=myOnPublishCallback)    if not success:
```

```
        print("Not connected to IoT")
```

```
time.sleep(10)
```


```
    deviceCli.commandCallback = myCommandCallback #
```

```
Disconnect the device and application from the cloud
```

```
deviceCli.disconnect()
```


```
# Initialize GPIO
def myCommandCallback(cmd):
    print("Command received: %s" % cmd.data['command'])
    status=cmd.data['command']
    if status=="motoron":
        print ("motor is on")
    elif status == "motoroff":
        print ("motor is off")
    else :
        print ("please send proper command")

try:
    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId, "auth-method": authMe}
    deviceCli = ibmiotf.device.Client(deviceOptions)
    #.....
```



```
Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```


Flow Chart



Observations & Results

The screenshot shows a Python 3.7.0 Shell window with the following output:

```
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py =====
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```



Advantages & Disadvantages Advantages:

- Farms can be monitored and controlled remotely.
- Increase in convenience to farmers.
- Less labor cost.
- Better standards of living.

Disadvantages:

- Lack of internet/connectivity issues.
- Added cost of internet and internet gateway infrastructure.
- Farmers wanted to adapt the use of Mobile App.

Conclusion

Thus, the objective of the project to implement an IOT system in order to help farmers to control and monitor their farms has been implemented successfully.

