

```
#include<Servo.h>

const int pingPin = 7;
int servoPin = 8;


Servo servo1;


void setup() {
  // initialize serial communication:
  Serial.begin(9600);
  servo1.attach(servoPin);
  pinMode(2,INPUT);
  pinMode(4,OUTPUT);
  pinMode(11,OUTPUT);
  pinMode(12,OUTPUT);
  pinMode(13,OUTPUT);
  pinMode(A0,INPUT);
  digitalWrite(2,LOW);
  digitalWrite(11,HIGH);

}


void loop() {

  long duration, inches, cm;


  pinMode(pingPin, OUTPUT);
  digitalWrite(pingPin, LOW);
```

```

delayMicroseconds(2);
digitalWrite(pingPin, HIGH);
delayMicroseconds(5);
digitalWrite(pingPin, LOW);

// The same pin is used to read the signal from the PING))) a HIGH pulse
// whose duration is the time (in microseconds) from the sending of the ping
// to the reception of its echo off of an object.
pinMode(pingPin, INPUT);
duration = pulseIn(pingPin, HIGH);

// convert the time into a distance
inches = microsecondsToInches(duration);
cm = microsecondsToCentimeters(duration);

//Serial.print(inches);
//Serial.print("in, ");
//Serial.print(cm);
//Serial.print("cm");
//Serial.println();
//delay(100);

servo1.write(0);

if(cm < 40)
{
    servo1.write(90);

```

```
    delay(2000);
}
else
{
    servo1.write(0);
}

// PIR with LED starts
int pir = digitalRead(2);

if(pir == HIGH)
{
    digitalWrite(4,HIGH);
    delay(1000);
}
else if(pir == LOW)
{
    digitalWrite(4,LOW);
}

//temp with fan
float value=analogRead(A0);
float temperature=value*0.48;

Serial.println("temperature");
Serial.println(temperature);
```

```
if(temperature > 20)
{
    digitalWrite(12,HIGH);
    digitalWrite(13,LOW);
}
else
{
    digitalWrite(12,LOW);
    digitalWrite(13,LOW);
}
}
```

```
long microsecondsToInches(long microseconds) {
    return microseconds / 74 / 2;
}
```

```
long microsecondsToCentimeters(long microseconds) {
    return microseconds / 29 / 2;
}
```

IBM-EPBL invited you to: x Upload files - IBM-EPBL/ x Circuit design Copy of H x IBM x Circuit design Glorious x soft suave salary for fre x +

tinkercad.com/things/dpq6IY4hmRT-copy-of-home-automation-system/editel

Home automation system

Simulator time: 00:00:00.546

Code Stop Simulation Send To

Components All

Search

General

- Resistor
- Capacitor
- Polarized Capacitor
- Diode
- Zener Diode
- Inductor

Input

- Pushbutton
- Potentiometer
- Slideswitch
- Photoresistor
- Photodiode
- Ambient Light Sensor...

Type here to search

71°F Cloudy 15:12 16-09-2022