HAZARDOUS AREA MONITORING FOR INDUSTRIAL PLANTS POWERED BY IOT

SUBMITTED BY

GOLI HEMASWI (113219041031)

BACHELOR OF ENGINEERING IN ELECTRONICS AND COMMUNICATION ENGINEERING

ASSIGNMENT-04

Question:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100cms send "alert" to ibm cloud and display in device recent events.

Upload document with wokwi share link and images of ibm cloud.

Solution:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#define ECHO_GPIO 12
#define TRIGGER_GPIO 13
#define MAX DISTANCE CM 100 // Maximum of 5 meters
#include "Ultrasonic.h"
Ultrasonic ultrasonic(13, 12);
int distance;
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
#define ORG "dv1snq"//IBM ORGANITION ID
#define DEVICE_TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform
#define DEVICE ID "12345"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "45682367915" //Token
String data3;
float h, t;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
```

```
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
void loop()// Recursive Function
 distance = ultrasonic.read(CM);
 if(distance < 100){</pre>
 Serial.print("Distance in CM: ");
 Serial.println(distance);
 PublishData(distance);
 delay(1000);
 if (!client.loop()) {
   mqttconnect();
 delay(1000);
Cloud. .... */
void PublishData(float temp) {
 mqttconnect();//function call for connecting to ibm
     creating the String in in form JSon to update the data to ibm cloud
 String payload = "{\"Alert Distance:\":";
```

```
payload += temp;
  payload += "}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");// if it successfully upload data on the cloud
failed
 } else {
   Serial.println("Publish failed");
void mqttconnect() {
 if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
     delay(500);
     initManagedDevice();
     Serial.println();
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
 while (WiFi.status() != WL_CONNECTED) {
   delay(500);
   Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
```

```
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
   Serial.println((subscribetopic));
   Serial.println("subscribe to cmd OK");
 } else {
    Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {</pre>
   //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
 Serial.println("data: "+ data3);
 if(data3=="lighton")
Serial.println(data3);
 else
Serial.println(data3);
data3="";
```

Wokwi link:

https://wokwi.com/projects/346659959540286034







