

SMS SPAM Classification

1) Import required library

In []:

```
import pandas as pd
import numpy as np
from keras import utils
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical
%matplotlib inline
```

2) i) Read dataset

In []:

```
!unzip "/content/drive/MyDrive/Colab Notebooks/spam.zip"
```

Archive: /content/drive/MyDrive/Colab Notebooks/spam.zip
inflating: spam.csv

In []:

```
df = pd.read_csv('spam.csv', delimiter=',', encoding='latin-1')
df
```

Out[]:

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro...	NaN	NaN	NaN
...
5567	spam	This is the 2nd time we have tried 2 contact u...	NaN	NaN	NaN
5568	ham	Will l_b going to esplanade fr home?	NaN	NaN	NaN
5569	ham	Pity, * was in mood for that. So...any other s...	NaN	NaN	NaN
5570	ham	The guy did some bitching but I acted like i'd...	NaN	NaN	NaN
5571	ham	Rofl. Its true to its name	NaN	NaN	NaN

5572 rows × 5 columns

2) ii)Pre-processing

In []:

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
```

```
df # Drop the columns that are not required for the neural network.
```

```
Out[ ]:
```

	v1	v2
0	ham	Go until jurong point, crazy.. Available only ...
1	ham	Ok lar... Joking wif u oni...
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...
3	ham	U dun say so early hor... U c already then say...
4	ham	Nah I don't think he goes to usf, he lives aro...
...
5567	spam	This is the 2nd time we have tried 2 contact u...
5568	ham	Will l_b going to esplanade fr home?
5569	ham	Pity, * was in mood for that. So...any other s...
5570	ham	The guy did some bitching but I acted like i'd...
5571	ham	Rofl. Its true to its name

5572 rows × 2 columns

```
In [ ]:
```


```
sns.countplot(df.v1,palette='Set3')
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

/usr/local/lib/python3.7/dist-packages/seaborn/_decorators.py:43: FutureWarning: Pass the following variable as a keyword arg: x. From version 0.12, the only valid positional argument will be `data`, and passing other arguments without an explicit keyword will result in an error or misinterpretation.

FutureWarning

```
Out[ ]:
```

Text(0.5, 1.0, 'Number of ham and spam messages')



```
In [ ]:
```

```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
In [ ]:
```

```
# Split into training and test data.
```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
In [ ]:
```

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = utils.pad_sequences(sequences,maxlen=max_len) # Padding the words to get equal length for all words in a sentence
```

```
In [ ]:
```

```
sequences_matrix.shape
```

```
Out[ ]:
```

```
(4736, 150)
```

```
In [ ]:
```

```
sequences_matrix.ndim
```

```
Out[ ]:
```

```
2
```

```
In [ ]:
```

```
sequences_matrix = np.reshape(sequences_matrix, (4736,150,1))
sequences_matrix.ndim #3d shape verification to proceed to RNN LSTM
```

```
Out[ ]:
```

```
3
```

4) Create Model for RNN

```
In [ ]:
```

```
from keras.models import Sequential
from keras.layers import Dense
from keras.layers import LSTM
from keras.layers import Embedding
```

```
In [ ]:
```

```
model = Sequential()
```

5) Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
In [ ]:
```

```
model.add(Embedding(max_words,50,input_length=max_len))
model.add(LSTM(units=64,input_shape = (sequences_matrix.shape[1],1),return_sequences=True))
model.add(LSTM(units=64,return_sequences=True))
model.add(LSTM(units=64,return_sequences=True))
model.add(LSTM(units=64))
model.add(Dense(units = 256,activation = 'relu'))
model.add(Dense(units = 1,activation = 'sigmoid'))
```

6) Compile the Model

```
In [ ]:
```

```
model.summary()
model.compile(loss='binary_crossentropy',optimizer='adam',metrics=['accuracy'])
```

Model: "sequential"

Layer (type)	Output Shape	Param #
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 150, 64)	29440
lstm_1 (LSTM)	(None, 150, 64)	33024
lstm_2 (LSTM)	(None, 150, 64)	33024
lstm_3 (LSTM)	(None, 64)	33024
dense (Dense)	(None, 256)	16640
dense_1 (Dense)	(None, 1)	257
embedding_1 (Embedding)	(None, 1, 50)	50000
lstm_4 (LSTM)	(None, 1, 64)	29440
lstm_5 (LSTM)	(None, 1, 64)	33024
lstm_6 (LSTM)	(None, 1, 64)	33024
lstm_7 (LSTM)	(None, 64)	33024
dense_2 (Dense)	(None, 256)	16640
dense_3 (Dense)	(None, 1)	257

=====
Total params: 390,818
Trainable params: 390,818
Non-trainable params: 0
=====

7)Fit the model on the training data.

In []:

```
X = model.fit(sequences_matrix,Y_train,batch_size=128,epochs=5,validation_split=0.2)
X
```

```
Epoch 1/5
30/30 [=====] - 45s 1s/step - loss: 0.4416 - accuracy: 0.8432 -
val_loss: 0.2616 - val_accuracy: 0.8903
Epoch 2/5
30/30 [=====] - 31s 1s/step - loss: 0.1363 - accuracy: 0.9591 -
val_loss: 0.0683 - val_accuracy: 0.9778
Epoch 3/5
30/30 [=====] - 33s 1s/step - loss: 0.0556 - accuracy: 0.9826 -
val_loss: 0.0633 - val_accuracy: 0.9821
Epoch 4/5
30/30 [=====] - 34s 1s/step - loss: 0.0369 - accuracy: 0.9894 -
val_loss: 0.0773 - val_accuracy: 0.9821
Epoch 5/5
30/30 [=====] - 32s 1s/step - loss: 0.0275 - accuracy: 0.9926 -
val_loss: 0.0833 - val_accuracy: 0.9821
```

Out[]:

```
<keras.callbacks.History at 0x7f0e3ddf3c10>
```

8)Save the model

In []:

```
model.save
```

Out []:

```
<bound method Model.save of <keras.engine.sequential.Sequential object at 0x7f0e42439910>
>
```

9) Evaluate the model on test set data.

In []:

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = utils.pad_sequences(test_sequences,maxlen=max_len)
```

In []:

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 6s 84ms/step - loss: 0.1020 - accuracy: 0.9701
```

In []:

```
l = accr[0]
a =accr[1]
print('Test set\n  Loss: {:.3f}\n  Accuracy: {:.3f}'.format(l,a))
```

```
Test set
  Loss: 0.102
  Accuracy: 0.970
```

In []: