Assignment -3

Python Programming

Assignment Date	01 october 2022
Student Name	Mr. Saravanan G
Student Roll Number	610819104041
Maximum Marks	2 Marks

Question-1:

```
** What is 7 to the power of 4?**

[1]  print(pow(7,4))

     2401
```

Question-2:

```
** Split this string:**

s = "Hi there Sam!"

*into a list. *

s = "Hi there Sam!"
print (s.split())

['Hi', 'there', 'Sam!']
```

Question-3:

```
** Given the variables:**

planet = "Earth"
diameter = 12742

** Use .format() to print the following string: **

The diameter of Earth is 12742 kilometers.

[3]  planet = "Earth"
     diameter = 12742
     print ('The diameter of {} is {} kilometers' .format(planet,diameter))

     The diameter of Earth is 12742 kilometers
```

Question-4:

```
** Given this nested list, use indexing to grab the word "hello" **

[4]  lst = [1,2,[3,4],[5,[100,200,['hello']],23,11],1,7]

[5]  lst = [1,2,[3,4],[5,[100,200,['hello']],23,11],1,7]
     print(lst[3][1][2])

     ['hello']
```

Question-5:

```
** Given this nest dictionary grab the word "hello". Be prepared, this will be annoying/tricky **

d = {'k1':[1,2,3,{'tricky':['oh','man','inception',{'target':[1,2,3,'hello']}]}]}

[6]  d = {'k1':[1,2,3,{'tricky':['oh','man','inception',{'target':[1,2,3,'hello']}]}]}
     print(d['k1'][3]['tricky'][3]['target'][3])

     hello
```

Question-6:

```
** What is the main difference between a tuple and a list? **

[8]  #tuple are immutable byut list are mutable
     #tuples are denoted in () and list are denoted as []
```

Question-7:

```
** Create a function that grabs the email website domain from a string in the form: **

user@domain.com

So for example, passing "user@domain.com" would return: domain.com

[10] def domainGet(email):
         print("Your domain is: " + email.split('@')[-1])

     email = input("Please enter your email: >")

     Please enter your email: >user@domain.com

[ ]  domainGet('user@domain.com')

     Your domain is: domain.com
```

Question-8:

```
** Create a basic function that returns True if the word 'dog' is contained in the input string. Don't worry about edge cases like a punctuation
being attached to the word dog, but do account for capitalization. **

[11] def findDog(st):
         if 'dog' in st.lower():
             print("True")
         else:
             print("False")

     st = "Is there a dog here?"
     findDog(st)

     True

[12] findDog('Is there a dog here?')

     True
```

Question-9:

```
** Create a function that counts the number of times the word "dog" occurs in a string. Again ignore edge cases. **

[13] value = 'This dog runs faster than the other dog dude!';

     def countdogs(value):
         count = 0
         for word in value.lower().split():
             if word == 'dog' or word == 'dogs':
                 count = count + 1
                 print(count)

     countdogs(value)

     1
     2
```

Question-10:

```
▾ Problem

  *You are driving a little too fast, and a police officer stops you. Write a function to return one of 3 possible results: "No ticket", "Small ticket", or "Big
  Ticket". If your speed is 60 or less, the result is "No Ticket". If speed is between 61 and 80 inclusive, the result is "Small Ticket". If speed is 81 or
  more, the result is "Big Ticket". Unless it is your birthday (encoded as a boolean value in the parameters of the function) – on your birthday, your
  speed can be 5 higher in all cases. *

  def caught_speeding(speed, is_birthday):

      if is_birthday:
          speeding = speed - 5
      else:
          speeding = speed

      if speeding > 80:
          return 'Big Ticket'
      elif speeding > 60:
          return 'Small Ticket'
      else:
          return 'No Ticket'
```

Question-11:

Create an employee list with basic salary values(at least 5 values for 5 employees) and using a for loop retreive each employee salary and calculate total salary expenditure.

```python
employee=[400,500,550,600,250]
sum=0
print ("salaryof 1st person is",employee[0])
print ("salaryof 2nd person is",employee[1])
print ("salaryof 3rd person is",employee[2])
print ("salaryof 4th person is",employee[3])
print ("salaryof 5th person is",employee[4])
for x in employee:
    sum=sum+x
print("The total salary is", sum)
```

```
salaryof 1st person is 400
salaryof 2nd person is 500
salaryof 3rd person is 550
salaryof 4th person is 600
salaryof 5th person is 250
The total salary is 2300
```

Question-12:

Create two dictionaries in Python:

First one to contain fields as Empid, Empname, Basicpay

Second dictionary to contain fields as DeptName, DeptId.

Combine both dictionaries.

```python
d1={'Empid':1,'Empname':"abc",'basicpay':10000}
d2={'Deptname':'cse','Deptid':2}

print({**d1, **d2})
```

```
{'Empid': 1, 'Empname': 'abc', 'basicpay': 10000, 'Deptname': 'cse', 'Deptid': 2}
```