Delivery of Sprint-2

DATE	17 November 2022
TEAM ID	PNT2022TMID26725
PROJECT NAME	SMART WASTE MANAGEMENT FOR METROPOLITAN CITIES

Code for Data Transfer from Sensors

```
#include <WiFi.h>
                                                           // library for wifi
  #include < PubSubClient.h>
                                                           // library for MQTT
  #include <LiquidCrystal_I2C.h> LiquidCrystal_I2C
  lcd(0x27, 20, 4);
                    credentials of IBM Accounts___
  #define ORG "ktymlx"
                                                           // IBM organisation id
  #define DEVICE_TYPE "new"
                                                          // Device type mentioned in ibm watson iot platform
  #define DEVICE_ID "09876"
                                                         // Device ID mentioned in ibm watson iot platform
  #define TOKEN "Kamesh@2002"
                                                           // Token
//
                    customise above values_____-
  char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name char publishTopic[] = "iot-2/evt/data/fmt/json"; char
  topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of strings char authMethod[] = "usetoken-
  auth"; // authentication method char token[] = TOKEN;
  char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
                                                                     //Client id
  WiFiClient wifiClient;
                                                                    // creating instance for wificlient
  PubSubClient client(server, 1883, wifiClient);
  #define ECHO_PIN 12
  #define TRIG_PIN 13 float
  dist;
  void setup()
  Serial.begin(115200);
                                  OUTPUT);
  pinMode(LED_BUILTIN,
  pinMode(TRIG_PIN,
                                  OUTPUT);
  pinMode(ECHO_PIN,INPUT);
  //pir pin pinMode(4, INPUT);
  //ledpins pinMode(23,
  OUTPUT); pinMode(2,
  OUTPUT); pinMode(4,
  OUTPUT); pinMode(15,
  OUTPUT);
```

```
0); lcd.print(""); wifiConnect();
mqttConnect();
float readcmCM()
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2); digitalWrite(TRIG_PIN,HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW); int duration=
pulseIn(ECHO_PIN, HIGH); return
duration * 0.034 / 2;
void loop()
lcd.clear();
publishData(); delay(500);
if (!client.loop())
  {
                                                                         // function call to connect to IBM
   mqttConnect();
  }
                                             _-retrieving to cloud_
                                                                                                        _*/
void wifiConnect()
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
  {
   delay(500);
   Serial.print(".");
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
void mqttConnect()
{
  if (!client.connected())
   {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    (!client.connect(clientId, authMethod, token))
     {
      Serial.print("."); delay(500);
     }
    initManagedDevice(); Serial.println();
void initManagedDevice()
{
  if (client.subscribe(topic))
   {
    Serial.println("IBM subscribe to cmd OK");
```

lcd.init(); lcd.backlight(); lcd.setCursor(1,

```
else
       Serial.println("subscribe to cmd FAILED");
   void publishData()
   float cm = readcmCM();
    if(digitalRead(34))
                                                                        //PIR motion detection
     \textbf{Serial}. println ("Motion
     Detected"); Serial.println("Lid
     Opened"); digitalWrite(15, HIGH);
   else
     digitalWrite(15, LOW);
   if(digitalRead(34)== true)
    if(cm <= 100)
                                                                      //Bin level detection
     digitalWrite(2, HIGH);
     Serial.println("High Alert!!!,Trash bin is about to be full");
     Serial.println("Lid Closed"); lcd.print("Full! Don't use"); delay(2000);
        lcd.clear();
                               digitalWrite(4,
                                                      LOW);
     digitalWrite(23, LOW);
  else if(cm > 150 && cm < 250)
     digitalWrite(4, HIGH);
     Serial.println("Warning!!,Trash is about to cross 50% of bin level"); digitalWrite(2,LOW);
     digitalWrite(23, LOW);
  else if(cm > 250 \&\& cm <= 400)
     digitalWrite(23, HIGH); Serial.println("Bin is
     available"); digitalWrite(2,LOW);
     digitalWrite(4, LOW);
     delay(10000); Serial.println("Lid Closed");
  else
    Serial.println("No motion detected");
   if(cm <= 100)
   digitalWrite(21,HIGH);
   String payload = "{\"High Alert!!\":\"";
   payload += cm; payload
   += "left\" }";
   Serial.print("\n");
   Serial.print("Sending payload: ");
   Serial.println(payload); if (client.publish(publishTopic, (char*) payload.c_str())) // if data is uploaded to cloud successfully,prints publish
ok or prints publish failed
  Serial.println("Publish OK");
```

```
if(cm <= 250)
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist; payload += "left\" }";
\textbf{Serial}.print("\n");
Serial.print("Sending distance: "); Serial.println(cm); if(client.publish(publishTopic,
(char*) payload.c_str()))
Serial.println("Publish OK");
}
else
Serial.println("Publish FAILED");
}
float inches = (cm / 2.54); //print on LCD lcd.setCursor(0,0); lcd.print("Inches"); lcd.setCursor(4,0);
lcd.setCursor(12,0); lcd.print("cm"); lcd.setCursor(1,1); lcd.print(inches, 1); lcd.setCursor(11,1);
lcd.print(cm, 1); lcd.setCursor(14,1); delay(1000); lcd.clear();
}
```

Connection Diagram

