

Sprint 1

```
{
  "nbformat": 4,
  "nbformat_minor": 0,
  "metadata": {
    "colab": {
      "provenance": []
    },
    "kernelspec": {
      "name": "python3",
      "display_name": "Python 3"
    },
    "language_info": {
      "name": "python"
    }
  },
  "cells": [
    {
      "cell_type": "code",
      "execution_count": null,
      "metadata": {
        "id": "Mu6nSJIEcEkq"
      },
      "outputs": [],
      "source": [
        "import numpy\n",
        "import tensorflow #open source used for both ML and DL for\n",
        "computation\n",
        "from tensorflow.keras.datasets import mnist #mnist dataset\n",
        "from tensorflow.keras.models import Sequential #it is a plain\n",
        "stack of layers\n",
        "from tensorflow.keras import layers #A Layer consists of a\n",
        "tensor- in tensor-out computat ion funct ion\n",
        "from tensorflow.keras.layers import Dense, Flatten #Dense-Dense\n",
        "Layer is the regular deeply connected r\n",
        "#faltten -used fot flattening the input or change the\n",
        "dimension\n",
        "from tensorflow.keras.layers import Conv2D #onvoLutiona l\n",
        "Layer\n",
        "from keras.optimizers import Adam #opt imizer\n",
        "from keras. utils import np_utils #used for one-hot encoding\n",
        "import matplotlib.pyplot as plt    #used for data visualization"
      ]
    },
    {
      "cell_type": "code",
      "source": [
        "(x_train, y_train), (x_test, y_test)=mnist.load_data ()\n",
        "#splitting the mnist data into train and test"
      ],
      "metadata": {
        "id": "aCcoR9IbcJ7z"
      }
    }
  ]
}
```

```

    },
    "execution_count": null,
    "outputs": []
  },
  {
    "cell_type": "markdown",
    "source": [
      "Downloading data from
https://storage.googleapis.com/tensorflow/tf-keras-datasets/mnist.npz\n",
      "11490434/11490434 [=====] - 1s
0us/step"
    ],
    "metadata": {
      "id": "eK8KcqX5cQNY"
    }
  },
  {
    "cell_type": "code",
    "source": [
      "print (x_train.shape) #shape is used for give the dimens ion
values #60000-rows 28x28-pixels\n",
      "print (x_test.shape)"
    ],
    "metadata": {
      "id": "dHjyggiiyTcj"
    },
    "execution_count": null,
    "outputs": []
  },
  {
    "cell_type": "markdown",
    "source": [
      "(60000, 28, 28)\n",
      "(10000, 28, 28)"
    ],
    "metadata": {
      "id": "H9OCiCUccYQ6"
    }
  },
  {
    "cell_type": "code",
    "source": [
      "x_train[0]"
    ],
    "metadata": {
      "id": "yKTc6HYgcbjU"
    },
    "execution_count": null,
    "outputs": []
  },
  {
    "cell_type": "markdown",
    "source": [

```

[illegible]

[illegible]

```

0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      0,      0,      18,      171,      219,      253,      253,
253,      253, \n",
      "
      195,      80,      9,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      55,      172,      226,      253,      253,      253,      253,
244,      133, \n",
      "
      11,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      136,      253,      253,      253,      212,      135,      132,
16,      0, \n",
      "
      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0], \n",
      "
      [  0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,      0,
0,      0, \n",
      "
      0,      0]], dtype=uint8)"
],
"metadata": {
  "id": "G4PlafH6ceYz"
}
},
{
  "cell_type": "code",
  "source": [
    "plt.imshow(x_train[6000])          #ploting the index=image"
  ],
  "metadata": {
    "id": "ZgiGA9_Fcn_b"
  },
  "execution_count": null,
  "outputs": []
},
{
  "cell_type": "markdown",
  "source": [

```

```
"metadata": {  
  "id": "60r31_r4creT"  
}  
  
},
```



```
{  
  "cell_type": "code",  
  "source": [  
    "numpy.argmax(y_train[6000])"  
  ],  
  "metadata": {  
    "id": "Wv5q_ZXTcw9j"  
  },  
  "execution_count": null,  
  "outputs": []  
},  
{  
  "cell_type": "markdown",  
  "source": [  
    "0"  
  ],  
  "metadata": {
```

```

        "id": "48UNMbUGc1LT"
    },
    {
        "cell_type": "code",
        "source": [
            "#Reshaping to format which CNN expects (batch, height, width,
channels)\n",
            "x_train=x_train.reshape (60000, 28, 28, 1).astype('float32')\n",
            "x_test=x_test.reshape (10000, 28, 28, 1).astype ('float32')\n",
            ],
        "metadata": {
            "id": "RSi2BdQKc36s"
        },
        "execution_count": null,
        "outputs": []
    },
    {
        "cell_type": "code",
        "source": [
            "number_of_classes = 10 #storing the no of classes in a
variable"
            ],
        "metadata": {
            "id": "M8y_pNh7c7jS"
        },
        "execution_count": null,
        "outputs": []
    },
    {
        "cell_type": "code",
        "source": [
            "y_train = np_utils.to_categorical (y_train, number_of_classes)
#converts the output in binary format\n",
            "y_test = np_utils.to_categorical (y_test, number_of_classes)\n",
            ],
        "metadata": {
            "id": "0LEAzEb9c9o7"
        },
        "execution_count": null,
        "outputs": []
    }
]
}

```