

## Assignment-4

Assignment Date	9 NOVEMBER 2022
Student Name	M. MOHAMED NAWAS
TEAM ID	PNT2022TMID45514

### Question:

1. Pull an Image from the docker hub and run it in the docker playground.

**Pull an image from the docker hub.**

```
Microsoft Windows [Version 10.0.19044.2130]
(c) Microsoft Corporation. All rights reserved.



C:\Users\Lenovo>docker pull dharshinipk/getting-started
Using default tag: latest
latest: Pulling from dharshinipk/getting-started
Digest: sha256:8dbed4d8c9fc72acca15d6dbe2734009adbb45a2a28a45330bcc0ca2b3ff5d7
Status: Image is up to date for dharshinipk/getting-started:latest
docker.io/dharshinipk/getting-started:latest

C:\Users\Lenovo>docker pull dharshinipk/docker_flask_with_form
Using default tag: latest
Error response from daemon: manifest for dharshinipk/docker_flask_with_form:latest not found: manifest unknown: manifest unknown


C:\Users\Lenovo>docker push dharshinipk/docker_flask_with_form
Using default tag: latest
The push refers to repository [docker.io/dharshinipk/docker_flask_with_form]
99633df762e2: Pushed
73ee95d8486b: Pushed
a79bf86c66cb: Pushed
583275d8d6c8: Pushed
0fc1deb8136e: Pushed
1f123186824c: Layer already exists
3d6eb1152931: Layer already exists
100796cdf3b1: Retrying in 1 second
54acb5a6fa8b: Pushing [----->] 71.27MB/528.7MB
8d51c618126f: Layer already exists
9ff6e4d46744: Pushing [----->] 8.333MB/18.95MB
a89d1d47b5a1: Layer already exists
655ed1b7a428: Layer already exists
net/http: TLS handshake timeout

C:\Users\Lenovo>docker images
REPOSITORY          TAG         IMAGE ID      CREATED       SIZE
dharshinipk/docker_flask_with_form   latest     94ac771be3b1  23 hours ago  932MB
docker_flask_with_form               latest     94ac771be3b1  23 hours ago  932MB
dharshinipk/getting-started          latest     cb90f98fd791  6 months ago  28.8MB
docker/getting-started               latest     cb90f98fd791  6 months ago  28.8MB

C:\Users\Lenovo>docker pull ubuntu:20.04
Error response from daemon: Head "https://registry-1.docker.io/v2/library/ubuntu/manifests/20.04": Get "https://auth.docker.io/token?account=dharshinipk&scope=repository%3Alibrary%3Aubuntu%3Apull&service=registry.docker.io": dialing auth.docker.io:443 no HTTPS proxy: connecting to 44.205.64.79:443: dial tcp 44.205.64.79:443: i/o timeout
```




- ## 2. Create a docker file for the job portal application and deploy it in Docker desktop application.




## Deploy in docker application



## Running in docker desktop




### 3. Create a IBM container registry and deploy helloworld app or jobportalapp.





## Creating a kubernetes cluster in ibm cloud



## Expose the same app to run in noteport

```
C:\Windows\System32\cmd.exe
10/16/2022 12:28 PM          3,721 windows shortcut.txt
08/25/2022 08:40 PM          2,897 YouTube.lnk
          24 File(s)      804,677,196 bytes
          9 Dir(s)      79,221,886,976 bytes free

C:\Users\gani\Desktop>cd deploy
The system cannot find the path specified.

C:\Users\gani\Desktop>kubectl apply -f kubernetes/depoly.yaml
error: the path "kubernetes/depoly.yaml" does not exist

C:\Users\gani\Desktop>kubectl apply -f depoly.yaml
error: the path "depoly.yaml" does not exist

C:\Users\gani\Desktop>kubectl apply -f C:\Users\gani\Desktop\deploy.yaml
deployment.apps/flask-app created

C:\Users\gani\Desktop>
```

```

C:\Windows\System32\cmd.exe
C:\Windows\system32\kubectl expose deployment flask-app --type=NodePort --name=flask-service
The Service "flask-service" is invalid: metadata.name: Invalid value: "flask-service": a DNS-1035 label must consist of lower case alphanumeric characters or '-', start with an alphabetic character, and end with an alphanumeric character (e.g. "my-name", or "abc-123", regex used for validation is "[a-z]([-a-z0-9]*[a-z0-9])?")
C:\Windows\system32\kubectl expose deployment flask-app --type=NodePort --name=flask-service
The Service "flask-service" is invalid: metadata.name: Invalid value: "flask-service": a DNS-1035 label must consist of lower case alphanumeric characters or '-', start with an alphabetic character, and end with an alphanumeric character (e.g. "my-name", or "abc-123", regex used for validation is "[a-z]([-a-z0-9]*[a-z0-9])?")
C:\Windows\system32\kubectl expose deployment flask-app --type=NodePort --name=flask-service
The Service "flask-service" is invalid: metadata.name: Invalid value: "flask-service": a DNS-1035 label must consist of lower case alphanumeric characters or '-', start with an alphabetic character, and end with an alphanumeric character (e.g. "my-name", or "abc-123", regex used for validation is "[a-z]([-a-z0-9]*[a-z0-9])?")
C:\Windows\system32\kubectl expose deployment flask-app --type=NodePort --name=flask-service
Error from server (AlreadyExists): services "flask-service" already exists
C:\Windows\system32>
C:\Windows\system32\kubectl -n kubernetes-dashboard get deploy
^C
C:\Windows\system32\kubectl -n kubernetes-dashboard get deploy
No resources found in kubernetes-dashboard namespace.
C:\Windows\system32\kubectl -n kubernetes-dashboard get deploy
No resources found in kubernetes-dashboard namespace.
C:\Windows\system32\kubectl proxy
Starting to serve on 127.0.0.1:8001
^C
C:\Windows\system32\kubectl -n kubernetes-dashboard get deploy
^C
C:\Windows\system32\kubectl -n kubernetes-dashboard get deploy
No resources found in kubernetes-dashboard namespace.
C:\Windows\system32\kubectl -n kubernetes-dashboard get pods
No resources found in kubernetes-dashboard namespace.
C:\Windows\system32\kubectl expose deployment flask-app --type=NodePort --name=flask-service
Error from server (AlreadyExists): services "flask-service" already exists
C:\Windows\system32\kubectl get ing
NAME          CLASS    HOSTS      ADDRESS      PORTS      AGE
flask-app-ingress  cnames  *          *            80         27s
C:\Windows\system32\kubectl get svc
NAME          TYPE      CLUSTER-IP      EXTERNAL-IP  PORT(S)      AGE

```