IBM ASSIGNMENT 4


- NAVEEN V M (TEAM LEAD) team id: PNT2022TMID22142

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#define ECHO_PIN 2
#define TRIG PIN 4
#define LED 5
//----credentials of IBM Accounts-----
#define ORG "ko6yr3"//IBM ORGANITION ID
#define DEVICE TYPE "esp32"//Device type mentioned in ibm watson IOT
Platform#define DEVICE_ID "esp123"//Device ID mentioned in ibm watson
IOT Platform#define TOKEN "*ZNl1x*zWaNUBOlbso"
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883,wifiClient); //calling the predefined client
id by passing parameter like server id, portand wificredential
void setup()// configureing the ESP32
  Serial.begin(115200);
  pinMode(TRIG_PIN, OUTPUT);
  pinMode(ECHO PIN, INPUT);
  pinMode(LED,OUTPUT);
  delay(10);
  Serial.println();
 wificonnect();
  mqttconnect();
```

```
float readDistanceCM() {
  digitalWrite(TRIG_PIN, LOW);
 delayMicroseconds(2);
 digitalWrite(TRIG_PIN, HIGH);
 delayMicroseconds(10);
 digitalWrite(TRIG_PIN, LOW);
 int duration = pulseIn(ECHO_PIN, HIGH);
 return duration * 0.034 / 2;
void loop()// Recursive Function
 float distance = readDistanceCM();
 bool isNearby = distance < 100;</pre>
 digitalWrite(LED, isNearby);
 Serial.print("Measured distance: ");
 Serial.println(distance);
 delay(100);
 if (isNearby == 1){
 PublishData(distance);
 delay(1000);
 if (!client.loop()) {
   mqttconnect();
    .....retrieving to
void PublishData(float distance) {
 mqttconnect();//function call for connecting to ibm
 String payload = "{\"Alert\":""\"";
 payload += distance;
 payload += " is less than 100cms\"";
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
```

```
Serial.println("Publish ok");// if it successfully upload data on the cloud
then it will print publish ok in Serial monitor or else it will print publish
failed
 } else {
   Serial.println("Publish failed");
void mqttconnect() {
 if (!client.connected()) {
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
     initManagedDevice();
     Serial.println();
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
 while (WiFi.status() != WL_CONNECTED) {
   delay(500);
   Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
   Serial.println((subscribetopic));
   Serial.println("subscribe to cmd OK");
 } else {
   Serial.println("subscribe to cmd FAILED");
```

Picture:-



Link:- https://wokwi.com/projects/new/esp32

Cloud output:-

