Delivery of Sprint-2

DATE	17 November 2022		
TEAM ID	PNT2022TMID53817		
PROJECT NAME	SMART WASTE MANAGEMENT FOR METROPOLITAN CITIES		

Code for Data Transfer from Sensors

	#include <wifi.h> #include <pubsubc #include="" 20,="" 4);<="" <liquidcry="" lcd(0x27,="" th=""><th></th><th>uidCrystal_I2C</th><th>// library for wifi // library for MQTT</th><th></th></pubsubc></wifi.h>		uidCrystal_I2C	// library for wifi // library for MQTT		
	//	credentials of I	BM Accounts	<u>-</u>		
#define ORG "el2iyd" #define DEVICE_TYPE "NodeMUC" #define DEVICE_ID "12345" #define TOKEN "12345678"			// Device type mentioned in ibm watson iot platform // Device ID mentioned in ibm watson iot platform			
//	,	customise abo	ve values			
char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name char publishTopic[] = "iot-2/evt/data/fmt/json"; char topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of strings char authMethod[] = "usetoke auth"; // authentication method char token[] = TOKEN;						
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID; //Client id						
	//				-	
WiFiClient wifiClient; PubSubClient client(server, 1883, wifiClient);		// creating instance f	// creating instance for wificlient			
	#define ECHO_PIN #define TRIG_PIN 1 dist;					
	void setup() { Social basin/115200	a).				
	Serial.begin(115200 pinMode(LED_BUIL pinMode(TRIG_PIN pinMode(ECHO_PII //pir pin pinMode(4	TIN, , N, INPUT);	OUTPUT); OUTPUT);			
	//ledpins pinMode OUTPUT); pinMod OUTPUT); pinMod OUTPUT); pinMode OUTPUT);	e(2, e(4,				

```
lcd.init(); lcd.backlight(); lcd.setCursor(1,
0); lcd.print(""); wifiConnect();
mqttConnect();
float readcmCM()
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2); digitalWrite(TRIG_PIN,
HIGH); delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW); int duration =
pulseIn(ECHO_PIN, HIGH); return
duration * 0.034 / 2;
void loop()
lcd.clear();
publishData(); delay(500);
if (!client.loop())
  {
    mqttConnect();
                                                                           // function call to connect to IBM
                                              _-retrieving to cloud_
void wifiConnect()
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
   delay(500);
   Serial.print(".");
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
void mqttConnect()
{
  if (!client.connected())
   {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
     (!client.connect(clientId, authMethod, token))
      {
       Serial.print("."); delay(500);
     initManagedDevice(); Serial.println();
void initManagedDevice()
  if (client.subscribe(topic))
    Serial.println("IBM subscribe to cmd OK");
```

```
else
       Serial.println("subscribe to cmd FAILED");
   void publishData()
   float cm = readcmCM();
    if(digitalRead(34))
                                                                         //PIR motion detection
     Serial.println("Motion
     Detected");
                     Serial.println("Lid
     Opened"); digitalWrite(15, HIGH);
   else
     digitalWrite(15, LOW);
   if(digitalRead(34)== true)
    if(cm <= 100)
                                                                       //Bin level detection
     digitalWrite(2, HIGH);
     Serial.println("High Alert!!!,Trash bin is about to be full");
     Serial.println("Lid Closed"); lcd.print("Full! Don't use"); delay(2000);
                                digitalWrite(4,
         lcd.clear();
                                                      LOW);
     digitalWrite(23, LOW);
   else if(cm > 150 && cm < 250)
     digitalWrite(4, HIGH);
     Serial.println("Warning!!,Trash is about to cross 50% of bin level"); digitalWrite(2,
     digitalWrite(23, LOW);
  else if(cm > 250 && cm <=400)
     digitalWrite(23, HIGH); Serial.println("Bin is
     available"); digitalWrite(2,LOW);
     digitalWrite(4, LOW);
     delay(10000); Serial.println("Lid Closed");
   else
    Serial.println("No motion detected");
   if(cm <= 100)
   digitalWrite(21,HIGH);
   String payload = "{\"High Alert!!\":\"";
   payload += cm; payload
   += "left\" }";
  Serial.print("\n");
   Serial.print("Sending payload: ");
  Serial.println(payload); if (client.publish(publishTopic, (char*) payload.c_str())) // if data is uploaded to cloud successfully,prints publish
ok or prints publish failed
  Serial.println("Publish OK");
```

```
if(cm <= 250)
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist; payload += "left\" }";
Serial.print("\n");
Serial.print("Sending distance: "); Serial.println(cm); if(client.publish(publishTopic,
(char*) payload.c_str()))
Serial.println("Publish OK");
}
else
{
Serial.println("Publish FAILED");
}
}
float inches = (cm / 2.54); //print on LCD lcd.setCursor(0,0); lcd.print("Inches"); lcd.setCursor(4,0);
lcd.setCursor(12,0); lcd.print("cm"); lcd.setCursor(1,1); lcd.print(inches, 1); lcd.setCursor(11,1);
lcd.print(cm, 1); lcd.setCursor(14,1); delay(1000); lcd.clear();
}
```

Connection Diagram

