

TEAM ID : PNT2022TMID16369

PROJECT NAME : AI-powered Nutrition Analyzer for Fitness Enthusiasts

Adding CNN Layers

- For information regarding CNN Layers refer to the link
Link: <https://victorzhou.com/blog/intro-to-cnns-part-1/>
- As the input image contains three channels, we are specifying the input shape as (64,64,3).
- We are adding a two convolution layer with activation function as “relu” and with a small filter size (3,3) and the number of filters (32) followed by a max-pooling layer.
- Max pool layer is used to down sample the input.(Max pooling is a pooling operation that selects the maximum element from the region of the feature map covered by the filter)
- Flatten layer flattens the input. Does not affect the batch size.

Creating the model

```
# Initializing the CNN
classifier = Sequential()

# First convolution Layer and pooling
classifier.add(Conv2D(32, (3, 3), input_shape=(64, 64, 3), activation='relu'))
classifier.add(MaxPooling2D(pool_size=(2, 2)))

# Second convolution Layer and pooling
classifier.add(Conv2D(32, (3, 3), activation='relu'))

# input_shape is going to be the pooled feature maps from the previous convolution Layer
classifier.add(MaxPooling2D(pool_size=(2, 2)))

# Flattening the Layers
classifier.add(Flatten())
```