

Importing required libraries

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from keras_preprocessing.sequence import pad_sequences
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras_preprocessing.sequence import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
import nltk
from nltk.corpus import stopwords
from nltk.stem.porter import PorterStemmer
from nltk.stem import WordNetLemmatizer
import re
%matplotlib inline
```

Reading Dataset

```
data = pd.read_csv("/content/spam.csv", encoding="ISO-8859-1")
data.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 5572 entries, 0 to 5571
Data columns (total 5 columns):
#   Column          Non-Null Count  Dtype
---  -
0   v1               5572 non-null  object
1   v2               5572 non-null  object
2   Unnamed: 2       50 non-null    object
3   Unnamed: 3       12 non-null    object
4   Unnamed: 4        6 non-null     object
dtypes: object(5)
memory usage: 217.8+ KB
```

Data Preprocessing


```
df = data.drop(data[["Unnamed: 2", "Unnamed: 3", "Unnamed: 4"]], axis=1)
df.rename(columns = {"v1": "Target", "v2": "Text"}, inplace = True)
df
```

	Target	Text
0	ham	Go until jurong point, crazy.. Available only ...
1	ham	Ok lar... Joking wif u oni...
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...
3	ham	U dun say so early hor... U c already then say...
4	ham	Nah I don't think he goes to usf, he lives aro...
...
5567	spam	This is the 2nd time we have tried 2 contact u...
5568	ham	Will l_b going to esplanade fr home?
5569	ham	Pity, * was in mood for that. So...any other s...
5570	ham	The guy did some bitching but I acted like i'd...
5571	ham	Rofl. Its true to its name

5572 rows × 2 columns

```
plt.figure(figsize=(6,4))
fg = sns.countplot(x= df["Target"], palette= ["black", "red"] )
fg.set_title("Count Plot of Classes", color="#58508d")
fg.set_xlabel("Classes", color="#58508d")
fg.set_ylabel("Number of Data points", color="#58508d")
```

```
Text(0, 0.5, 'Number of Data points')
```




Double-click (or enter) to edit

```
nltk.download('punkt')
```

```
[nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data]   Unzipping tokenizers/punkt.zip.
True
```

```
df["No_of_Characters"] = df["Text"].apply(len)
```

```
df["No_of_Words"]=df.apply(lambda row: nltk.word_tokenize(row["Text"]), axis=1).apply(len)
df["No_of_sentence"]=df.apply(lambda row: nltk.sent_tokenize(row["Text"]), axis=1).apply(len)
df.describe().T
```

	count	mean	std	min	25%	50%	75%	max	
No_of_Characters	5572.0	80.118808	59.690841	2.0	36.0	61.0	121.0	910.0	
No_of_Words	5572.0	18.695621	13.742587	1.0	9.0	15.0	27.0	220.0	
No_of_sentence	5572.0	1.970747	1.417778	1.0	1.0	1.0	2.0	28.0	

```
df.head()
```

	Target	Text	No_of_Characters	No_of_Words	No_of_sentence
0	ham	Go until jurong point, crazy.. Available only ...	111	24	2
1	ham	Ok lar... Joking wif u oni...	29	8	2
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	155	37	2
3	ham	U dun say so early hor... U c already then say...	49	13	1

```
plt.figure(figsize=(18,12))
fg = sns.pairplot(data=df, hue="Target",palette=["green","red"])
plt.show(fg)
```

<Figure size 1296x864 with 0 Axes>



```
def Clean(Text):
    sms = re.sub('[^a-zA-Z]', ' ', Text)
    sms = sms.lower() #converting to lowercase
    sms = sms.split()
    sms = ' '.join(sms)
    return sms
df["Clean_Text"] = df["Text"].apply(Clean)
df["Tokenize_Text"] = df.apply(lambda row: nltk.word_tokenize(row["Clean_Text"]), axis=1)
nltk.download('stopwords')

[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data]   Unzipping corpora/stopwords.zip.
True

def remove_stopwords(text):
    stop_words = set(stopwords.words("english"))
    filtered_text = [word for word in text if word not in stop_words]
    return filtered_text
df["Nostopword_Text"] = df["Tokenize_Text"].apply(remove_stopwords)
nltk.download('wordnet')

[nltk_data] Downloading package wordnet to /root/nltk_data...
True

nltk.download('omw-1.4')

[nltk_data] Downloading package omw-1.4 to /root/nltk_data...
True

lemmatizer = WordNetLemmatizer()
def lemmatize_word(text):
    lemmas = [lemmatizer.lemmatize(word, pos='v') for word in text]
    return lemmas
df["Lemmatized_Text"] = df["Nostopword_Text"].apply(lemmatize_word)
corpus= []
for i in df["Lemmatized_Text"]:
    msg = ' '.join([row for row in i])
    corpus.append(msg)
corpus[:5]

['go jurong point crazy available bugis n great world la e buffet cine get amore
wat',
'ok lar joke wif u oni',
'free entry wkly comp win fa cup final tkts st may text fa receive entry question
std txt rate c apply',
```

```
'u dun say early hor u c already say',
'nah think go usf live around though']
df.tail()
```

	Target	Text	No_of_Characters	No_of_Words	No_of_sentence	Clean_Text	T
5567	spam	This is the 2nd time we have tried 2 contact u...	161	35	4	this is the nd time we have tried contact u u ...	
5568	ham	Will i_b going to esplanade fr home?	37	9	1	will b going to esplanade fr home	
5569	ham	Pity, * was in mood for that. So...any other s...	57	15	2	pity was in mood for that so any other suggest...	
5570	ham	The guy did some bitching but I acted like	125	27	1	the guy did some bitching but i acted like i d...	

```
X = df.Clean_Text
Y = df.Target
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

Layers

```
def RNN():
    inputs = Input(name='inputs',shape=[max_len])
    layer = Embedding(max_words,50,input_length=max_len)(inputs)
    layer = LSTM(64)(layer)
    layer = Dense(256,name='FC1')(layer)
```

```

layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
return model

```

Compiling

```

model = RNN()
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])

```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	500000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_1 (Activation)	(None, 1)	0
Total params: 96,337		
Trainable params: 96,337		
Non-trainable params: 0		

Fill model

```
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=15,validation_split=0.2,callbacks=callbacks)
```

```

Epoch 1/15
30/30 [=====] - 1s 17ms/step - loss: 0.0427 - accuracy: 0.95
Epoch 2/15
30/30 [=====] - 0s 13ms/step - loss: 0.0301 - accuracy: 0.97
<keras.callbacks.History at 0x7f5ac6ecddd0>


```



Save model

```
model.save('lstm_model')
```

```
WARNING:absl:Found untraced functions such as lstm_cell_layer_call_fn, lstm_cell_la
```



Test model

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 0s 6ms/step - loss: 0.0591 - accuracy: 0.9
```

