


ASSIGNMENT 4

Assignment date	20 oct 2022
Student name	C.jeevan kumar
Student rollno	312819106016
Marks	2 Marks

INPUT:



CODE:

```
#include <stdio.h>
#include <stdbool.h>
#include <freertos/FreeRTOS.h>
#include <freertos/task.h>
#include <esp_err.h>

#include "ultrasonic.h"

#define ECHO_GPIO 12
```

```
#define TRIGGER_GPIO 13
```

```
#define MAX_DISTANCE_CM 500 // Maximum of 5 meters
```

```

void ultrasonic_test(void *pvParameters)
{
    float
    distance;

    ultrasonic_sensor_t sensor = {
    .trigger_pin = TRIGGER_GPIO,
    .echo_pin = ECHO_GPIO
    };

    ultrasonic_init(&sensor);

    while (true) {
        esp_err_t res = ultrasonic_measure(&sensor,
        MAX_DISTANCE_CM, &distance);

        if (res == ESP_OK) {
            printf("Distance: %0.04f m\n", distance);
        } // Print error
        else {
            printf("Error %d: ", res);
            switch (res) {
            case ESP_ERR_ULTRASONIC_PING:
                printf("Cannot ping (device is in invalid state)\n");
            break;
            case ESP_ERR_ULTRASONIC_PING_TIMEOUT:
                printf("Ping timeout (no device found)\n");
            break;
            case ESP_ERR_ULTRASONIC_ECHO_TIMEOUT:
                printf("Echo timeout (i.e. distance too big)\n");
            break;
            default:

```

```


        printf("%s\n", esp_err_to_name(res));
    }
}

vTaskDelay(pdMS_TO_TICKS(500));
}
}

void app_main()
{
    xTaskCreate(ultrasonic_test,
"ultrasonic_test",
configMINIMAL_STACK_SIZE * 3, NULL, 5, NULL);
}

```

OUTPUT:



main.cdiagram.jsonultrasonic.hultrasonic.cesp_idf_lib_helpers.h

Library Manager

```
15 float distance;
16
17 ultrasonic_sensor_t sensor = {
18     .trigger_pin = TRIGGER_GPIO,
19     .echo_pin = ECHO_GPIO
20 };
21
22 ultrasonic_init(&sensor);
23
24 while (true) {
25     esp_err_t res = ultrasonic_measure(&sensor, MAX_DISTANCE_CM, &di
26
27     if (res == ESP_OK) {
28         printf("Distance: %0.04f m\n", distance);
29     } // Print error
30     else {
31         printf("Error %d: ", res);
32         switch (res) {
33             case ESP_ERR_ULTRASONIC_PING:
34                 printf("Cannot ping (device is in invalid state)\n");
35                 break;
36             case ESP_ERR_ULTRASONIC_PING_TIMEOUT:
37                 printf("Ping timeout (no device found)\n");
38                 break;
39             case ESP_ERR_ULTRASONIC_ECHO_TIMEOUT:
40                 printf("Echo timeout (i.e. distance too big)\n");
```

Simulation

00:10.517 76%

Editing Ultrasonic Distance Sensor

Distance: 337cm

Distance: 3.4176 m
Distance: 3.4176 m
Distance: 3.4176 m
Distance: 3.4174 m
Distance: 3.4174 m
Distance: 3.4174 m
Distance: 3.4174 m