DEVELOP A PYTHON SCRIPT

<u>Date</u>	11 November 2022
<u>Team ID</u>	PNT2022TMID09351
<u>Project Name</u>	Signs with Smart Connectivityfor Better Road Safety
<u>Maximum Marks</u>	4 Marks

CODE:

```
#include <TinyGPS++.h>
#include <SoftwareSerial.h>
TinyGPSPlus gps;
SoftwareSerial ss (3,4);
char n;
int a;
void setup() {
Serial.begin(9600);
ss.begin(9600);
pinMode (2, INPUT):
pinMode (6, OUTPUT);
pinMode(11, OUTPUT);
pinMode(10, OUTPUT);
pinMode (9, OUTPUT);
pinMode (12, OUTPUT); //apr
digitalWrite(11,HIGH);
digitalWrite(6,HIGH);
attachInterrupt (digitalPinToInterrupt (2), piezo,CHANGE);
}
void loop() {
n-Serial.read();
// Serial.println(" ");
delay (200);
if (n=='3') {
digitalWrite(6,HIGH);
digitalWrite(11,HIGH);
digitalWrite(12,HIGH);
delay(200);
digitalWrite(12,LOW);
} else if (n=='2')
digitalWrite(6,LOW);
digitalWrite(11,LOW);
digitalWrite(10,LOW);
digitalWrite(9,LOW);
digitalWrite(12,HIGH);
delay(200);
digitalWrite(12,LOW);
} else if (n=='1')
```

analogWrite(11,100);

```
analogWrite(6,100);
digitalWrite(12,HIGH);
delay(200);
digitalWrite(12,LOW);
// while (ss.available() > 0)
// if (gps.encode(ss.read()))
// displayInfo();
void displayInfo()
// Serial.print (F("Location: "));
if (gps.location.isValid())
Serial.print(gps.location.lat(), 6);
Serial.print (F(","));
Serial.print(gps.location. Ing(), 6); }
// Serial.print (F ("INVALID"));
Serial.print("10.305125");
Serial.print(',');
Serial.print("76.389582");
/* Serial.print(F(" Date/Time: "));
if (gps.date.isValid())
Serial.print(gps.date.month());
Serial.print (F("/"));
Serial.print(gps.date.day());
Serial.print (F("/"));
Serial.print(gps.date.year());
}
else
Serial.print(F("INVALID"));
Serial.print (F(" "));
if (gps.time.isValid())
if (gps.time.hour() < 10) Serial.print (F("0"));
Serial.print(gps.time.hour());
Serial.print (F(":"));
if (gps.time.minute() < 10) Serial.print(F("0"));</pre>
Serial.print (gps.time.minute());
Serial.print (F(":"));
if (gps.time.second() < 10) Serial.print(F("0"));
Serial.print(gps.time.second());
Serial.print (F("."));
if (gps.time.centisecond() < 10) Serial.print(F("0"));
Serial.print(gps.time.centisecond());
}
else
// Serial.print (F("INVALID"));
}*/
Serial.println();
```