

Source code 1

Python code

```
import time
import sys
import ibmiotf.application # to install pip install ibmiotf
import ibmiotf.device

#Provide your IBM Watson Device Credentials
organization = "kdldkd" #replace the ORG ID
deviceType = "smartcropprotection123"#replace the Device type with
deviceId = "87654321"#replace Device ID
authMethod = "token"
authToken = "12345678" #Replace the authToken

def myCommandCallback(cmd): # function for Callback
    print("Command received: %s" % cmd.data)
    if cmd.data['command']=='motoron':
        print("Motor On IS RECEIVED")

    elif cmd.data['command']=='motoroff':
        print("Motor Off IS RECEIVED")

    if cmd.command == "setInterval":
```

```

        if 'interval' not in cmd.data:
            print("Error - command is missing required
information: 'interval'")
        else:
            interval = cmd.data['interval']
    elif cmd.command == "print":
        if 'message' not in cmd.data:
            print("Error - command is missing required
information: 'message'")
        else:
            output=cmd.data['message']
            print(output)

try:
    deviceOptions = {"org": organization, "type": deviceType, "id":
deviceId, "auth-method": authMethod, "auth-token": authToken}
    deviceCli = ibmiotf.device.Client(deviceOptions)
    #.....

except Exception as e:
    print("Caught exception connecting device: %s" % str(e))
    sys.exit()

# Connect and send a datapoint "hello" with value "world" into the
cloud as an event of type "greeting" 10 times

```

```
deviceCli.connect()
```

```
while True:
```

```
    deviceCli.commandCallback = myCommandCallback
```

```
# Disconnect the device and application from the cloud
```

```
deviceCli.disconnect()
```