Project development phase
Sprint - II

Date	04 November 2022
Team ID	PNT2022TMID13566
Project Name	Project - Industry-specific intelligent fire management system
Maximum Marks	20 marks

LINK: https://wokwi.com/projects/348062828084593236

OUTPUT:


IBM-Project-2847-1658484090/Sprint
sketch.ino - Wokwi Arduino and
New Issue · IBM-EPBL/IBM-Project-28
wokwi.com/projects/348062828084593236
WOKWI
SAVE
SHARE
sketch.ino
Docs
M
sketch.ino
diagram.json
libraries.txt
Library Manager
Simulation
00:07.280
101%
ESP32
#include <time.h>
#include <WiFi.h>
#include <PubSubClient.h>
#define ORG "pq685h"
#define DEVICE_TYPE "NodeMCU"
#define DEVICE_ID "12345"
#define TOKEN "12345678"
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/data/fmt/json";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, wifiClient);
float temperature = 0;
int gas = 0;
int flame = 0;
String flame_status = "";
String Gas_status = "";
String exhaust_fan_status = "";
String sprinkler_status = "";
void setup() {
Serial.begin(99900);
wifiConnect();
Connecting to Wifi...WiFi connected, IP address: 10.10.0.2
Reconnecting MQTT client to pq685h.messaging.internetofthings.ibmcloud.com
Publish OK
Publish OK
Publish OK
Publish OK
Publish OK
Type here to search
ENG
20:55
13-11-2022

CODE:

```
#include <time.h>
#include <WiFi.h>
#include <PubSubClient.h>

#define ORG "pq685h"
#define DEVICE_TYPE "NodeMCU"
#define DEVICE_ID "12345"
#define TOKEN "12345678"

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/data/fmt/json";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;

WiFiClient wifiClient;
PubSubClient client(server, 1883, wifiClient);

float temperature  = 0;
int gas = 0;
```

```
int flame = 0;

String flame_status = "";
String Gas_status = "";
String exhaust_fan_status = "";
String sprinkler_status = "";


void setup() {
  Serial.begin(99900);
   wifiConnect();
   mqttConnect();
}

void loop() {

  srand(time(0));

    //initial variables and random generated data

    temperature = random(-20,125);
    gas = random(0,1000);
    int flamereading = random(200,1024);
    flame = map(flamereading,200,1024,0,2);
```

```
//set a flame status

switch (flame) {
case 0:
    flame_status = "No Fire";
    break;
case 1:
    flame_status = "Fire is Detected";
    break;
}

//send the sprinkler status

if(flame==1){
    sprinkler_status = "Working";
}
else{
    sprinkler_status = "Not Working";

}

//toggle the fan according to gas reading
```

```
if(gas > 100){
    Gas_status = "Gas Leakage is Detected";
    exhaust_fan_status = "Working";

}
else{
    Gas_status = "No Gas Leakage is Detected";
    exhaust_fan_status = "Not Working";
}

//json format for IBM Watson

String payload = "{";
payload+="\"gas\":";
payload+=gas;
payload+=",";
payload+="\"temperature\":";
payload+=(int)temperature;
payload+=",";
payload+="\"flame\":";
payload+=flamereading;
payload+=",";
payload+="\"fire_status\":\""+flame_status+"\",";
payload+="\"sprinkler_status\":\""+sprinkler_status+"\",";
```

```
    payload+="\"Gas_status\":\""+Gas_status+"\",";
    payload+="\"exhaust_fan_status\":\""+exhaust_fan_status+"\"}";

    if(client.publish(publishTopic, (char*) payload.c_str()))
    {
        Serial.println("Publish OK");
    }
    else{
        Serial.println("Publish failed");
    }
    delay(1000);


    if (!client.loop())
    {
      mqttConnect();
    }
}


void wifiConnect()
{
  Serial.print("Connecting to ");
  Serial.print("Wifi");
```

```
  WiFi.begin("Wokwi-GUEST", "", 6);
  while (WiFi.status() != WL_CONNECTED)
  {
    delay(500);
    Serial.print(".");
  }
  Serial.print("WiFi connected, IP address: ");
  Serial.println(WiFi.localIP());

}


void mqttConnect()
{
  if (!client.connected())
  {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    while (!client.connect(clientId, authMethod, token))
    {
      Serial.print(".");
      delay(500);
    }
```

```
    Serial.println();
  }
}
```