SPRINT 2

Date	12 November 2022
Team ID	PNT2022TMID13627
Project Name	Smart Waste Management System for Metropolitan cities

CODE FOR DETECTING BIN LEVEL AND DISPLAYING IT IN IBM CLOUD:

esp32-dht22.ino:


```
#include <WiFi.h>
#include <PubSubClient.h>
#include <LiquidCrystal_IZC.h>
LiquidCrystal_IZC lcd(0x27, 20, 4);
                                                                                     // library for wifi
// library for MQTT
   //---- credentials of IBM Accounts ----
  #define ORG "mldk59" // IBM organisation id #define DEVICE_TYPE "pythoncode" // Device type mentioned in ibm
   watson iot platform
#define DEVICE_ID "252525"  // Device ID mentioned in ibm watson iot
   platform
#define TOKEN "QZqODYo6U*Q6b+IpuC" // Token
  //----- customise above values -----
  char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name char publishTopic[] = "iot-2/evt/data/fmt/json"; // topic name and type of event perform and format in which data to be send char topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of strings char authMethod[] = "use-token-auth"; // authentication method char token[] = TOKEN:
  char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID; //Client id
  WiFiClient wifiClient; // creating instance for wificlient PubSubClient client(server, 1883, wifiClient);
  #define ECHO_PIN 12
#define TRIG_PIN 13
  float dist;
  void setup()
 void setup()
Serial.begin(115200);
pinMode(LED_BUILTIN, OUTPUT);
pinMode(ECHO_PIN, INPUT);
pinMode(ECHO_PIN, INPUT);
//pir pin
pinMode(34, INPUT);
     //ledpins
     pinMode(23, OUTPUT);
pinMode(2, OUTPUT);
pinMode(4, OUTPUT);
pinMode(15, OUTPUT);
     lcd.init();
     lcd.backlight();
     lcd.setCursor(1, 0);
lcd.print("");
wifiConnect();
     mqttConnect();
float readcmCM()
   digitalWrite(TRIG_PIN, LOW);
   delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
   delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
void loop()
{
```

```
lcd.clear();
  publishData();
delay(500);
if (!client.loop())
    {
    mqttConnect();
nnect to IBM
                                                                                         // function call to
/* -----retrieving to cloud------*/
void wifiConnect()
 Serial.print("Connecting to ");
Serial.print("Wiffi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != ML_CONNECTED)
{
    delay(500);
    Serial.print(".");
}
   Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
void mqttConnect()
  {
   if (!client.connected())
                   {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    while (!client.connect(clientId, authMethod, token))
    ,
}
                          {
   Serial.print(".");
   delay(500);
                  initManagedDevice();
Serial.println();
}
          void initManagedDevice()
{
               if (client.subscribe(topic))
                   {
   Serial.println("IBM subscribe to cmd OK");
                  {
    Serial.println("subscribe to cmd FAILED");

          void publishData()
             float cm = readcmCM();
            if(digitalRead(34))
                                                                                               //pir motion detection
            {
    Serial.println("Motion Detected");
    Serial.println("Lid Opened");
    digitalWrite(15, HIGH);
           if(digitalRead(34)== true)
           {
  if(cm <= 60)</pre>
         detection
           etection
{
    digitalWrite(2, HIGH);
    Serial.println("High Alert!!!,Trash bin is about to be full");
    Serial.println("Lid Closed");
    lcd.print("Full! Don't use");
    delay(2000);
               lcd.clear();
digitalWrite(4, LOW);
digitalWrite(23, LOW);
             } else if(cm > 60 && cm < 120)
               digitalWrite(4, HIGH);
Serial.println("Warning!!,Trash is about to cross 50% of bin level");
digitalWrite(2, LOW);
digitalWrite(23, LOW);
             } else if(cm > 120)
```

```
digitalWrite(23, HIGH);
Serial.println("Bin is available");
digitalWrite(2,LOW);
digitalWrite(4, LOW);
     delay(10000);
Serial.println("Lid Closed");
Serial...
} else
{
Serial.println("No motion detected");
digitalWrite(2, LOW);
digitalWrite(15, LOW);
digitalWrite(4, LOW);
digitalWrite(4, LOW);
}
}
           digitalWrite(15, LOW);
     }
 if(cm <= 60)
{
digitalWrite(21,HIGH);
String payload = "{\"High_Alert\":";</pre>
payload += cm;
payload += " )";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.print(n(payload);
  if \ (client.publish(publishTopic, \ (char^*) \ payload.c\_str())) \\  // \ if \ data \ is uploaded to cloud successfully,prints publish ok else prints publish failed 
 {
Serial.println("Publish OK");
 else if(cm <= 120)
{
         digitalWrite(22,HIGH);
String payload = "(\"Warning\":";
payload *= cm ;
payload *= " ";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.print(payload);
if(client.publish(publishTopic, (char*) payload.c_str()))
           {
Serial println("Publish OK");
           Serial.println("Publish FAILED");
           else
           Serial.println();
}
                float inches = (cm / 2.54);
                                                                                                                                                              //print on lcd
               loat inches = (cm /
lod.setCursor(0,0);
lod.print("Inches");
lod.setCursor(4,0);
lod.setCursor(12,0);
               icd.setcursor(12,0);
lcd.print("cm");
lcd.setCursor(1,1);
lcd.print(inches, 1);
lcd.setCursor(11,1);
lcd.print(cm, 1);
```

CIRCUIT DIAGRAM:



IBM WATSON IOT PLATFORM OUTPUT:

