

MAHENDRA ENGINEERING COLLEGE FOR WOMEN

NAME:SOUNDARYA.N

SUB:IBM

REG

NO:611419106064

ASSIGNMENT -3

import

numpy as np

import pandas as pd

from PIL import ImageFile

from tqdm import tqdm

import h5py

import cv2

import matplotlib.pyplot as plt

%matplotlib inline

import seaborn as sns

from sklearn.model_selection import train_test_split

from sklearn.metrics import confusion_matrix

from sklearn.metrics import plot_confusion_matrix

from tensorflow.keras.utils import to_categorical

from tensorflow.keras.preprocessing import image as keras_image

from tensorflow.keras.models import Sequential, load_model

from tensorflow.keras.layers import Dense

```
from tensorflow.keras.layers import Activation, Dropout

from tensorflow.keras.layers import Conv2D, MaxPooling2D, GlobalMaxPooling2D

from tensorflow.keras.callbacks import ReduceLROnPlateau, ModelCheckpoint

from tensorflow.keras.layers import LeakyReLU

def model():

    model = Sequential()

    model.add(Conv2D(128, (3, 3), input_shape=x_train.shape[1:]))

    model.add(LeakyReLU(alpha=0.02))

    model.add(MaxPooling2D(pool_size=(2, 2)))

    model.add(Dropout(0.25))

    model.add(Conv2D(128, (3, 3)))

    model.add(LeakyReLU(alpha=0.02))

    model.add(MaxPooling2D(pool_size=(2, 2)))

    model.add(Dropout(0.25))

    model.add(GlobalMaxPooling2D())

    model.add(Dense(512))

    model.add(LeakyReLU(alpha=0.02))

    model.add(Dropout(0.5))
```

```
model.add(Dense(10))

model.add(Activation('softmax'))


model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])


return model


model = model()


# To save the best model
checkpointer = ModelCheckpoint(filepath='weights.best.model.hdf5', verbose=2, save_best_only=True)


# To reduce learning rate dynamically
lr_reduction = ReduceLROnPlateau(monitor='val_loss', patience=5, verbose=2, factor=0.2)


# Train the model
history = model.fit(x_train, y_train, epochs=75, batch_size=32, verbose=2,
                    validation_data=(x_valid, y_valid),
                    callbacks=[checkpointer,

data_generator = keras_image.ImageDataGenerator(shear_range=0.3,
                                                zoom_range=0.3,
                                                rotation_range=30,
                                                horizontal_flip=True)


dg_history = model.fit_generator(data_generator.flow(x_train, y_train, batch_size=64),
                                steps_per_epoch = len(x_train)//64, epochs=7, verbose=2,
```

```
validation_data=(x_valid, y_valid),  
callbacks=[checkpointer,lr_reduction])
```