## PROJECT DEVELOPMENT PHASE SPRINT-3

Date	05 NOVEMBER 2022
Team ID	PNT2022TMID4166
Project Name	Hazardous Area Monitoring for Industrial Plant powered by IoT
Maximum Marks	4 Marks

## CODE:

```
#include <WiFi.h>
#include < PubSubClient.h>
#include <DHT.h>
WiFiClient wifiClient;
String data3;
#define DHTTYPE DHT11
#define DHTPIN 4
#define MQTPIN 34
DHT dht(DHTPIN, DHTTYPE);
#define ORG "v6wg8x"
#define DEVICE_TYPE "projectFinal"
#define DEVICE_ID "FinalDeliverable"
#define TOKEN "A1ymH))p*JB&iMWNpY"
#define speed 0.034
void callback(char* topic, byte* playload, unsigned int payloadLength);
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char topic[] = "iot-2/cmd/test/fmt/String";
char authMethod[] = "use-token-auth";
```

```
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
PubSubClient client(server, 1883, callback, wifiClient);
void publishData();
String command;
String data = "";
long duration;
float dist;
void setup()
 Serial.begin(115200);
 dht.begin();
 wifiConnect();
 mqttConnect();
}
void loop() {
 publishData();
 delay(500);
 if (!client.loop()) {
  mqttConnect();
 }
}
void wifiConnect() {
 Serial.print("Connecting to "); Serial.print("Wifi");
 WiFi.begin("JerroldWi-Fi","75779901");
 while (WiFi.status() != WL_CONNECTED) {
```

```
delay(500);
  Serial.print(".");
 Serial.print("WiFi connected, IP address: "); Serial.println(WiFi.localIP());
}
void mqttConnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting MQTT client to "); Serial.println(server);
  while (!client.connect(clientId, authMethod, token)) {
  Serial.print(".");
   delay(500);
  }
  initManagedDevice();
  Serial.println();
}
void initManagedDevice() {
 if (client.subscribe(topic)) {
  Serial.println("IBM subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
 }
}
void publishData()
 int sensorValue = analogRead(MQTPIN); //MQT 135 connected to GPIO 34 (Analog ADC1_CH6)
 Serial.print("AirQua=");
 Serial.print(sensorValue, DEC);
 Serial.println(" PPM");
 float humid = dht.readHumidity();
 float temp = dht.readTemperature(true);
```

```
String payload = "{\"Humidity\":";
 payload += humid;
 payload += "}";
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish OK");
 }
 payload = "{\"Temperature\":";
 payload += temp;
 payload += "}";
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish OK");
 }
 payload = "{\"Air Quality\":";
 payload += String(sensorValue);
 payload += "}";
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish OK");
 }
}
void callback(char* subscribeTopic, byte* payload, unsigned int payloadLength) {
 Serial.print("callback invoked for topic:");
 Serial.println(subscribeTopic);
 for (int i = 0; i < payloadLength; i++) {
  dist += (char)payload[i];
 }
 Serial.println("data:" + data3);
 if (data3 == "lighton") {
 Serial.println(data3);
 data3 = "";
```