

## ASSIGNMENT-4

DOMAIN : IOT

NAME : VARSHETHA.I

REGISTER NUMBER : 714019106119

COLLEGE : SRI SHAKTHI INSTITUTE OF ENGINEERING AND TECHNOLOGY

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events. Upload document with wokwi share link and images of IBM cloud

### Solution:

```
#include <WiFi.h>
#include
<PubSubClient.h>
#include
<ArduinoJson.h>

WiFiClient

wifiClient;#define

ORG "kr9fjo"
#define DEVICE_TYPE "TestDeviceType"
#define DEVICE_ID "12345"
#define TOKEN "VJsSC148dk1dCN3UqS"
#define speed 0.034

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/abcd_1/fmt/json";
char topic[] = "iot-
2/cmd/home/fmt/String";char authMethod[]
= "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
PubSubClient client(server, 1883,
wifiClient);void publishData();

const int
trigpin=5; const
int echopin=18;
String command;
String data="";
String
lat="14.167589";
String
lon="80.248510";
```

```

String
name="point2";
String icon="";

long
duration;
int dist;

    void setup()
{

Serial.begin(115200);
pinMode(trigpin, OUTPUT);
pinMode(echopin, INPUT);
wifiConnect();
mqttConnect();
}

void loop() {

    publishData
    ();
    delay(500);

    if
        (!client.loop())
        {mqttConnect();
        }
}

void wifiConnect() {
    Serial.print("Connecting to ");
    Serial.print("Wifi");WiFi.begin("Wokwi-GUEST", "",
6);
    while (WiFi.status() != WL_CONNECTED)
        {delay(500);
        Serial.print(".");
        }
    Serial.print("WiFi connected, IP address: "); Serial.println(WiFi.localIP());
}

void mqttConnect() {
    if (!client.connected()) {
        Serial.print("Reconnecting MQTT client to "); Serial.println(server);
        while (!client.connect(clientId, authMethod, token)) {
            Serial.print(".");
            delay(1000);
        }
        initManagedDevice();
        Serial.println();
    }}

```

```

void initManagedDevice() {
    if (client.subscribe(topic)) {
        Serial.println(client.subscribe(topic));
        Serial.println("subscribe to cmd OK");
    } else {
        Serial.println("subscribe to cmd FAILED");
    }
}

void publishData()
{
    digitalWrite(trigpin, LOW);

    digitalWrite(trigpin, HIGH);
    delayMicroseconds(10);
    digitalWrite(trigpin, LOW);
    duration=pulseIn(echopin, HIGH);
    dist=duration*speed/2;

    if(dist<100){
        dist=100-
        dist;
        icon="fa-
        trash";
    }else{
        dist=0;
        icon="fa-trash-o";
    }
    DynamicJsonDocument
    doc(1024);String payload;
    doc["Name"]=name;
    doc["Latitude"]=lat;
    doc["Longitude"]=lon;
    doc["Icon"]=icon;
    doc["FillPercent"]=dist;
    serializeJson(doc,
    payload); delay(3000);
    Serial.print("\n");
    Serial.print("Sending payload: ");
    Serial.println(payload);
    if (client.publish(publishTopic, (char*) payload.c_str())) {
        Serial.println("Publish OK");
    } else {
        Serial.println("Publish FAILED");
    }
}


```

## OUTPUT:

```

1  #include <WiFi.h>
2  #include <PubSubClient.h>
3  #include <ArduinoJson.h>
4
5  WiFiClient wifiClient;
6
7  #define ORG "kr9fjo"
8  #define DEVICE_TYPE "TestDeviceType"
9  #define DEVICE_ID "12345"
10 #define TOKEN "VjSSC148dK1dCN3uq5"
11 #define speed 0.034
12
13 char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
14 char publishTopic[] = "iot-2/evt/abcd_1/fmt/json";
15 char topic[] = "iot-2/cmd/home/fmt/String";
16 char authMethod[] = "use-token-auth";
17 char token[] = TOKEN;
18 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
19 PubSubClient client(server, 1883, wifiClient);
20 void publishData();
21
22 const int trigpin=5;
23 const int echopin=18;
24 String command;
25 String data="";
26 String lata="14.167589";
27 String lon="80.248510";
28 String name="point2";
29 String icon="";
30
31 long duration;
32 int dist;
33
34 void setup()
35 {
36   Serial.begin(115200);
37   pinMode(trigpin, OUTPUT);
38   pinMode(echopin, INPUT);

```



| Device ID | Status       | Device Type | Class ID | Date Added           | Descriptive Location |
|-----------|--------------|-------------|----------|----------------------|----------------------|
| 12345     | Disconnected | RaspberryPi | Device   | Oct 29, 2022 8:53 PM |                      |

| Event       | Value           | Format | Last Received     |
|-------------|-----------------|--------|-------------------|
| Ultra_Sonic | {"Distance":29} | json   | a few seconds ago |
| Ultra_Sonic | {"Distance":92} | json   | a few seconds ago |
| Ultra_Sonic | {"Distance":86} | json   | a few seconds ago |
| Ultra_Sonic | {"Distance":62} | json   | a few seconds ago |
| Ultra_Sonic | {"Distance":10} | json   | a few seconds ago |

1 Simulation running