TEAM ID:	PNT2022TMID44437
PROJECT NAME:	Smart Farmer-IOT Enabled
	Smart Farming Application

FINAL CODE:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include "DHT.h"// Library for dht11
#define DHTPIN 15 // what pin we're connected to
#define DHTTYPE DHT22 // define type of sensor DHT 11
#define LED 2
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin
and typr of dht connected
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "i3869j"//IBM ORGANITION ID
#define DEVICE_TYPE "abcd"//Device type mentioned in ibm watson
IOT Platform
#define DEVICE ID "1234"//Device ID mentioned in ibm watson IOT
Platform
#define TOKEN "12345678"
                             //Token
String data3;
float h. t:
//----- Customise the above values -----
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";//
Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type
of event perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd
REPRESENT command type AND COMMAND IS TEST OF
FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
```

```
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client
id
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
  dht.begin();
 pinMode(LED,OUTPUT);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
void loop()// Recursive Function
 h = dht.readHumidity();
 t = dht.readTemperature();
 Serial.print("temp:");
 Serial.println(t);
 Serial.print("Humid:");
 Serial.println(h);
 PublishData(t, h);
 delay(1000);
 if (!client.loop()) {
  mqttconnect();
/*....retrieving to Cloud....*/
```

```
void PublishData(float temp, float humid) {
 mqttconnect();//function call for connecting to ibm
   creating the String in in form JSon to update the data to ibm cloud
 String payload = "{\"temp\":";
 payload += temp;
 payload += "," "\"Humid\":";
  payload += humid;
 payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c str())) {
  Serial.println("Publish ok");// if it successfully upload data on the
cloud then it will print publish ok in Serial monitor or else it will print
publish failed
 } else {
  Serial.println("Publish failed");
}
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
  while (!!!client.connect(clientId, authMethod, token)) {
   Serial.print(".");
      delay(500);
   initManagedDevice();
   Serial.println();
void wificonnect() //function defination for wificonnect
```

```
Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to
establish the connection
 while (WiFi.status() != WL_CONNECTED) {
  delay(500);
  Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
}
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; <math>i++) {
  //Serial.print((char)payload[i]);
  data3 += (char)payload[i];
 Serial.println("data: "+ data3);
 if(data3=="lighton")
Serial.println(data3);
digitalWrite(LED,HIGH);
 else
Serial.println(data3);
```

```
digitalWrite(LED,LOW);
}
data3="";
}
```