SOURCE CODE

```
import time
import sys
import ibmiotf.application
import ibmiotf.device
import random
#Provide your IBM Watson Device Credentials organization = "udjkcs"
deviceType = "1234" deviceId
= "1234567" authMethod = "token"
authToken = "123456789"# Initialize GPIO

def myCommandCallback(cmd):
print("Command received: %s" % cmd.data['command'])
status=cmd.data['command']
if status=="lighton":
print ("led is on")
elif status == "lightoff":
print ("led is off")else :
print ("please send proper command")#print(cmd)

try:
deviceOptions = {"org": organization, "type": deviceType, "id": deviceId, "auth-
method":
```

```
authMethod, "auth-token": authToken}
deviceCli = ibmiotf.device.Client(deviceOptions)#.....

except Exception as e:
print("Caught exception connecting device: %s" % str(e))sys.exit()


# Connect and send a datapoint "hello" with value "world" into the cloud as an
event of type "greeting"10 times deviceCli.connect()

while True:
#Get Sensor Data from DHT11

temp=random.randint(0,100) Humid=random.randint(0,100)
pH=random.randint(0,14)

data = { 'temp' : temp, 'Humid': Humid ,'pH' : pH }#print data
def myOnPublishCallback():
print ("Published Temperature = %s C" % temp, "Humidity = %s %%" % Humid,
"pHValue =
%s" % pH,  "to IBM Watson")

success = deviceCli.publishEvent("IoTSensor", "json", data, qos=0,
on_publish=myOnPublishCallback)
if not success:
```

```
print("Not connected to IoTF")time.sleep(10)


deviceCli.commandCallback = myCommandCallback
```

```
        # Disconnect the device and application from the cloud
deviceCli.disconnect()
```