

CODING AND SOLUTIONING

(Code Layout, Reliability, Reusability)

Date	13 November 2022
Team ID	PNT2022TMID17260
Project Name	Real-Time River Water Quality Monitoring and Control System
Maximum Mark	2 Marks

KEY IDEA 1 - Code should be easy to understand.

KEY IDEA 2 - Code should be written to maximize the usage for as many applications as possible

Naming Convention:

KEY IDEA 3 -

- Choosing specific words
- Avoiding generic names (or knowing when to use them)
- Using concrete names instead of abstract names
- Attaching extra information to a name, by using a suffix or prefix
- Deciding how long a name should be
- Using name formatting to pack extra information

Choose Specific Words

You have to choose the words that are very specific and avoiding 'empty' words. For example, the word **get** is very unspecific, as in this example: `def GetPage(url):`

The word `GetPage()` doesn't really say much. Does this method get a page from a local cache, from a database, or from the Internet? If it's from the Internet, a more specific name might be `FetchPage()` or `DownloadPage()`

The name `Size()` doesn't convey much information. A more specific name would be `Height()`, `NumNodes()`, `MemoryBytes()`, etc.

The name `Stop()` is okay, but depending on what exactly it does, there might be a more specific name: `Kill()` if it's a heavyweight operation that can't be undone. `Pause()` if there is a way to `Resume()` it.

Finding more colourful words

Don't be afraid to use a thesaurus or ask a friend for better name suggestions. English is a rich language, and there are a lot of words to choose from.

send ~ deliver, dispatch, announce, distribute, route find ~ search, extract, locate, recover start ~ launch, create, begin, open make ~ create, set up, build, generate, compose, add, new

KEY IDEA 4 - It's better to be clear and precise than to be cute.

Avoid Generic Names like tmp and retval

Instead of using an empty name like this, **pick a name that describes the entity's value or purpose**

Using a generic name sometimes will help you to detect a bug **tmp or**

temp

```
if (right < left) { tmp
= right; right =
left; left = tmp; }
```

In cases like these, the name tmp is perfectly fine. The variable's sole purpose is temporary storage, with a lifetime of only a few lines.

But here's a case where tmp is just used out of laziness:

```
String tmp = user.name(); tmp += " "
+ user.phone_number(); tmp += " "
+ user.email(); ...
template.set("user_info",
tmp);
```

Even though this variable has a short lifespan, being temporary storage isn't the most important thing about this variable. Instead, a name like user_info would be more descriptive.

In the following case, tmp should be in the name, but just as a part of

```
it: tmp_file = tempfile.NamedTemporaryFile() ...
```

```
SaveData(tmp_file, ...)
```

Notice that we named the variable tmp_file and not just tmp, because it is a file object. Imagine if we just called it tmp:

```
SaveData(tmp, ...)
```

Looking at just this one line of code, it isn't clear if tmp is a file, a filename, or maybe even the data being written.

Loop Iterators

i, j, iter, it can be used as indices and loop iterators (In fact, if you used one of these names for some other purpose, it would be confusing - So, Don't do that). But sometimes there are better iterator names than i, j and k

```
for (int i = 0; i < clubs.size(); i++)
for (int j = 0; j < clubs[i].members.size();
j++) for (int k = 0; k < users.size(); k++)
if (clubs[i].members[k] == users[j])
cout << "user[" << j << "] is in club[" << i << "]" << endl;
```

In the if statement, `members[]` and `users[]` are using the wrong index. Bugs like these are hard to spot because that line of code seems fine in isolation:

```
if (clubs[i].members[k] == users[j])
```

In this case, using more precise names may have helped. You can name them as `club_i`, `member_i`, `user_i` or more succinctly `(ci,mi,ui)`. This approach would help the bug stand out more: `if (clubs[ci].members[ui] == users[mi])` # Bug! First letters don't match up.

As you've seen, there are some situations where generic names are useful. A lot of the time, they're overused out of pure laziness. This is understandable—when nothing better comes to mind, it's easier to just use a meaningless name like `foo` and move on. But if you get in the habit of taking an extra few seconds to come up with a good name, you'll find your **naming muscle** builds quickly.

Prefer Concrete Names over Abstract Names

For example, suppose you have an internal method named `ServerCanStart()`, which tests whether the server can listen on a given TCP/IP port. The name `ServerCanStart()` is somewhat abstract, though. A more concrete name would be `CanListenOnPort()`. This name directly describes what the method will do.

Please don't try to smash two orthogonal ideas into one. (Follow Single Responsibility Rule can help you easier to naming a method)

Attaching Extra Information to a

Name Values with Units

```
var start = (new Date()).getTime(); // top of the page ...
var elapsed = (new Date()).getTime() - start; // bottom of the page
document.writeln("Load time was: " + elapsed + " seconds"); More explicit:

var start_ms = (new Date()).getTime(); // top of the page ...
var elapsed_ms = (new Date()).getTime() - start_ms; // bottom of the page
document.writeln("Loadtime was: " + elapsed_ms / 1000 + " seconds");
Start(int delay) - delay -> delay_secs CreateCache(int size) - size -
> size_mb ThrottleDownload(float limit) - limit -> max_kbps Rotate(float angle) - angle - >
degrees_cw
```

Encoding Other Important Attributes

Many security exploits come from not realizing that some data your program receives is not yet in a safe state. For this, you might want to use variable names like `untrustedUrl` or `unsafeMessageBody`. After calling functions that cleanse the unsafe input, the resulting variables might be `trustedUrl` or `safeMessageBody`.

A password is in “plaintext” and should be encrypted before further processing - password - better name: plaintext_password

A user-provided comment that needs escaping before being displayed - comment - better name: unescaped_comment

Bytes of html have been converted to UTF-8 - html - better name:

html_utf8Incoming data has been "url encoded" - data - data_urlenc

You shouldn't use attributes like unescaped_ or _utf8 for every variable in your program. They're most important in places where a bug can easily sneak in if someone mistakes what the variable is, especially if the consequences are dire, as with a security bug. Essentially, if it's a critical thing to understand, put it in the name.

How long should a Name be

How do you decide between naming a variable d, days The answer depends on exactly how the variable is being used.

Shorter Names Are Okay for Shorter Scope

Identifiers that have a small scope (how many other lines of code can "see" this name) don't need to carry as much information.

```
if (debug) { map<string,int>
    m;
    LookUpNamesNumbers(
        &m);
    Print(m);
}
```

you can get away with shorter names because all that information (what type the variable is, its initial value, how it's destroyed) is easy to see.

Even though m doesn't pack any information, it's not a problem, because the reader already has all the information she needs to understand this code.

```

class Program
{
    0 references
    static async Task Main(string[] args)
    {
        WriteLine("Please type the username for the desired user:");
        var username = ReadLine();

        var github = new GitHubClient(new ProductHeaderValue("MyAmazingApp"));

        try
        {
            var user = await github.User.Get(username);
            WriteLine($"The user {user.Name} was succesfully retrieved!");
            WriteLine($"The user {user.Name} has {user.PublicRepos} public repositories. Do you want to see the list? (y/n)");
            var response = ReadLine();

            if (string.Equals(
                "y",
                response,
                StringComparison.InvariantCultureIgnoreCase))
            {
                var repos = await github.Repository.GetAllForUser(username);
                foreach (var repo in repos.OrderBy(x => x.CreatedAt))
                {
                    WriteLine($"{repo.CreatedAt:yyyy-MM-dd} | {repo.Name}");
                }
            }
        }
    }
}

```