CODE:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "f59trs"//IBM ORGANITION ID
#define DEVICE_TYPE "ultrasonicsensor"//Device type mentioned in
ibm watson IOT Platform
#define DEVICE_ID "distancedetection"//Device ID mentioned in ibm
#define TOKEN "AlGMGaaF01nawa1QA3" //Token
String data3;
float dist;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";//
Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and
char subscribetopic[] = "iot-2/cmd/test/fmt/String";//
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client
```

```
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient);
//calling the predefined client id by passing parameter like
server id, portand wificredential
int LED = 4;
int trig = 5;
int echo = 18;
void setup()
Serial.begin(115200);
pinMode(trig,OUTPUT);
pinMode(echo, INPUT);
pinMode(LED, OUTPUT);
delay(10);
wificonnect();
mqttconnect();
void loop()// Recursive Function
 digitalWrite(trig,LOW);
  digitalWrite(trig,HIGH);
  delayMicroseconds(10);
  digitalWrite(trig,LOW);
  float dur = pulseIn(echo,HIGH);
  float dist = (dur * 0.0343)/2;
  Serial.print ("Distancein cm");
  Serial.println(dist);
  PublishData(dist);
  delay(1000);
  if (!client.loop()) {
    mqttconnect();
Cloud. . . . . . . */
void PublishData(float dist) {
  mqttconnect();//function call for connecting to ibm
ibm cloud
```

```
String object;
  if (dist <100)
    digitalWrite(LED,HIGH);
    Serial.println("object is near");
    object = "Near";
  else
    digitalWrite(LED,LOW);
    Serial.println("no object found");
    object = "No";
  String payload = "{\"distance\":";
  payload += dist;
  payload += "," "\"object\":\"";
  payload += object;
  payload += "\"}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");// if it sucessfully upload data
on the cloud then it will print publish ok in Serial monitor or
else it will print publish failed
  } else {
    Serial.println("Publish failed");
void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
     initManagedDevice();
     Serial.println();
```

```
void wificonnect() //function defination for wificonnect
  Serial.println();
  Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials
to establish the connection
 while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
   Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
   //Serial.print((char)payload[i]);
    data3 += (char)payload[i];
```

```
// Serial.println(data3);
// digitalWrite(LED,LOW);

// }
data3="";
```

OUTPUT:

When object is not near to the ultrasonic sensor

