Assignment -3

Python Programming

Assignment Date	11 October 2022
Student Name	S. Vijaya Rama Lakshmi
Student Roll Number	953719106043
Maximum Marks	2 Marks

Question-1:

Image Augumentation

Solution:

⋆ 1. Image Augmentation

```
[ ] # Import necessary lib.
      from tensorflow.keras.preprocessing.image import ImageDataGenerator
 [ ] # Image augmentation on training variable
      train_datagen = ImageDataGenerator(rescale=1./255,
                                         zoom_range=0.2,
                                         horizontal_flip=True)
 [ ] # Image augmentation on testing variable
      test_datagen = ImageDataGenerator(rescale=1./255)
[ ] # Image augmentation on training data
    xtrain = train_datagen.flow_from_directory('/content/flowers',
                                                 target_size=(64,64),
                                                 class_mode='categorical',
                                                 batch_size=100)
[ ] # Image augmentation on testing data
    xtest = test_datagen.flow_from_directory('/content/flowers',
                                               target_size=(64,64),
                                               class_mode='categorical',
                                              batch_size=100)
```

Question-2:

Create Model

Solution:

2.Create the model

```
[ ] model = Sequential() # Initializing sequential model
```

QUESTION -3

Add Layers (Convolution, MaxPooling, Flatten, Dense-(Hidden Layers), Output)

Solution:

3.Add Layers

(Convolution, MaxPooling, Flatten, Dense-(Hidden Layers), Output)

```
[ ] # Importing requested library.
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Convolution2D, MaxPooling2D, Flatten, Dense

[ ] # Build a CNN block

model.add(Convolution2D(32,(3,3),activation='relu',input_shape=(64,64,3))) # convolution layer
model.add(MaxPooling2D(pool_size=(2, 2))) # Max pooling layer
model.add(Flatten()) # Flatten layer
model.add(Dense(300,activation='relu')) # Hidden layer 1
model.add(Dense(150,activation='relu')) # Hidden layer 2
model.add(Dense(4,activation='softmax')) # Output layer
```

QUESTION-4

Compile the model

Solution:

→ 4.Compile The Model

```
[ ] # Compiling the model
model.compile(optimizer='adam',loss='categorical_crossentropy',metrics=['accuracy'])
```

QUESTION-5

Fit the model

Solution:

5.Fit The Model

QUESTION-6

Save the model

Solution:

→ 6.Save The Model

```
[ ] # Save model

model.save('flowers.h5')
```

QUESTION -7

Test the model

Solution:

→ 7.Test the model

```
[ ] from tensorflow.keras.preprocessing import image
  import numpy as np

[ ] # Testing 1

  img = image.load_img('/flowers/dandelion/33907694863_f7c0f23ef3_n.jpg',target_size=(64,64)) # Reading image
  x = image.img_to_array(img) # Converting image into array
  x = np.expand_dims(x,axis=0) # expanding Dimensions
  pred = np.argmax(model.predict(x)) # Predicting the higher probablity index
  op = [daisy', 'dandelion', 'rose', 'sunflower', 'tulip'] # Creating list
  op[pred] # List indexing with output
```

```
img = image.load_img('/flowers/daisy/1150395827_6f94a5c6e4_n.jpg',target_size=(64,64)) # Reading image
x = image.img_to_array(img) # Converting image into array
x = np.expand_dims(x,axis=0) # expanding Dimensions
pred = np.argmax(model.predict(x)) # Predicting the higher probablity index
op = [daisy', 'dandelion', 'rose', 'sunflower', 'tulip'] # Creating list
op[pred] # List indexing with output
```