## MAHENDRA ENGINEERING COLLEGE FOR WOMEN

NAME:S.Prabadevi

REG NO: 611419106044

CLASS:4 year ECE

SUB: IBM

import numpy as np

import pandas as pd

from PIL import ImageFile

from tqdm import tqdm

import h5py

import cv2

import matplotlib.pyplot as plt

%matplotlib inline

import seaborn as sns

from sklearn.model\_selection import train\_test\_split

from sklearn.metrics import confusion\_matrix

from sklearn.metrics import plot\_confusion\_matrix

```
from tensorflow.keras.utils import to_categorical
from tensorflow.keras.preprocessing import image as keras_image
from tensorflow.keras.models import Sequential, load_model
from tensorflow.keras.layers import Dense
from tensorflow.keras.layers import Activation, Dropout
from tensorflow.keras.layers import Conv2D, MaxPooling2D, GlobalMaxPooling2D
from tensorflow.keras.callbacks import ReduceLROnPlateau, ModelCheckpoint
from tensorflow.keras.layers import LeakyReLU
def model():
  model = Sequential()
  model.add(Conv2D(128, (3, 3), input_shape=x_train.shape[1:]))
  model.add(LeakyReLU(alpha=0.02))
  model.add(MaxPooling2D(pool_size=(2, 2)))
  model.add(Dropout(0.25))
  model.add(Conv2D(128, (3, 3)))
  model.add(LeakyReLU(alpha=0.02))
  model.add(MaxPooling2D(pool_size=(2, 2)))
  model.add(Dropout(0.25))
  model.add(GlobalMaxPooling2D())
```

```
model.add(Dense(512))
  model.add(LeakyReLU(alpha=0.02))
  model.add(Dropout(0.5))
  model.add(Dense(10))
  model.add(Activation('softmax'))
  model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])
  return model
model = model()
# To save the best model
checkpointer = ModelCheckpoint(filepath='weights.best.model.hdf5', verbose=2,
save_best_only=True)
# To reduce learning rate dynamically
Ir_reduction = ReduceLROnPlateau(monitor='val_loss', patience=5, verbose=2, factor=0.2)
# Train the model
history = model.fit(x_train, y_train, epochs=75, batch_size=32, verbose=2,
          validation_data=(x_valid, y_valid),
           callbacks=[checkpointer,
data_generator = keras_image.lmageDataGenerator(shear_range=0.3,
                          zoom_range=0.3,
```

## rotation\_range=30, horizontal\_flip=True)