

Literature Survey 1:

The author has observed gas leakage and LPG levels where gas leakage occurs automatically. The authors suggests that gas leakage is performed by various gas sensors. Whose author has worked on gas leaks and mentions that we can take care if a found using a sensor and gas booking can be done automatically when a small amount of gas is taken closed.

RFID tag microcontroller, pressure sensors and buzzers are used to monitor gas. Through this paper important parameters are used to find the level of gas in the container. The good purpose of this project is to get notification of gas leak to user when gas leakage is started. Arduino was originally created as a tool for fast sampling and activities for students with no knowledge for electronics. This paper uses a microcontroller, buzzer and a gas sensor to detect gas leakage system. When a gas leak is detected by a gas sensor ,the microcontroller turn on the buzzer in critical condition. The author suggest that this message or instruction may be displayed using an LCD display for LPG monitoring.

- The proposed system detects LPG leaks and alerts customers. The alarm starts when the system notice and increases in LPG leakage concentration by sending an alarm and sending a message to specific mobile phone. The device assures safety and prevents explosions. A microcontroller based system based on gas sensor(MQ6) has been developed in proposed system to detect LPG leakage . The unit is also integrated with an alarm unit to detect signal a leak.

Literature Survey 2:

A number of reviews on the subject of gas leakage detection techniques were done in the past either as part of research papers/technical reports on a certain leak detection method and other gas related subjects. A.Mahalingam, r. T. Naayagi, n. E. Mastorakis; they introduce design and implementation of an economic gas leakage detector. They gave the formulation of many problems in previous gas leakage detectors. They told that several standards have been formulated for the design of a gas leakage detection system such as IEEE, BS 5730, and IEC. For this work, the recommended UK safety standards have been adopted. The proposed alarm system is mainly meant to detect LPG leakage, which is most commonly used in residential and commercial premises. The system detects not only the presence of gas (gas leak), but also the amount of leakage in the air, and accordingly raises an appropriate audio visual alarm. The objective of the system is to detect LPG gases such as propane and butane. The allowed UK level for butane is 600 ppm above which it is considered to be of high level and poses a danger. The proposed system ensures a continuous monitoring of the gas levels. If the gas level increases above the normal threshold level of 400 ppm butane (LPG), the system starts to issue early warning alarms at 100ms interval, which implies low level gas leakage. If the leakage level increases to 575 ppm of butane (LPG), the system activates high severity audio alarms at 50 ms intervals warning the occupants to run to safety.

Literature Survey 3:

A number of reviews on the subject of gas leakage detection techniques were done in the past either as part of research papers/technical reports on a certain leak detection method and other gas related subjects. A.Mahalingam, r. T. Naayagi, n. E. Mastorakis; they introduce design and implementation of an economic gas leakage detector. They gave the formulation of many problems in previous gas leakage detectors. They told that several standards have been formulated for the design of a gas leakage detection system such as IEEE, BS 5730, and IEC. For this work, the recommended UK safety standards have been adopted. The proposed alarm system is mainly meant to detect LPG leakage, which is most commonly used in residential and commercial premises. The system detects not only the presence of gas (gas leak), but also the amount of leakage in the air, and accordingly raises an appropriate audio visual alarm. The objective of the system is to detect LPG gases such as propane and butane. The allowed UK level for butane is 600 ppm above which it is considered to be of high level and poses a danger. The proposed system ensures a continuous monitoring of the gas levels. If the gas level increases above the normal threshold level of 400 ppm butane (LPG), the system starts to issue early warning alarms at 100ms interval, which implies low level gas leakage. If the leakage level increases to 575 ppm of butane (LPG), the system activates high severity audio alarms at 50 ms intervals warning the occupants to run to safety.

Literature Survey 4:

Prof. M.Amsaveni, A.Anurupa, R.S.Anu Preetha, C.Malarvizhi, M.Gunasekaran; they told in their research paper on "GSM based LPG leakage detection and controlling system" the leakage of LPG gas is detected by the MQ-6 gas sensor. Its analog output is given to the microcontroller. It consists of predefined instruction set. Based on this, the exhaust fan is switched on. So, the concentration of gas inside the room gets decreased. Then, the stepper motor is rotated thus closing the knob of the cylinder. Because of this process, the leakage of gas is stopped. The relay is switched to off the power supply of the house. The buzzer produces an alarm to indicate the gas leakage. Then, the user is alerted by SMS through the GSM module. They proposed their methodology that the system takes an automatic control action after the detection of 0.001% of LPG leakage. This automatic control action provides a mechanical handle for closing the valve. We are increasing the security for human by means of a relay which will shut down the electric power to the house. Also by using GSM, we are sending an alert message to the users and a buzzer is provided for alerting the neighbors about the leakage.

Literature Survey 5:

Ch. Manohar Raju and N. Sushma Rani, they introduce an android based automatic gas detection and indication robot. They proposed prototype depicts a mini mobile robot which is capable to detect gas leakage in hazardous places. Whenever there is an occurrence of gas leakage in a particular place the robot immediately read and sends the data to android mobile through wireless communication like Bluetooth. We develop an android application for android based smartphones which can receive data from robot directly through Bluetooth. The application warns with an indication whenever there is an occurrence of gas leakage and we can also control the robot movements via Bluetooth by using text commands as well as voice commands. The previous mobile robots are based on heterogeneous technologies like GSM, GPS, internet based etc., but the main disadvantage of those prototypes were the absence of communication in particular areas. So, with the rapid developments and tremendous changes in technology we have lots of techniques to eradicate previous problems. Wireless communication protocols play a vital role in present trends. Bluetooth, WI-Fi, Zigbee etc., we use one of the best feature of smartphone, i.e., the Bluetooth technology to control and monitor parameters driven by a robot. They introduce a robot and mobile application for In the meantime, the system prototype has imposingly demonstrated its use and capability in intensive series of tests. The drive unit, the navigation system and, therefore, the complementary sensor systems performed superbly throughout the tests. The robot facilitates independent gas detection and leak localization in sites that are otherwise troublesome to access. Moreover, it helps to avoid mistreatment of human inspectors in probably dangerous environments. However, before ready-ing in industrial settings, more development is needed (e.g., in explosion protection, package development, etc.), and in fact leg a problems should be processed before ready-ing in business settings. Still, it is certain that an autonomous, mobile gas detection and leak localization robot is possible today and can significantly enhance safety.