GAS LEAKAGE MONITORING AND ALERTING SYSTEM

TEAM ID	PNT2022TMID15951
TEAM MEMBERS	Barani G Ashwini R Akshaya KS Abitha J

GAS LEAKAGE DETECTION:

CODE FOR GAS LEAKAGE DETECTION:

```
int gasSensor=A1;int
buzzer=13;
int led=12; void
setup()
{

  pinMode(A1, INPUT);
  pinMode(13, OUTPUT);
  pinMode(12, OUTPUT);
  Serial.begin(9600);
}



void loop()

{

  int sensorValue=analogRead(gasSensor);
  Serial.print("GAS LEVEL:");
```

```
  Serial.println(sensorValue);
  delay(1000);
  if(sensorValue>200)
  {

    digitalWrite(buzzer,HIGH);
    digitalWrite(led,HIGH);
  }

  else

  {

    digitalWrite(buzzer,LOW);
    digitalWrite(led,LOW);
  }
}
```

Step 1:

Gas leakage is detected by the gas sensor



Step2:

Buzzer is attached in order to get buzzer sound when the gas exceeds its level



Step 3:

1. Led is attached

2. The LED is not on when there is no leakage i.e it does not exceeds its value



Step 4:

1. LED gets ON.

2. When there is a gas leakage, LED gets on and the buzzer gives the alert by sound.



Step1:

Circuit is designed for Gas leakage Monitoring and Alerting.



Step 2:

i. Simulate the circuit.
ii. After the simulation the circuit shows a message “ALL CLEAR” in LCD Display.
iii. It significantly shows that the harmful gas is not Emitted and the place is Safe.



Step 3:

I. When Harmful gas is emitted in the Industry.
II. The Gas Sensor will detect the harmful gas leakage.
III. Then the LCD Display will show a “ALERT” Message and also shows “Evacuate”.





Code FOR GAS LEAKAGE MONITORING & ALERTING :

```
#include <LiquidCrystal.h>
```

```
 LiquidCrystal lcd(5,6,8,9,10,11);



 //pin
 variables
 int redled =
 3; int
 greenled =
 2;int
 buzzer = 4;
 int sensor =
 A0;
 int sensorThresh = 400;
  void setup()
  {
pinMode(redled,OUTP
UT);
pinMode(greenled,OUT
PUT);
pinMode(buzzer,OUTP
UT);
pinMode(sensor,INPUT
); Serial.begin(9600);
lcd.begin(16,2);
  }
void loop()
{
int analogValue =
analogRead(sensor);
Serial.print(analogValue);
//gas concenteration
condition
if(analogValue>sensorT
hresh)
  {
```

```
digitalWrite(redled,HI
GH);
digitalWrite(greenled,
LOW);
tone(buzzer,1000,100
00); lcd.clear();

//to print on LCD
lcd.setCursor(0,1);
lcd.print("ALERT");
delay(1000);
lcd.clear();
lcd.setCursor(0,1);
lcd.print("EVACUA
TE");delay(1000);
  }
else
{
digitalWrite(greenled,H
IGH);
digitalWrite(redled,LO
W);
noTone(buzzer);
   lcd.clear();
   lcd.setCursor(0,
   1);
   lcd.print("ALL
   CLEAR");
   delay(1000);
  }

 }
```

Result:

The Gas Leakage is Monitored and Alerting Message is Successfully Send.