MAIN CODE

Team ID: PNT2022TMID16239

Project Name : Smart Waste Management System

Code for Data transfer to IBM

```
#include <WiFi.h>                                   // library for wifi
#include <PubSubClient.h>                           // library for MQTT
#include <LiquidCrystal_I2C.h>
#include <mjson.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);

//------------------------ credentials of IBM Accounts ------------------------
------

#define ORG "1yot2m"                            // IBM organisation id #define
DEVICE_TYPE "ESP"                  // Device type mentioned in ibm watson
iot platform
#define DEVICE_ID "12345"                 // Device ID mentioned in ibm watson
iot platform
#define TOKEN "87654321"            // Token

//------------------------ customise above values ----------------------------
------------------------
 char server[] = ORG
".messaging.internetofthings.ibmcloud.com";                 // server name char
publishTopic[] = "iot-
2/evt/data/fmt/json";                                  // topic name and type of
event perform and format in which data to be send char topic[] = "iot-
2/cmd/led/fmt/String";                                      // cmd Represent
type and command is test format of strings char authMethod[] = "use-
tokenauth";                                          // authentication
method char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":"
DEVICE_ID;                      //Client id

//------------------------------------------------------------------------------
----------------------------------------

WiFiClient wifiClient;                                                      //
creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
```

```
#define ECHO_PIN 12
#define TRIG_PIN 13
float dist; String
data3; bool SealBin =
true; void setup()
{
  Serial.begin(115200);
pinMode(LED_BUILTIN, OUTPUT);
pinMode(TRIG_PIN, OUTPUT);
pinMode(ECHO_PIN, INPUT);
  //pir pin
pinMode(34, INPUT);


  //ledpins
pinMode(23, OUTPUT);
pinMode(2, OUTPUT);
pinMode(4, OUTPUT);
pinMode(15, OUTPUT);
      lcd.init();
lcd.backlight();
lcd.setCursor(1, 0);
lcd.print("");
wifiConnect();
mqttConnect();
}  float
readcmCM()
{   digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);   int
duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
}
void loop()
 {
lcd.clear();
publishData();
  delay(500);   if
(!client.loop())
    {       mqttConnect();                                    // function
call to connect to IBM
    }
}
```

```
/* ------------------------------retrieving to cloud-----------------------
-----------------------------*/
 void wifiConnect()
{
  Serial.print("Connecting to ");
  Serial.print("Wifi");
  WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
    {
      delay(500);
      Serial.print(".");
    }
  Serial.print("WiFi connected, IP address: ");
  Serial.println(WiFi.localIP());
} void mqttConnect()
  {     if
(!client.connected())
      {
        Serial.print("Reconnecting MQTT client to ");
Serial.println(server);
        while (!client.connect(clientId, authMethod, token))
          {
            Serial.print(".");
delay(500);
          }
        initManagedDevice();
        Serial.println();
      }
}
void initManagedDevice()
  {     if
(client.subscribe(topic))
      {
        Serial.println("IBM subscribe to cmd OK");
      }
else
```

```
{
        Serial.println("subscribe to cmd FAILED");
      }   } void
publishData()
{   float cm =
readcmCM();
   if(digitalRead(34))                                  //pir motion detection
{
    Serial.println("Motion Detected");
Serial.println("Lid Opened");     digitalWrite(15,
HIGH);


       if(digitalRead(34)==
true)
 {   if(cm <= 60)                                                  //Bin
level detection   {
    digitalWrite(2, HIGH);
    Serial.println("High Alert!!!,Trash bin is about to be full");
Serial.println("Lid Closed");     lcd.print("Full! Don't use");
delay(2000);     lcd.clear();     digitalWrite(4, LOW);
digitalWrite(23, LOW);
  }   else if(cm > 60 && cm <
120)
  {
    digitalWrite(4, HIGH);
    Serial.println("Warning!!,Trash is about to cross 50% of bin level");
digitalWrite(2, LOW);     digitalWrite(23, LOW);
      }   else if(cm
> 120)
  {
    digitalWrite(23, HIGH);
    Serial.println("Bin is available");
digitalWrite(2,LOW);     digitalWrite(4,
LOW);

}
    delay(10000);
   Serial.println("Lid Closed");
 } else
 {
```

```
   Serial.println("No motion detected");
digitalWrite(2, LOW);     digitalWrite(15,
LOW);     digitalWrite(4, LOW);
digitalWrite(23, LOW);
 }

 }   else   {
digitalWrite(15, LOW);

  }

  if(cm <= 60)
{
digitalWrite(21,HIGH);
String payload = "{\"High_Alert\":";
payload += cm; payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str()))         // if data
is uploaded to cloud successfully,prints publish ok else prints publish failed
{
Serial.println("Publish OK");
} }
else if(cm <= 120)
{
digitalWrite(22,HIGH);
String payload = "{\"Warning\":";
payload += cm ; payload += " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload); if(client.publish(publishTopic,
(char*) payload.c_str()))
{
Serial.println("Publish OK");
} else
{
Serial.println("Publish FAILED");
} }  else if(cm >
120)
{
digitalWrite(23,HIGH);
String payload = "{";
```

```
payload += cm; payload
+= " }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str()))         // if data
is uploaded to cloud successfully,prints publish ok else prints publish failed
{
Serial.println("Publish OK");
}
}    float inches = (cm / 2.54);                                          //print
on lcd   lcd.setCursor(0,0);   lcd.print("Inches");   lcd.setCursor(4,0);
lcd.setCursor(12,0);   lcd.print("cm");   lcd.setCursor(1,1);
lcd.print(inches, 1);   lcd.setCursor(11,1);   lcd.print(cm, 1);
lcd.setCursor(14,1);   delay(1000);   lcd.clear();
}


//handles commands from user side


void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{


  Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {
       data3 +=
(char)payload[i];   }
  Serial.println("data: "+ data3);
   const char *s =(char*) data3.c_str();
double pincode = 0;
              const char
*buf;           int len;
                 if (mjson_find(s, strlen(s), "$.command", &buf, &len))  //
And print it          {


          String command(buf,len);


if(command=="\"SealBin\"")
          {
            SealBin = true;


          }


               }
```

```
data3="";   }
```