

# PYTHON CODE FOR QR SCANNER

TEAM ID : PNT2022TMID00940

```
import cv2
import numpy as np
import time
import pyzbar.pyzbar as pyzbar
from ibmcloudant.cloudant_v1 import CloudantV1
from ibmcloudant import CouchDbSessionAuthenticator
from ibm_cloud_sdk_core.authenticators import BasicAuthenticator

authenticator = BasicAuthenticator('apikey-267fe83f32ec443b804f3c76d688d2e3',
'b1456cbe3c712c2d555623fe092c074478521354')
service = CloudantV1(authenticator=authenticator)

service.set_service_url('https://4f470103-dd2c-4f50-94e8-3439395a7935-bluemix.cloudant.com')

cap= cv2.VideoCapture(0)
font = cv2.FONT_HERSHEY_PLAIN

while True:
    _, frame = cap.read()
    decodedObjects = pyzbar.decode (frame)
    for obj in decodedObjects:
        #print ("Data", obj.data)
        a=obj.data.decode('UTF-8')
        cv2.putText(frame, "Ticket", (50, 50), font, 2, (255, 0, 0), 3)

        #print (a)
```

```
try:
    response = service.get_document(
        db='booking',
        doc_id = a
    ).get_result()
    print (response)
    time.sleep(5)
except Exception as e:
    print ("Not a Valid Ticket")
    time.sleep(5)

cv2.imshow("Frame",frame)
if cv2.waitKey(1) & 0xFF ==ord('q'):
    break

cap.release()
cv2.destroyAllWindows()
client.disconnect()
```

# PYTHON CODE FOR TRAIN LOCATION

```
import wiotp.sdk.device
import time
import random

myConfig = {
    "identity": {
        "orgId": "ojhlri",
        "typeId": "GPS",
        "deviceId": "12345"
    },
    "auth": {
        "token": "12345678"
    }
}

def myCommandCallback (cmd):
    print ("Message received from IBM IoT Platform: %s" % cmd.data['command'])
    m=cmd.data['command']

client = wiotp.sdk.device.DeviceClient(config=myConfig, logHandlers=None)
client.connect()

def pub (data):
    client.publishEvent(eventId="status", msgFormat="json", data=myData, qos=0,
onPublish=None)

    print ("Published data Successfully: %s", myData)

while True:
    myData={'name': 'Train1', 'lat': 17.6387448, 'lon': 78.4754336}
```

```
pub (myData)
time.sleep (3)
#myData={'name': 'Train2', 'lat': 17.6387448, 'lon': 78.4754336)
#pub (myData)
#time.sleep (3)
myData={'name': 'Train1', 'lat': 17.6341908, 'lon': 78.4744722}
pub(myData)
time.sleep(3)
myData={'name': 'Train1', 'lat': 17.6340889, 'lon': 78.4745052}
pub (myData)
time.sleep (3)
myData={'name': 'Train1', 'lat': 17.6248626, 'lon': 78.4720259}
pub (myData)
time.sleep (3)
myData={'name': 'Train1', 'lat': 17.6188577, 'lon': 78.4698726}
pub (myData)
time.sleep (3)
myData={'name': 'Train1', 'lat': 17.6132382, 'lon': 78.4707318}
pub (myData)
time.sleep (3)
client.commandCallback = myCommandCallback
client.disconnect ()
```