

## **PROJECT PROGRESS TRACKING**

Date	10 November 2022
Team ID	PNT2022TMID17666
Project Name	Project - IoT based safety gadget for ChildSafety Monitoring and Notification
TEAM LEADER	PRIYA.V
TEAM MEMBERS	VASUNTHARA.D JANANI.R JANANI ISHWARYA.S

### **INTRODUCTION:**

Our proposed system consists of Raspberry Pi microprocessor in which all other sensors, GPS and GSM are integrated. The users are required to register using their credentials to use the application. The device will be given to the children for monitoring them regularly. We will feed the boundary value while writing code for the system and we control it using GPS for that device which is also known as Geo Fencing. These data are stored in the server.

If the device moves, out of that boundary the server transfers an alert call by activating the GSM, to the user. The live location of the device will be updated in the server and pinged in the website for every few seconds.

The server-side coding was written in PHP and the controller side coding was written in Python. The user will receive an alert call and after entering the login ID and password, they can check the live location through GPS, which was updated in the application. When giving boundary for the school unit, we can also maintain attendance by updating the entry and exit of the child, in and out, of school in the application.

We feed specific threshold values for sensors like temperature and pulse in which, if the device exceeds those threshold values or if the device gets exposed to abnormal condition, then those values tend to be updated in the server.

## TRACKING:

The server compares the currently obtained values with the coded threshold values, if they are beyond the threshold value, it generates an alert message through GSM. The alert messages are delivered to specified users in the form of SMS and the user can be able to login to the application to check the status and updated information. After receiving the alert messages, if the user wants to visually check the status of the child, they are required to enter specific IP address of that camera for the first time before syncing and can be able to watch the live streaming videos which are updated to the server, for further uses they can directly view. The microprocessor is used to control all these actions and the alert was done by checking for specific user of that device in the database.

