SMARTFARMER- IOT ENABLED SMART FARMING APPLICATION

_

Team ID: PNT2022TMID07143

Team Member

<u>Dharshini S -610519106009</u>

<u>Jayaraman R - 610519106020</u>

<u>Lalprasanth N - 610519106029</u>

<u>Shankari - 610519106062</u>

1. INTRODUCTION

- a. Project Overview
- b. Purpose

2. LITERATURE SURVEY

- a. Existing problem
- b. References
- c. Problem Statement Definition

3. IDEATION & PROPOSED SOLUTION

- a. Empathy Map Canvas
- b. Ideation & Brainstorming
- c. Proposed Solution
- d. Problem Solution fit

4. REQUIREMENT ANALYSIS

- a. Functional requirement
- b. Non-Functional requirements

5. PROJECT DESIGN

- a. Data Flow Diagrams
- b. Solution & Technical Architecture
- c. User Stories

6. PROJECT PLANNING & SCHEDULING

- a. Sprint Planning & Estimation
- b. Sprint Delivery Schedule

7. CODING & SOLUTIONING (Explain the features added in the project along with code)

- **a**. Feature 1
- b. Feature 2
- c. Database Schema (if Applicable)

8. IBM cloud & TESTING

- a. Test Cases
- b. User Acceptance Testing in MIT app
- c. Fast2sms

9. RESULTS

a. Performance Metrics


10. ADVANTAGES & DISADVANTAGES

- 11.CONCLUSION
- 12.FUTURE SCOPE
- 13.APPENDIX

INTRODUCTION

1.1 Project overview

IoT- based agriculture system helps the farmer in monitoring different parameters of his field like soil moisture, Temperature, humidity using some sensors. Farmers can monitor all the sensor parameters by using a web or mobile application even if the farmer is not near his field. Watering the crop is one of the important tasks for the farmers. They can make the decision whether to water the crop or postpone it by monitoring the sensor parameters and controlling the motor pumps from the mobile application itself.



1.2 Purpose

The smart agriculture model main aim to avoid water wastage in the irrigation process. It is low cost and efficient system Is shown below. It includes NodeMCU, Arduino Nano, sensors like soil moisture and Dht11, solenoid valves, relays.

2.LITERATURE SURVEY

2.1 Existing problem

Smart agriculture farming system is a new idea of farming in agriculture, because which uses IoT technology to monitor the crop 24/7 and sends the information to the cloud. This emerging system increases the quality and quantity of agricultural products. IoT technology provides the information about farming fields and then takes action depending on the farmer input. In this project we can design an IoT based advanced solution for monitoring the soil conditions and atmosphere for efficient crop growth is presented. The developed system is capable of monitoring temperature, humidity, soil moisture type using Ardunio UNO R3 and different sensors connected to the microcontroller. Also, a notification is shown in farmer's phone using Wi-Fi about environmental condition and water levels of the crop field

- It is not a secure system.
- There is no motion detection for protection of agriculture field.
- Automation is not available.

2.2 References

LITERATURE SURVEY


PAPER TITLE	AUTHOR NAME	OBJECTIVES		
Smart Farming management system using IOT Reference <u>HERE</u>	Garigipati Vijay Kumar, Pallikonda Jashuva	Due to the usage of this system, adequate water is pumped and rain is also utilized efficiently using Node MCU, Sensors like Soil Moisture sensor, Humidity and Temperature Sensor and All the information are send to the farmers mobile using wifi technology.		
IoT Based Intelligent Agriculture Field Monitoring System Reference <u>HERE</u>	Md Ashifuddin Mondal, Zeenat Rehena	Arduino board controls the high voltage farming equipments without human intervention. Also the system sends the environmental parameters values to the cloud from the field in real time through wireless communication in every certain time interval.		
Survey on Smart Agriculture Using IOT Reference <u>HERE</u>	Shweta A M, Dr V. Nagaveni	Smart agriculture reduces wastage of water, fertilizers and increases the crop yield.using Internet of Things (IoT), Agriculture, Agriculture Precision, Raspberry Pi, Temperature Sensor, Smart Farming, Soil Moisture		

2.3 Problem Statement Definition

The soil moisture sensor measures wetness content in the soil. The Arduino UNO microcontroller used to receive input from a various sensor and it can be controlled automatically. When soil moisture sensor goes low the water pump will be on and it exceeds defined levels of the water motor will turn off automatically. We can constantly monitor the growth of a crop using ultrasonic sensor. PIR sensor detects the motion or unusual movement in the agricultural land. This device his very helpful to the former to monitor and control environmental parameters at their field. The farmers did not go to their field, they can remotely monitor and control using cloud

3.IDEATION & PROPOSED SOLUTION

3.1 Empathy Map Canvas



3.2Ideation and Brainstorming



3.3 Proposed Solution

S.No	Parameters	Description	
1	Problem statement	SmartFarmer-Iot Enabled Smart Farming Application	
	(problem to be solved)		
2	dea/Solution	This project helps the farmer in monitoring different	
	Description	parameters of his field like soil, moisture, Temperature	
		and humidity using some sensors. Farmers can monitor	
		all the sensor parameters by using a web or mobile	
		application even if the farmers is not near his field.	
3	Novelty/Uniqueness	Watering the crops is one of the important tasks for the	
		farmers. They can make the decision whether to water	
		the crop or postpone it by monitoring the sensor	
		parameter and controlling the motor pumps from the	
		mobile application .	
4	Social impact/Customer	Smart Farming allows farmers to be much more precise.	
	Satisfaction	By Using Iot farmers boosts operational proficiency and	
		reduces energy waste. Farmer can monitoring and get all	
		the sensor parameters data about his field in real time	
		through web application	
5	Business	• Cost Efficiency	
	Model(Revenue Model)	• Fuel Efficiency	
6	Scalability the solution	This project has HIGH SCALABILITY in monitoring all the	
		sensor parameters and controlling the motor pump	
		through mobile applications	

3.4 Problem solution fit

1.Customer Segments	6. Customer constrains	5. Available solutions
The customers who are	The customer wants a device	The moisture-controlled
going to adapt this project	which could be the solution	irrigation system could be the
are: *Large Scale Farmer	in the field of watering the	best solution for this problem
*Remote Farmers	crops even the farmer is not	statement that has been
	presence in field and the	provided by the farmers and
	device should fulfill all the	also it specifically satisfies the
	following constraints * Cost	customer constraints also.
	and Time Efficient *	
	Resource Efficient	

2. Jobs to be done. The customer needs to automate the process of irrigation in cost efficient, energy efficient, reduced power consumption and can be achieved in a reliable	9.Problem route cause 1) The problem has its route stabled at the rate of the fast-moving world since people move fast of the times and since they have their work to be stagnated similarly farmers face the inability in the process of irrigation 2)In some times, farmers can't get or predict the sensing parameters data accurately (humidity, moisture, temperature)	7.Bahaviour The customer wants to make the revolutionary propagation in the rating of the irrigation through the reliability of amount of water availability on the land.
3.Triggers The reliability and easy accessibility of this finished projects yields the Customer's attraction and they can easily be installed in their fields	10. Solution. Our solution for this project is to initiate the reliability of the irrigation system using the sensor sensed information from the field and also make the automation is on and off of water pump	8. Channels of behavior The channels of behaviorrecombine the ration of following: *ONLINE: Using mobile application the farmers can controlling the motor pumps through online mode. *OFFLINE: Farmers can get the sensing parameters data via SMS.
4. Emotions Before – manual system is necessary to monitor the fields After — Manual system is not Necessary since in our project we'll develop a mobile or web applications so the farmers can control and monitor about his field. So, the customers feel comfortable and Happy.		

4.REQUIREMENT ANALYSIS

FR.No	Functional Requirement (Epic)	Sub Requirement (Story/Sub-Task)
FR-1	User Registration	Registration through Gmail
I'W-I	User Registration	Registration through Form
FR-2	User Confirmation	Confirmation via Email
rk-Z	oser commination	Confirmation via OTP
FR-3	Log in to System	Check credentials check
LV-9	Log in to System	Role of Access
FR-4		Manage System Admin
	Manage Modules	Manage Roles of User
		Manage User permission
ED E	Charle Cradentials Datails	Temperature details
FR-5	Check Credentials Details	Humidity details
FR-6	Log out	Exit the application

4.2 Non-Functional requirements

FR No.	Non-Functional Requirement	Description
NFR-1	Usability	Usability includes easy learn ability, efficiency in use, remember ability, lack of errors in operation and subjective pleasure
NFR-2	Security	Sensitive and private data must be protected from their production until the decision-making and storage stages
NFR-3	Reliability	The shared protection achieves a better trade-off between costs and reliability.
NFR-4	Performance	The idea of implementing sensors with sensing soil and environmental or ambient parameters in farming will be more efficient for overall monitoring


5.PRODUCT DESIGN

5.1Data flow diagrams


A Data Flow Diagram (DFD) is a traditional visual representation of the information flows within a system. A neat and clear DFD can depict the right amount of the system requirement

graphically. It shows how data enters and leaves the system, what changes the information, and where data is stored.

- The different soil parameters temperature, soil moistures and then humidity are sensed using different sensors and obtained value is stored in the IBM cloud.
- Arduino UNO is used as a processing Unit that process the data obtained from the sensors and whether data from the weather API.
- NODE-RED is used as a programming tool to write the hardware, software, and APIs. The MQTT protocol is followed for the communication.
- All the collected data are provided to the user through a mobile application that was
 developed using the MIT app inventor. The user could plan through an app, weather to
 water the crop or not depending upon the sensor values. By using the app they can
 remotely operate to the motor switch



5.2Solution and Technical Architecture



- The different soil parameters temperature, soil moistures and then humidity are sensed using different sensors and obtained value is stored in IBM cloud.
- Arduino Uno is used as a processing unit that process the data obtained from the sensors and weather data from the weather API
- NODE-RED is used as a programming tool to write the hardware, software and APIs. The MQTT protocol is followed for the communication.
- All the collected data are provided to the user through a mobile application that was developed using the MIT app inventor. The user could decide through an app, whether to water the crop or not depending upon the sensor values, By using the app,they can remotely operate the motor switch(0n/off).

6.PROJECT PLANNING AND SCHEDULING

Sprint	User Story Number	User Story/ Task	Story Points	Priority	Team Mambers
Sprint 1	USN-1	Sensors and wi-fi module with python code	2	High	Lalprasanth N Dharshini S Shankari J Jayaraman R

Sprint 2 USN-2	USN-2	IBM Watson IoT Platform,workflows for IoT Scenarious using	2	High	Lalprasanth N Dharshini S Shankari J
		Node-Red			Jayaraman R
					Lalprasanth N
Sprint 3 USN-3	IICN_3	USN-3 To Develop an Mobile application using MIT	2	High	Dharshini S
	0311-3				Shankari J
					Jayaraman R
					Lalprasanth N
Sprint 4	USN-4	To make the user to interact with Software	2	High	Dharshini S
					Shankari J
					Jayaraman R

7.CODING AND SOLUTIONING

7.1 Feature

```
import time
import sys
import ibmiotf.application
import ibmiotf.device
import random
#Provide your IBM Watson Device Credentials
orgId = "oy32g"
deviceType = "Dharshini"
deviceId = 2002
token = "sridharan11"
authMethod = "use-token-auth"
# Initialize GPIO
def myCommandCallback(cmd):
 print("Command received: %s" % cmd.data['command'])
  status=cmd.data['command']
 if status=="motoron":
   print ("motor is on")
```


```
else:
   print ("motor is off")
  #print(cmd)
try:
 deviceOptions = {"org": orgId, "type": deviceType, "id": deviceId, "auth-method":
authMethod, "auth-token": Token}
 deviceCli = ibmiotf.device.Client(deviceOptions)
 #.....
except Exception as e:
print("Caught exception connecting device: %s" % str(e))
sys.exit()
# Connect and send a datapoint "hello" with value "world" into the cloud as an event of type
"greeting" 10 times
deviceCli.connect()
while True:
 #Get Sensor Data from DHT11
 temp=random.randint(-20,125)
 hum=random.randint(0,100)
 soil=random.randint(0,100)
 data = { 'temp' : temp, 'hum': hum, 'soil': soil}
 #print data def myOnPublishCallback( ):
 print (f"Published temp = {temp} C, hum = {hum}, soil = {soil} deg c to IBM Watson")
 success = deviceCli.publishEvent("IoTSensor", "json", data,
qos=0,on_publish=myOnPublishCallback)
 if not success:
   print("Not connected to IoTF")
   time.sleep(10)
 deviceCli.commandCallback = myCommandCallback
 # Disconnect the device and application from the cloud
 deviceCli.disconnect()
```


```
- 0 X
*untitled*
   File Edit Format Run Options Window Help
File Edit Format Run Options Window Help
Import time
Import type
Import time
Import imiotf.application
Import imiotf.device
Import random
Frovide your ISM Watson Device Credentials
Orgrd = "0y32g"
deviceType = "Dharshini"
devicetd = 2002
token = "stindarani!"
auttNethod = "use-token-auth"
f Initialize GPID back(cmd):
print("Command zecolved: %s" % cmd.data['command'])
if status=cmd.data['command')
if status=cmd.data['command')
print ("motor is on")
else:
print ("motor is off")
                 #print(cmd)
          xcept Exception as e:
print("Caught exception connecting device: %s" % str(e))
sys.exit()
   # Connect and send a datapoint "hello" with value "world" into the cloud as an event of type "greeting" 10 times deviceCli.connect()
      The List Dead Cobus Contons Woodow Page
Python S.7.0 (v)7.7.0:18f9cc3193, Jun 27 2014, 04:39:511 [MDC v.1914 64 Bit (AMD64)] on win12
Type "copyright", "credits" or "license()" for more information.
                               Type "Copyright", "Credita" of "Alconomic to more than "Copyright", by "Copyright", "Credital" ("Credital") (
```

_ No _ N


8. IBM- Cloud & Testing


8.1Testcase







Web application using node red.









8.2 User Aceceptance Testing in MIT app












Fast2SMS:



9.Results

9.1 Performance Metrics





10.Advantages and disadvantages

Advantages:

- A remote-control system can help in working irrigation system valves dependent on schedule. Irrigating remote farm properties can be exceptionally troublesome and laborintensive. It gets hard to comprehend when the valves were started and whether the ideal measure of water was distributed.
- For situations where a quick reaction is required, manual valve actuation may not be conceivable constantly. Thus, remote observing and control of irrigation systems, generators or wind machines or some other motor-driven hardware become the next logical step.
- Various solutions are available to monitor engine statistics and starting or stopping the
 engine. When the client chooses to begin or stop the motor, the program transmits a
 sign to the unit within seconds by means of a mobile phone system.
- Submersible weight sensors or ultrasonic sensors can screen the degree of tanks, lakes, wells and different kinds of fluid stockpiling like fuel and compost. The product figures volume dependent on the tank or lake geometry after some time. It conveys alarms dependent on various conditions.

Disadvantages:

- The smart agriculture needs availability of internet continuously. Rural part of most of the developing countries do not fulfil this requirement. Moreover internet connection is slower.
- The smart farming based equipment require farmers to understand and learn the use of technology. This is major challenge in adopting smart agriculture farming at large scale across the countries.

11.Conclusion

Farmers can benefit greatly from an IoT-based smart agriculture system. As a result of the lack of irrigation, agriculture suffers. Climate factors such as humidity, temperature, and moisture can be adjusted dependent on the local environmental variables. This technology also detects animal invasions, which are a major cause of crop loss. This technology aids in the scheduling of irrigation based on present data from the field and records from a climate source. It helps in deciding the farmer to whether to do irrigation or not to do. Continuous internet connectivity is required for continuous monitoring of data from sensors. This also can be overcome by using GSM unit as an alternative of mobile app. By GSM, SMS can be sent to farmer's phone.

12.Future scope

In the current project we have implemented the project that can protect and maintain the the crop. In this project the farmer monitor and control the field remotely. In future we can add or update few more things to this project.

- We can create few more models of the same project ,so that the farmer can have information of a entire.
- We can update the this project by using solar power mechanism. So that the power supply from electric poles can be replaced with solar panels. It reduces the power line cost. It will be a one time investment. We can add solar fencing technology to this project.
- We can use GSM technology to this project so that the farmers can get the information directly to his home through SMS. This helps the farmer to get information if there is a internet issues.
- We can add camera feature so that the farmer can monitor his field in real time. This helps in avoiding thefts

13.Appendix

Source Code

```
import time
import sys
import ibmiotf.application
import ibmiotf.device
import random
#Provide your IBM Watson Device Credentials
orgId = "oy32g"
deviceType = "Dharshini"
deviceId = 2002
token = "sridharan11"
authMethod = "use-token-auth"
# Initialize GPIO
def myCommandCallback(cmd):
 print("Command received: %s" % cmd.data['command'])
  status=cmd.data['command']
  if status=="motoron":
   print ("motor is on")
  else:
    print ("motor is off")
  #print(cmd)
try:
 deviceOptions = {"org": orgId, "type": deviceType, "id": deviceId, "auth-method":
authMethod, "auth-token": Token}
```

```
deviceCli = ibmiotf.device.Client(deviceOptions)
 #.....
except Exception as e:
 print("Caught exception connecting device: %s" % str(e))
sys.exit()
# Connect and send a datapoint "hello" with value "world" into the cloud as an event of type
"greeting" 10 times
deviceCli.connect()
while True:
 #Get Sensor Data from DHT11
 temp=random.randint(-20,125)
 hum=random.randint(0,100)
 soil=random.randint(0,100)
 data = { 'temp' : temp, 'hum': hum, 'soil': soil}
 #print data def myOnPublishCallback( ):
 print (f"Published temp = {temp} C, hum = {hum}, soil = {soil} deg c to IBM Watson")
 success = deviceCli.publishEvent("IoTSensor", "json", data,
gos=0,on_publish=myOnPublishCallback)
 if not success:
   print("Not connected to IoTF")
   time.sleep(10)
 deviceCli.commandCallback = myCommandCallback
 # Disconnect the device and application from the cloud
 deviceCli.disconnect()
```

 $\textbf{Github Link}: \underline{https://github.com/IBM-EPBL/IBM-Project-31209-1660197678.git}$

Project Demo link

https://drive.google.com/file/d/1zZDA866EhZg7gj_RaLxPpj4LjCHus5dW/view?usp=drivesdk