
IOT ASSIGNMENT 1

Topic: Assignment on Smart Home in Tinker Card

Name: Nandhini. N



Code:

```
#include <Servo.h>
int output1Value = 0;
int sen1Value = 0;
int sen2Value = 0;
int const gas_sensor = A1;
int const LDR = A0;
int limit = 400;

long readUltrasonicDistance(int triggerPin, int echoPin)
{
   pinMode(triggerPin, OUTPUT); // Clear the trigger
   digitalWrite(triggerPin, LOW);
   delayMicroseconds(2);
// Sets the trigger pin to HIGH state for 10 microseconds
```

```
digitalWrite(triggerPin, HIGH);
 delayMicroseconds(10);
 digitalWrite(triggerPin, LOW);
 pinMode(echoPin, INPUT);
 // Reads the echo pin, and returns the sound wave travel time
in microseconds
 return pulseIn(echoPin, HIGH);
}
Servo servo 7;
void setup()
 Serial.begin(9600);
 pinMode(A0, INPUT)
 pinMode(A1,INPUT);
 pinMode(13, OUTPUT);
 servo_7.attach(7, 500, 2500);
 pinMode(8,OUTPUT);
 pinMode(9, INPUT);
 pinMode(10, OUTPUT);
 pinMode(4, OUTPUT);
 pinMode(3, OUTPUT);
}
void loop()
int val1 = analogRead(LDR);
 if (val1 > 500)
 {
                    digitalWrite(13, LOW);
  Serial.print("Bulb ON = ");
  Serial.print(val1)
```

```
else
  digitalWrite(13, HIGH);
   Serial.print("Bulb OFF = ");
  Serial.print(val1);
sen2Value = digitalRead(9);
 if (sen2Value == 0)
  digitalWrite(10, LOW);
  digitalWrite(4, HIGH);
  digitalWrite(3, LOW);
  Serial.print(" | NO Motion Detected ");
 }
 if (sen2Value == 1)
   digitalWrite(10, HIGH);
  delay(3000);
  digitalWrite(4, LOW);
  digitalWrite(3, HIGH);
   Serial.print("
                 || Motion Detected!
                                            ");
 }
 delay(300);
int val = analogRead(gas_sensor);
 Serial.print("|| Gas Sensor Value = ");
 Serial.print(val);
//val = map(val, 300, 750, 0, 100);
 if (val > limit)
  tone(8, 650);
```

```
delay(300);
noTone(8);
 sen1Value = 0.01723 * readUltrasonicDistance(6, 6);
 if (sen1Value < 100)
  servo_7.write(90);
  Serial.print("
                || Door Open!; Distance = ");
  Serial.print(sen1Value);
  Serial.print("\n");
 }
 else
  servo 7.write(0);
  Serial.print(" || Door Closed!; Distance = ");
  Serial.print(sen1Value);
  Serial.print("\n");
 delay(10); // Delay a little bit to improve simulation
performance
```