Project Development Delivery Of Sprint-4

Date	10 November 2022
Team ID	PNT2022TMID19682
Project Name	Industry Specific Intelligence Fire Management System

Submitted by : Dinesh S , Karuppusamy A ,Balavenkatesh R , Karthick C

Student Roll number :732219EC025 , 732219EC042 , 732219ECL01 , 732219ECL03

```
#include <WiFi.h>
#include <Wire.h>
#include <SPI.h>
#include "ThingSpeak.h"  #include
<WiFiClient.h>

unsigned long myChannelNumber = 2; const char *  myWriteAPIKey
= "25V40ZAPI6KIZFGY";
int LED_PIN = 32; // the current reading from the input pin
int BUZZER_PIN= 12; const int
mq2 = 4;      int
value = 0;

//Flame int flame_sensor_pin = 10 ;// initializing pin 10 as the sensor digital
output pin int  flame_pin = HIGH ; // current state of sensor

char ssid[] = "Rathi";  char  pass[]
= "Rathidevi";     WiFiClient
client;
#define PIN_LM35 39
#define ADC_VREF_mV 3300.0
#define ADC_RESOLUTION 4096.0
#define RELAY_PIN    17
#define RELAY_PIN1  27


void setup()
{
  Serial.begin(115200);
```

```
pinMode(RELAY_PIN, OUTPUT);    pinMode(RELAY_PIN1, OUTPUT);
  Serial.print("Connecting to ");
  Serial.println(ssid);
WiFi.begin(ssid, pass);    int wifi_ctr
= 0;
  while (WiFi.status() != WL_CONNECTED)
  {
  delay(1000);
Serial.print(".");
  }
  Serial.println("WiFi connected");
ThingSpeak.begin(client); pinMode(LED_PIN, OUTPUT); pinMode(mq2, INPUT);
pinMode ( flame_sensor_pin , INPUT ); // declaring sensor pin as input pin for
Arduino  pinMode(BUZZER_PIN, OUTPUT);
}


void temperature()
{
  int adcVal = analogRead(PIN_LM35);    float milliVolt = adcVal *
(ADC_VREF_mV / ADC_RESOLUTION); float tempC = milliVolt /
10;  Serial.print("Temperature: ");
  Serial.print(tempC);
Serial.print("°C");    if(tempC
> 60)
  {
    Serial.println("Alert");
    digitalWrite(BUZZER_PIN, HIGH); // turn on
  }  else
  {
     digitalWrite(BUZZER_PIN, LOW); // turn on
  }
   int x = ThingSpeak.writeField(myChannelNumber,1, tempC, myWriteAPIKey);    }


void GasSensors()
{
  //mq2

  int gassensorAnalogmq2 = analogRead(mq2);
  Serial.print("mq2 Gas Sensor: ");
```

```
  Serial.print(gassensorAnalogmq2);
  Serial.print("\t");
  Serial.print("\t");
  Serial.print("\t");

  if (gassensorAnalogmq2 > 1500)
  {
    Serial.println("mq2Gas");      Serial.println("Alert");
digitalWrite(RELAY_PIN1, HIGH); // turn on fan 10 seconds      delay(100);
  }  else
  {
    Serial.println("No mq2Gas");      digitalWrite(RELAY_PIN1,
LOW);  // turn off fan 10 seconds      delay(100);

  }
  int a = ThingSpeak.writeField(myChannelNumber,4, gassensorAnalogmq2,
myWriteAPIKey);

}

void flamesensor()
{ flame_pin = digitalRead ( flame_sensor_pin ) ; // reading from the sensor
if (flame_pin == LOW ) // applying condition
{
Serial.println ( " ALERT: FLAME IS DETECTED" ) ;    digitalWrite (BUZZER_PIN,
HIGH ) ;// if state is high, then turn high the BUZZER  } else
{
Serial.println ( " NO FLAME DETECTED " ) ;
digitalWrite (BUZZER_PIN , LOW ) ; // otherwise turn it low
}  int value = digitalRead(flame_sensor_pin); // read the analog value from sensor

  if (value ==LOW) {     Serial.print("FLAME");
digitalWrite(RELAY_PIN, HIGH);
  } else {
    Serial.print("NO FLAME");
digitalWrite(RELAY_PIN, LOW);
  }
} void loop() {
temperature();   GasSensors();    flamesensor();


}
```