

```

import wiotp.sdk.device
import time
import random
myConfig = {
    "identity": {
        "orgId": "IDmd07mg",
        "typeId": "raspberrypi",
        "deviceId": "12345"
    },
    "auth": {
        "token": "12345678"
    }
}

```

```

def myCommandCallback (cmd):
    print ("Message received from IBM IoT Platform: %s" % cmd.data['command'])
    m=cmd.data['command']

```

```

client = wiotp.sdk.device.DeviceClient(config=myConfig, logHandlers=None)
client.connect()

```

```

def pub (data):
    client.publishEvent(eventId="status", msgFormat="json", data=myData, qos=0, onPublish=None)
    print ("Published data Successfully: %s", myData)

```

```

while True:
    myData={'name': 'Train1', 'lat': 17.6387448, 'lon': 78.4754336}
    pub (myData)
    time.sleep (3)
    #myData={'name': 'Train2', 'lat': 17.6387448, 'lon': 78.4754336}
    #pub (myData)
    #time.sleep (3)
    myData={'name': 'Train1', 'lat': 17.6341908, 'lon': 78.4744722}
    pub(myData)
    time.sleep(3)
    myData={'name': 'Train1', 'lat': 17.6340889, 'lon': 78.4745052}
    pub (myData)
    time.sleep (3)
    myData={'name': 'Train1', 'lat': 17.6248626, 'lon': 78.4720259}
    pub (myData)
    time.sleep (3)
    myData={'name': 'Train1', 'lat': 17.6188577, 'lon': 78.4698726}
    pub (myData)
    time.sleep (3)
    myData={'name': 'Train1', 'lat': 17.6132382, 'lon': 78.4707318}
    pub (myData)
    time.sleep (3)
    client.commandCallback = myCommandCallback
client.disconnect ()

```