```
#include <WiFi.h>
                                // library for wifi
#include < PubSubClient.h >
                                    // library for MQTT
#include <LiquidCrystal I2C.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);
//----- credentials of IBM Accounts ------
#define ORG "9gbe4w"
                                  // IBM organisation id
#define DEVICE_TYPE "SWMSMC"
                                        // Device type mentioned in ibm watson iot platform
#define TOVEN." //
                                   // Device ID mentioned in ibm watson iot platform
#define TOKEN "sUNA41tG6-Pa)0rk5X" // Token
//----- customise above values -----
char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name
                                                        // topic name and type of event
char publishTopic[] = "iot-2/evt/data/fmt/json";
perform and format in which data to be send
char topic[] = "iot-2/cmd/led/fmt/String";
                                                     // cmd Represent type and
command is test format of strings
char authMethod∏ = "use-token-auth";
                                                        // authentication method
char token∏ = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
                                                               //Client id
WiFiClient wifiClient;
                                                // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
#define ECHO_PIN 12
#define TRIG PIN 13
float dist;
void setup()
 Serial.begin(115200);
 pinMode(LED_BUILTIN, OUTPUT);
 pinMode(TRIG_PIN, OUTPUT);
 pinMode(ECHO_PIN, INPUT);
 //pir pin
 pinMode(4, INPUT);
 //ledpins
 pinMode(23, OUTPUT);
 pinMode(2, OUTPUT);
 pinMode(4, OUTPUT);
 pinMode(15, OUTPUT);
 lcd.init();
 lcd.backlight();
 lcd.setCursor(1, 0);
 lcd.print("");
 wifiConnect():
 mqttConnect();
float readcmCM()
 digitalWrite(TRIG_PIN, LOW);
```

```
delayMicroseconds(2);
 digitalWrite(TRIG_PIN, HIGH);
 delayMicroseconds(10);
 digitalWrite(TRIG_PIN, LOW);
 int duration = pulseIn(ECHO_PIN, HIGH);
 return duration * 0.034 / 2;
}
void loop()
       lcd.clear();
 publishData();
 delay(500);
 if (!client.loop())
   mqttConnect();
                                        // function call to connect to IBM
}
   -----*/
void wifiConnect()
 Serial.print("Connecting to ");
 Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL_CONNECTED)
    delay(500);
    Serial.print(".");
 Serial.print("WiFi connected, IP address: ");
 Serial.println(WiFi.localIP());
void mqttConnect()
  if (!client.connected())
     Serial.print("Reconnecting MQTT client to ");
     Serial.println(server);
     while (!client.connect(clientId, authMethod, token))
       Serial.print(".");
       delay(500);
     initManagedDevice();
     Serial.println();
void initManagedDevice()
  if (client.subscribe(topic))
     Serial.println("IBM subscribe to cmd OK");
  else
```

```
Serial.println("subscribe to cmd FAILED");
void publishData()
 float cm = readcmCM();
 if(digitalRead(34))
                                         //pir motion detection
  Serial.println("Motion Detected");
  Serial.println("Lid Opened");
  digitalWrite(15, HIGH);
 else
  digitalWrite(15, LOW);
if(digitalRead(34)== true)
                                              //Bin level detection
 if(cm <= 100)
  digitalWrite(2, HIGH);
  Serial.println("High Alert!!!, Trash bin is about to be full");
  Serial.println("Lid Closed");
  lcd.print("Full! Don't use");
  delay(2000);
  lcd.clear();
  digitalWrite(4, LOW);
  digitalWrite(23, LOW);
 else if(cm > 150 && cm < 250)
  digitalWrite(4, HIGH);
  Serial.println("Warning!!, Trash is about to cross 50% of bin level");
  digitalWrite(2, LOW);
  digitalWrite(23, LOW);
 else if(cm > 250 && cm <=400)
  digitalWrite(23, HIGH);
  Serial.println("Bin is available");
  digitalWrite(2,LOW);
  digitalWrite(4, LOW);
  delay(10000);
  Serial.println("Lid Closed");
}
else
  Serial.println("No motion detected");
 if(cm <= 100)
```

```
digitalWrite(21,HIGH);
String payload = "{\"High Alert!!\":\"";
payload += cm;
payload += "left\" }":
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
                                                               // if data is uploaded to cloud
successfully, prints publish ok else prints publish failed
Serial.println("Publish OK");
if(cm <= 250)
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist;
payload += "left\" }";
Serial.print("\n");
Serial.print("Sending distance: ");
Serial.println(cm);
if(client.publish(publishTopic, (char*) payload.c_str()))
Serial.println("Publish OK");
else
Serial.println("Publish FAILED");
 float inches = (cm / 2.54);
                                                      //print on lcd
 lcd.setCursor(0,0);
        lcd.print("Inches");
        lcd.setCursor(4,0);
        lcd.setCursor(12,0);
        lcd.print("cm");
        lcd.setCursor(1,1);
        lcd.print(inches, 1);
        lcd.setCursor(11,1);
        lcd.print(cm, 1);
        lcd.setCursor(14,1);
        delay(1000);
        lcd.clear();
}
```