


SPRINT DELIVERY 2

Team ID: PNT2022TMID20456

Simulation of sensors on IBM Watson IOT platform







CODE

```
#include <stdio.h>
```

#include <stdlib.h>

#include <WiFi.h>//library for wifi

#include <PubSubClient.h>//library for MQtt

#include "DHT.h"// Library for dht11

#define DHTPIN 15 // what pin we're connected to

#define DHTTYPE DHT22 // define type of sensor DHT 11

#define LED 2

DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of dht connected

void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);

//----credentials of IBM Accounts-----

#define ORG "aiig05"//IBM ORGANITION ID

```
#define DEVICE_TYPE "Farmer_IoT"//Device type mentioned in ibm watson
IOT Platform
#define DEVICE_ID "1911090"//Device ID mentioned in ibm watson IOT
Platform
#define TOKEN "1911090abcdefgh"
                                     //Token
String data3;
float t;
int moisture;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server
Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event
perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
//----
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined
client id by passing parameter like server id, portand wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
 dht.begin();
 pinMode(LED,OUTPUT);
 delay(10);
 Serial.println();
```

```
wificonnect();
 mqttconnect();
void loop()// Recursive Function
{
 moisture = random(0,50);
 t = dht.readTemperature();
 Serial.print("temp:");
 Serial.println(t);
 Serial.print("moisture:");
 Serial.println(moisture);
 PublishData(t, moisture);
 delay(1000);
 if (!client.loop()) {
  mqttconnect();
/.....retrieving to Cloud...../
void PublishData(float temp, int moisture) {
 mqttconnect();//function call for connecting to ibm
 /*
   creating the String in in form JSon to update the data to ibm cloud
 */
 String payload = "{\"temp\":";
 payload += temp;
 payload += "," "\"moisture\":";
 payload += moisture;
```

```
payload += "}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
  Serial.println("Publish ok");// if it successfully upload data on the cloud then it
will print publish ok in Serial monitor or else it will print publish failed
 } else {
  Serial.println("Publish failed");
 }
}
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
  while (!!!client.connect(clientId, authMethod, token)) {
   Serial.print(".");
   delay(500);
   initManagedDevice();
   Serial.println();
 }
void wificonnect() //function defination for wificonnect
{
 Serial.println();
 Serial.print("Connecting to ");
```

```
WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection
 while (WiFi.status() != WL_CONNECTED) {
  delay(500);
  Serial.print(".");
 }
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
 } else {
  Serial.println("subscribe to cmd FAILED");
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {
  //Serial.print((char)payload[i]);
  data3 += (char)payload[i];
```

```
Serial.println("data: "+ data3);
if(data3=="lighton")
{
Serial.println(data3);
digitalWrite(LED,HIGH);
}
else
{
Serial.println(data3);
digitalWrite(LED,LOW);
}
data3="";
}
```