

Date	18 November 2022
Team ID	PNT2022TMID37031
Project Name	Project - IoT Based Safety Gadget For Child Safety Monitoring & Notification
Maximum Marks	2 Marks

NOTIFICATION AND STORE DATA

```
#include<WiFi.h>//library for wifi
#include<PubSubClient.h>//library for
MQTT
void callback(char* subscribe topic, byte* payload, unsigned int payloadlength);
//-----credentials of IBM Account-----
#define ORG "frpi8s"// IBM ORGANIZATION ID
#define DEVICE_TYPE "NodeMCU"//DEVICE TYPE MENTIONED IN IOT
WATSON
PLATFORM #define DEVICE_ID "12345"//DEVICE ID MENTIONED IN IOT
WATSONPLATFORM
#define TOKEN "12345678"//Token String data3;floatdist;
//-----customize the above value -----char server [] =ORG
".messaging.internetofthings.ibmcloud.com";//servername
char publish topic[]="ultrasonic/evt/Data/fmt/json";/*topic nameandtype
of event perform and formatin
which data to be send*/
char subscribetopic[]="ultrasonic/cmd/test/fmt/String";/*cmd REPRESENT
Command tupe and
COMMAND IS TEST OF FORMAT STRING*/
char authMethod[]="use-token-auth";//authentication method char
token[]=TOKEN;
char clientid[]="d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//CLIENT ID
//
WiFiClient wifiClient;// creating an instance for wificlient PubSubClient
client(server, 1883 , callback , wifiClient);/*calling thepredefined
client id by passing parameter like server id,portand wificredential*/int LED =4;
int trig =5; int echo=18; void setup(){
```

```

Serial.begin(115200); pinMode(trig,OUTPUT); pinMode(echo,INPUT);
pinMode(LED,OUTPUT); delay(10); Serial.println(); wificonnect();
mqttconnect();
void loop() { digitalWrite(trig,LOW); digitalWrite(trig,HIGH);
delayMicroseconds(10); digitalWrite(trig,LOW);
float dur=pulseIn(echo,HIGH); float dist=(dur * 0.0343)/2;
Serial.print("distance in
cm"); Serial.println(dist); PublishData(dist);
delay(1000);
if (!client.loop()){ mqttconnect();
}
}
/* ..... retriving to
cloud. ....
*/
void PublishData(float dist){ mqttconnect();//function call for connecting to ibm
/*creating the string in form of JSON to update the data to ibm cloud*/String
object;if(dist<100)
{
digitalWrite(LED,HIGH); Serial.println("no object is near");
object="Near";
}
else
{
digitalWrite(LED,LOW); Serial.println("no object found"); object="No";
}
String payload="{\"distance\":"; payload +=dist; payload
+=",\" \"object\":\":"; payload += object;payload +=
"\":";
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishtopic, (char*) payload.c_str())){ Serial.println("Publish
ok");/* if its sucessfully upload data on the cloud then it will print publish ok in
serial monitor or else it will printpublish
failed*/
} else{
Serial.println("Publish failed");

```

```

}
}
void mqttconnect(){ if(!client.connected()){
Serial.print("Reconnecting client to "); Serial.println(server);
while(!!!client.connect(clientid,authMethod,
token)){ Serial.print("."); delay(500);
}
initManagedDevice();
Serial.println();
}
}

void wificonnect();//function defenition for wificonnect
{
Serial.println(); Serial.print("Connecting to ");WiFi.begin("vivo 1816",
"taetae95",6);//PASSING THE WIFI CREDIDENTIALS TO
ESTABLISH CONNECTION
while (WiFi.status() !=WL_CONNECTED){ delay(500);
Serial.print(".");
}
Serial.println(""); Serial.println("WiFi connected"); Serial.println("IP
address");
Serial.println(WiFi.localIP());
}
void initManagedDevice(){ if(client.subscribe(subscribetopic)){
Serial.println((subscribetopic)); Serial.println("subscribe to cmd OK");
}else{
Serial.println("subscribe to cmd failed");
}
}
void callback(char* subscribetopic,byte*payload,unsigned int
payloadLength)
{
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic); for(int i=0; i< payloadLength; i++){
//Serial.print((char)payload[i]); data3 +=(char)payload[i];
}
//Serial.println("dta: "+ data3);
//if(data3=="Near")
//{
//Serial.println(data3);

```

```

//digitalWrite(LED,HIGH);
//}
//else //{
//Serial.println(data3);
//digitalWrite(LED,LOW);//} data3="";
}

```

CIRCUIT DIAGRAM:

