

Assignment 4


Kubernetes / Docker

Student Name	Harsini S.R.
Student Roll Number	111519205011


Question:

1. Pull an Image from docker hub and run it in docker playground.
2. Create a docker file for the jobportal application and deploy it in Docker desktop application.
3. Create a IBM container registry and deploy helloworld app or jobportalapp.
4. Create a Kubernetes cluster in IBM cloud and deploy helloworld image or jobportal image and also expose the same app to run in nodeport.

Solution:



Pull an Image from docker hub and run it in docker playground.



Getting Started
Getting Started
Our Application
Updating our App
Sharing our App
Persisting our DB
Using Bind Mounts
Multi-Container Apps
Using Docker Compose
Image Building Best Practices
What Next?

Getting Started

The command you just ran

Congratulations! You have started the container for this tutorial! Let's first explain the command that you just ran. In case you forgot, here's the command:

```
docker run -d -p 80:80 docker/getting-started
```

You'll notice a few flags being used. Here's some more info on them:

- `-d` - run the container in detached mode (in the background)
- `-p 80:80` - map port 80 of the host to port 80 in the container
- `docker/getting-started` - the image to use

Pro tip

You can combine single character flags to shorten the full command. As an example, the command above could be written as:

```
docker run -dp 80:80 docker/getting-started
```

Table of contents

The command you just ran
The Docker Dashboard
What is a container?
What is a container image?

The Docker Dashboard

Before going too far, we want to highlight the Docker Dashboard, which gives you a quick view of the containers running on your machine. It gives you quick access to container logs, lets you get a shell inside the container, and lets you easily manage container lifecycle (stop, remove, etc.).

A screenshot of the Docker Playground interface showing the 'Docker Dashboard' for a specific container. The top left shows a digital clock at 03:51:42 and a 'CLOSE SESSION' button. Below it, there's a section for 'Instances' with a '+ ADD NEW INSTANCE' button. The main area displays details for a container named 'cdnqatu3_cdnqclm0qau000ccn7rg'. It shows the IP address '192.168.0.8', an 'OPEN PORT' button set to '80', and resource usage: 'Memory 2.44% (97.43MiB / 3.906GiB)' and 'CPU 0.73%'. There's an 'SSH' button and a terminal window showing the command 'ssh ip172-18-0-29-cdnqatu3tccg00b2oe60@direct.labs.pl'. Below the dashboard, there's a 'DELETE' button and an 'EDITOR' button. The terminal window shows the following output:

```
#####  
# WARNING!!!!  
# This is a sandbox environment. Using personal credentials  
# is HIGHLY discouraged. Any consequences of doing so are  
# completely the user's responsibilities.  
#  
# The PWD team.  
#####  
[node1] (local) root@192.168.0.8 ~  
$ docker run -d -p 80:80 docker/getting-started  
Unable to find image 'docker/getting-started:latest' locally  
latest: Pulling from docker/getting-started  
df9b9388f04a: Pull complete  
5867cba5fcbdb: Pull complete  
4b639e65cb3b: Pull complete  
061ed9e2b976: Pull complete  
bc19f3e8eeb1: Pull complete  
4071be97c256: Pull complete  
79b586f1a54b: Pull complete  
0c9732f525d6: Pull complete  
Digest: sha256:b558be874169471bd4e65bd6eac8c303b271a7ee8553ba47481b73b2bf597aee  
Status: Downloaded newer image for docker/getting-started:latest  
7dc1935ef5b1195786ac3f2f3ca64b6alc89c8a20c783d726b0b52a65ffe63ac  
[node1] (local) root@192.168.0.8 ~  
$
```

Create a docker file for the jobportal application and deploy it in Docker desktop application.

Containers

Images

Volumes

Dev Environments BETA

Extensions BETA

Add Extensions

Images on disk

Images [Give feedback](#)

LOCAL REMOTE REPOSITORIES

☐ In use only

NAME ↑	TAG	IMAGE ID	CREATED	SIZE
alpine/git	latest	42a1cda0ba24	23 days ago	43.61 MB
docker101tutorial	latest	99d88e797864	about 5 hours ago	28.91 MB
harsinisampleapp	latest	b6aa458ec41e	less than a minute ago	932.42 MB
harsinistr/docker101tutorial	latest	99d88e797864	about 5 hours ago	28.91 MB

RAM 2.85GB

CPU 0.25%

Connected to Hub

v4.14.0

Last login: Sat Nov 12 16:31:17 on tty000

harsini@Harsinis-MacBook-Pro ~ % cd desktop

harsini@Harsinis-MacBook-Pro desktop % cd flask_with_form_and_docker-main

harsini@Harsinis-MacBook-Pro flask_with_form_and_docker-main % docker build -t harsinisampleapp

"docker build" requires exactly 1 argument.

See 'docker build --help'.

Usage: docker build [OPTIONS] PATH | URL | -

Build an image from a Dockerfile

harsini@Harsinis-MacBook-Pro flask_with_form_and_docker-main % docker build -t harsinisampleapp .

[+] Building 55.7s (11/11) FINISHED

=> [internal] load build definition from Dockerfile

=> => transferring dockerfile: 267B

=> [internal] load .dockerignore

=> => transferring context: 2B

=> [internal] load metadata for docker.io/library/python:3.10.6

=> [auth] library/python:pull token for registry-1.docker.io

=> [internal] load build context

=> => transferring context: 19.58kB

=> [1/5] FROM docker.io/library/python:3.10.6@sha256:745efdfb7e4aac9a8422bd8c62d8bc35a693e8979a240d29677cb03e6aa91852

=> resolve docker.io/library/python:3.10.6@sha256:745efdfb7e4aac9a8422bd8c62d8bc35a693e8979a240d29677cb03e6aa91852

=> sha256:3e94d13e5e74ae17ff21376f57b95c7e1706931f8704aa99260968d81f6e4 5.16MB / 5.16MB

=> sha256:745efdfb7e4aac9a8422bd8c62d8bc35a693e8979a240d29677cb03e6aa91852 2.35kB / 2.35kB

=> sha256:1671565cc8d8f8c365c9b661d3fbc164e73d0f1fb0430c6179588428f99a9da2e 55.01MB / 55.01MB

=> sha256:fa9c7528c6a85216129e0a67bf962a77927b1cda58ba85546a41598539a57d6 10.88MB / 10.88MB

=> sha256:8d1f943ceaa3b3ce85df5c0926a7958836b84b700176bf9c56d8f37ac13fca 2.22kB / 2.22kB

=> sha256:d25a66380b10283603ff696d777bba5c0b1b9126fb0be7d11809574946bcf84 8.53kB / 8.53kB

=> sha256:53ad072f9cd16f08e93b182b20b758e11acc0ef60babe0fb1043c08de1901a 54.58MB / 54.58MB

=> sha256:d6b983117533b718374f1701ef593dd2afa6613c7908c6553be8e2a150e4448a 196.79MB / 196.79MB

=> sha256:d8092d56ded5476fe7c302256eb4dc6ff495ae8fb4dd28aa18d0cb7581e24a6c 6.29MB / 6.29MB

=> extracting sha256:1671565cc8d8f8c365c9b661d3fbc164e73d0f1fb0430c6179588428f99a9da2e

=> sha256:c71afcc57059adc44c5f3c348594df62035bb204f0057aa22cacba1d285a5 20.02MB / 20.02MB

=> extracting sha256:3e94d13e5e74ae17ff21376f57b95c7e1706931f8704aa99260968d81f6e4

=> sha256:864a10b3c704553e08bc5fcd12fbaee1c07048f6365f9fa35e84a285413da40b 234B / 234B

=> extracting sha256:fa9c7528c6a85216129e0a67bf962a7702e701daa585ab85546a41598830657d6

=> sha256:4334b2fe0819ddc1c355093aae88f21601a7c85a31cdadac8dc48fb6ed3c 3.04MB / 3.04MB

=> extracting sha256:53ad072f9cd16f08e93b182b20b758e11acc0ef60babe0fb1043c08de1901a

=> extracting sha256:d6b983117533b718374f1701ef593dd2afa6613c7908c6553be8e2a150e4448a

=> extracting sha256:d8092d56ded5476fe7c302256eb4dc6ff495ae8fb4dd28aa18d0cb7581e24a6c

=> extracting sha256:c71afcc57059adc44c5f3c348594df62035bb204f0057aa22cacba1d285a5

=> extracting sha256:864a10b3c704553e08bc5fcd12fbaee1c07048f6365f9fa35e84a285413da40b

=> extracting sha256:4334b2fe0819ddc1c355093aae88f21601a7c85a31cdadac8dc48fb6ed3c

=> [2/5] WORKDIR /app

=> [3/5] COPY requirements.txt .

=> [4/5] RUN pip install -r requirements.txt

=> [5/5] COPY . .

=> exporting to image


=> exporting layers

=> writing image sha256:b6aa458ec41ebf84735c1244dc2f57cb4a3ea88ba62139ce02f3c75be36aa

=> naming to docker.io/library/harsinisampleapp

Use 'docker scan' to run Snyk tests against images to find vulnerabilities and learn how to fix them

harsini@Harsinis-MacBook-Pro flask_with_form_and_docker-main %



Blog Page

Messages

Message One

Message One Content

Message Two

Message Two Content

Create a IBM container registry and deploy helloworld app or jobportalapp

Wasm is a fast, light alternative to Linux containers – try it out today in the [Docker+Wasm Technical Preview](#)

[Explore](#)
[Repositories](#)
[Organizations](#)
[Help](#)

[Upgrade](#)
 harsinir

[harsinir](#)
[Repositories](#)
[harsinisampleapp](#)

Using 0 of 1 private repositories. [Get more](#)

[General](#)
[Tags](#)
[Builds](#)
[Collaborators](#)
[Webhooks](#)
[Settings](#)

harsinir / harsinisampleapp

Description

This repository does not have a description

Last pushed: 13 hours ago

Docker commands

To push a new tag to this repository,

```
docker push harsinir/harsinisampleapp:tagname
```

Tags and scans

This repository contains 1 tag(s).

Tag	OS	Type	Pulled	Pushed
latest		Image	13 hours ago	13 hours ago

[See all](#)

Automated Builds

Manually pushing images to Hub? Connect your account to GitHub or Bitbucket to automatically build and tag new images whenever your code is updated, so you can focus your time on creating.

Available with Pro, Team and Business subscriptions.

[Upgrade](#)
[Learn more](#)

IBM Cloud

Container Registry

Quick start

Namespaces1

Repositories0

Images0

Trash0

Settings

Search resources and products...

CatalogManageHarsini SR's Account

Namespaces

LocationTokyo

Resource group: Filter...Search

Create

	Name	Resource group	Repository count	Image count	Retention policy	
	harsinins	Default	0	0	Retain all images	

Items per page: 251-1 of 1 item11 of 1 page

IBM Cloud

Container Registry

Quick start

Namespaces1

Repositories1

Images1

Trash0

Settings

Search resources and products...

CatalogManageHarsini SR's Account

Namespaces

LocationTokyo

Resource group: Filter...Search

Create

	Name	Resource group	Repository count	Image count	Retention policy	
	harsinins	Default	1	1	Retain all images	
	Repository		Image count		Last updated	
	jp.icr.io/harsinins/hello-world		1		415 days ago	

Items per page: 251-1 of 1 item11 of 1 page

IBM Cloud

Container Registry

Quick start

Namespaces1

Repositories1

Images1

Trash0

Settings

Search resources and products...

Q

Catalog

Manage

Harsini SR's Account

?

Repositories




LocationTokyo

Q Search

↺

⚙

Create +

<input type="checkbox"/>	Name	Image count	Namespace	Last updated	
<input type="checkbox"/>	 hello-world jp.jcr.io/harsinins/hello-world	1	harsinins	415 days ago	:
Digest					
Manifest type					
Tags					
Created					
Size					
Security status					
<input type="checkbox"/>	 f54a58bc1aac	Docker	latest	415 days ago	2 KB
					 Unsupported OS
					:

Items per page: 251-1 of 1 item11 of 1 page

Images

LocationTokyo



View by: Digest

Q Search

↺

⚙

Create +

<input type="checkbox"/>	Repository@digest	Tags	Manifest type	Created	Size	Security status	
<input type="checkbox"/>	 harsinins/hello-world@sha256:f54a58bc1aac...	latest	Docker	415 days ago	2 KB	 Unsupported OS	:

Items per page: 251-1 of 1 item11 of 1 page

Create a Kubernetes cluster in IBM cloud and deploy helloworld image

```
drain      Drain node in preparation for maintenance
taint      Update the taints on one or more nodes

Troubleshooting and Debugging Commands:
describe   Show details of a specific resource or group of resources
logs       Print the logs for a container in a pod
attach     Attach to a running container
exec       Execute a command in a container
port-forward Forward one or more local ports to a pod
proxy      Run a proxy to the Kubernetes API server
cp         Copy files and directories to and from containers
auth       Inspect authorization
debug      Create debugging sessions for troubleshooting workloads and nodes

Advanced Commands:
diff        Diff the live version against a would-be applied version
apply       Apply a configuration to a resource by file name or stdin
patch       Update fields of a resource
replace     Replace a resource by file name or stdin
wait        Experimental: Wait for a specific condition on one or many resources
kustomize   Build a kustomization target from a directory or URL..

Settings Commands:
label       Update the labels on a resource
annotate    Update the annotations on a resource
completion  Output shell completion code for the specified shell (bash, zsh, fish, or powershell)

Other Commands:
alpha       Commands for features in alpha
api-resources Print the supported API resources on the server
api-versions Print the supported API versions on the server, in the form of "group/version"
config      Modify kubeconfig files
plugin      Provides utilities for interacting with plugins
version     Print the client and server version information

Usage:
  kubectl [flags] [options]

Use "kubectl <command> --help" for more information about a given command.
Use "kubectl options" for a list of global command-line options (applies to all commands).
harsini@Harsinis-MacBook-Pro ~ % kubectl apply -f https://raw.githubusercontent.com/kubernetes/dashboard/v2.6.1/aio/deploy/recommended.yaml
namespace/kubernetes-dashboard created
serviceaccount/kubernetes-dashboard created
service/kubernetes-dashboard created
secret/kubernetes-dashboard-certs created
secret/kubernetes-dashboard-csrf created
secret/kubernetes-dashboard-key-holder created
configmap/kubernetes-dashboard-settings created
role.rbac.authorization.k8s.io/kubernetes-dashboard created
clusterrole.rbac.authorization.k8s.io/kubernetes-dashboard created
rolebinding.rbac.authorization.k8s.io/kubernetes-dashboard created
clusterrolebinding.rbac.authorization.k8s.io/kubernetes-dashboard created
deployment.apps/kubernetes-dashboard created
service/dashboard-metrics-scraper created
deployment.apps/dashboard-metrics-scraper created
harsini@Harsinis-MacBook-Pro ~ % kubectl proxy
Starting to serve on 127.0.0.1:8001
```

The screenshot shows the Kubernetes Dashboard interface. The top navigation bar includes the Kubernetes logo, a search bar, and a 'Workloads' menu. The main content area is divided into two sections. The top section, 'Workload Status', displays three large green circles representing the status of Deployments, Pods, and Replica Sets, each with a label 'Running: 2'. The bottom section, 'Deployments', shows a table with columns for Name, Images, Labels, Pods, and Created. It lists two deployments: 'dashboard-metrics-scraper' and 'kubernetes-dashboard', both with 1/1 pods and created 47 minutes ago. Below the Deployments section, the 'Pods' section is partially visible, showing a table with columns for Name, Image, Labels, Node, Status, Restarts, CPU/Memory Usage, and Created.

Name	Images	Labels	Pods	Created
dashboard-metrics-scraper	kubernetesui/metrics-scraper:v1.0.8	k8s-app: dashboard-metrics-scraper	1 / 1	47 minutes ago
kubernetes-dashboard	kubernetesui/dashboard:v2.6.1	k8s-app: kubernetes-dashboard	1 / 1	47 minutes ago

[illegible]

Blog Page

Messages

Message One Content

Message Two Content

dashboard-adminuser.yaml

```
apiVersion: v1
kind: ServiceAccount
metadata:
  name: admin-user
  namespace: kubernetes-dashboard
---
```

```

kind: Secret
metadata:
  name: admin-user-token
  namespace: kubernetes-dashboard
  annotations:
    kubernetes.io/service-account.name: admin-user
type: kubernetes.io/service-account-token

---
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRoleBinding
metadata:
  name: admin-user
roleRef:
  apiGroup: rbac.authorization.k8s.io
  kind: ClusterRole
  name: cluster-admin
subjects:
- kind: ServiceAccount
  name: admin-user
  namespace: kubernetes-dashboard

```

flask_deployment.yaml

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: flask-app

spec:
  replicas: 1
  selector:
    matchLabels:
      app: flask-app
  template:
    metadata:
      labels:
        app: flask-app

    spec:
      containers:
        - name: flask-app-container
          image: flask-app
          imagePullPolicy: Never
          ports:
            - containerPort: 5000
              protocol: TCP

```

flask_ingress.yaml

```
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: flask-app-ingress
  annotations:
    kubernetes.io/ingress.class: nginx
    nginx.ingress.kubernetes.io/ssl-redirect: "false"

spec:
  rules:
    - http:
        paths:
          - backend:
              service:
                name: flask-app-service
                port:
                  number: 5000
            path: /
            pathType: Prefix
```

flask_service.yaml

```
apiVersion: v1
kind: Service
metadata:
  name: flask-app-service
spec:
  type: ClusterIP
  ports:
    - port: 5000
  selector:
    app: flask-app
```

```
1 apiVersion: v1
2 kind: ServiceAccount
3 metadata:
4   name: admin-user
5   namespace: kubernetes-dashboard
6 ---
7 apiVersion: v1
8 kind: Secret
9 metadata:
10  name: admin-user-token
11  namespace: kubernetes-dashboard
12  annotations:
13    kubernetes.io/service-account.name: admin-user
14  type: kubernetes.io/service-account-token
15 ---
16
17 apiVersion: rbac.authorization.k8s.io/v1
18 kind: ClusterRoleBinding
19 metadata:
20   name: admin-user
21 roleRef:
22   apiGroup: rbac.authorization.k8s.io
23   kind: ClusterRole
24   name: cluster-admin
25 subjects:
26 - kind: ServiceAccount
27   name: admin-user
28   namespace: kubernetes-dashboard
```