



IBM PROJECT

GAS LEAKAGE MONITORING AND ALERTING

SYSTEM FOR INDUSTRIES

Team ID: PNT2022TMID30401

Team Leader: SUGUNA .K

Team Members:

- ▶ SURYA .M
- ▶ SOWNDHARYA .J
- ▶ SRIJA .K

CONTENTS

TITL E	PAGE NUMBER
1. INTRODUCTION	4
a. Project Overview	4
b. Purpose	4
2. LITERATURE SURVEY	4
a. Existing Problem	4
b. References	4
c. Problem Statement Definition	5
3. IDEATION & PROPOSED SOLUTION	5
a. Empathy Map Canvas	5
b. Ideation & Brainstorming	6
c. Proposed Solution	8
d. Problem Solution fit	9
4. REQUIREMENT & ANALYSIS	10
a. Functional Requirement	10
b. Non-Functional requirements	10
5. PROJECT DESIGN	11
a. Data Flow Diagrams	11
b. Solution & Technical Architecture	11
c. User Stories	12
6. PROJECT PLANNING & SCHEDULING	13
a. Sprint Planning & Estimation	13
b. Sprint Delivery Schedule	13
c. Reports from JIRA	13
7. CODING & SOLUTIONING	14
a. Feature 1	14
b. Feature 2	15
8. TESTING	15
a. Test Cases	15

b. User Acceptance Testing	15
9. RESULTS	15
a. Performance Metrics	15
10. ADVANTAGES & DISADVANTAGES	16
11. CONCLUSION	16
12. FUTURE SCOPE	17
13. APPENDIX	17
Source Code	17
GitHub & Project Demo Link	17

1. TRODUCTION

Project Overview:

This project helps the industries in monitoring the emission of harmful gases. In several areas, the integration of gas sensors helps in monitoring the gas leakage. If in any area gas leakage is detected the admins will be notified along with the location. In the web application, admins can view the sensor parameters.

Purpose:

Inhaling concentrated gas can lead to asphyxia and possible death. To overcome these disasters, we designed a system for monitoring and alerting the leakage of those harmful gases. This makes the industrialists get rid of the fear of any disasters caused by the gases.

2. LITERATURE SURVEY

Existing Problem:

This scheme is meant to fulfill the daily needs of the people. In our country 40 percent people die due to gas explosion at home. That number keeps growing. Even pregnant women and small children are affected. Using a GSM module and a mobile phone, the Gas Leakage Monitor is used to find, intimate leaks. The buzzer and LED are then activated after the gas leak is detected using a bracket sensor. When the designated time has passed, it will automatically turn off.

References:

[1] Shital Imade, Priyanka Rajmane, Aishwarya Gavali, V. N. Nayakwadi "Review paper on- LPG Gas leakage detection using IOT": IJIRS –International Journal of Innovative Research & Studies, Volume 8, Issue 2, Feb 2018 IJIRS: ISSN NO: 2319-9725. [2] Gas Leakage Detection Based on Arduino And Alarm Sound, Rhonnel S. Paculanan, Israel Carino, International Journal of Innovative Technology and Exploring Engineering (IJITEE) Vol 8, April 2019. [3] Dr. Chetana Tukkoji, Mr. Sanjeev Kumar, "Review paper on- LPG Gas leakage detection using IOT": IJEAST –International Journal of Engineering Applied Science & Technology, Volume 4, Issue 12, April 2020 IJEAST (online): 603-609. [4] Sanjoy Das, Sahana S, Soujanya K Swathi M C, "Gas leakage detection and prevention using IoT", International Journal of Scientific Research % Engineering Trends. Vol 6, Issue 3, May-June 2020, ISSN (online): 2395-566X. [5] Amatul Munnaza, Rupa Tejaswi, Tarun Kumar Reddy, Saranga Moahan "IoT Based Gas Leakage Monitoring Syste", Journal of Xi'an University of Architecture & Technology, Vol 12, ISSN No: 1006-7930, Issue 5, 2020. [6] B. F. Alshammari, M. T. Chughtai, "IoT Gas leakage detector and warning generator". Engineering and Technology and Applied Science Research Volume 10, Issue August 2020 .6142-6146. [7] Gas Leakage Detection and Prevention System, Shreyas

Thorat, Neha Tonape, International Journal of Trendy Research, Vol 4, Issue 7, Dec 2020, ISSN NO: 2582-0958. [8] Rohan KH1, Navanika Reddy, Pranamya Maddy, Sachit Girish, Dr. Badari Nath K “IoT based gas leakage detection and Alerting system”: JRP Publications, Vol. 1(1), pp. 002- 006, February 2021. [9] D. Surie, O. Laguionie, T. Pederson, “Wireless sensor networking of everyday objects in a smart home environment”, Proceedings of the International Conference on Intelligent Sensors”, Sensor Networks and Information Processing ISSNIP- 2008, pp. 189 – 194. REFERENCE: [10] J. Tsado, O. Imoru, S.O. Olayemi, “Design and construction of a GSM based gas leak Alert system”¹, IEEE Transaction, IRJEEE Vol. 1(1), pp. 002-006, September, 2014. [11] M. Eisenhower, P. Rosengren, P. Antolin, “A Development Platform for Integrating Wireless Devices and Sensors into Ambient Intelligence Systems”, pp.1- 3. [12] Harshada Navale, Prof. B.V.Pawar, “Arm Based Gas Monitoring System”. International Journal of Scientific & Technology Research Volume 3, Issue 6, June 2014. [13] Byeongkwan Kang, Sunghoi Park, Tacklim Lee and Sehyun Park, "IoT based Monitoring System using Tri-level Context Making Model for Smart Home Services", 2015 IEEE International Conference on Consumer Electronics (ICCE), 2015. [14] Abhishek, P. Bharath, “Automation of LPG cylinder booking and leakage monitoring system,” International Journal of Combined Research and Development (IJCRD), pp. 693–695, 2016

Problem statement definition:

This device does not get damaged very quickly, and if it does get damaged, water is the main reason for it. This device is easily damaged by water. Therefore, this device should be installed in a place where water does not go. This installation will not damage the device, if the device does, an example is water.

This tool is considered to be one and very safe for the users. My members are trusted. My members' invention is considered very safe for this country and its people and their families. Absence of this tool makes women in our country nervous by the spread of gas in their kitchen and is considered to be a sign of some accident. It is also proud to think of this project for people's lives only to eliminate this fear.

3. IDEATION & PROPOSED SOLUTION:


Empathy Map Canvas:

Empathy Map Canvas

Gain insight and understanding on solving customer problems.


1

Build empathy and keep your focus on the user by putting yourself in their shoes.



Ideation & Brainstorming:

Template



Brainstorm & idea prioritization

Use this template in your own brainstorming sessions so your team can unleash their imagination and start shaping concepts even if you're not sitting in the same room.

⌚ 10 minutes to prepare
🕒 1 hour to collaborate
👥 2-8 people recommended

[Share template feedback](#)

➔

Before you collaborate

A little bit of preparation goes a long way with this session. Here's what you need to do to get going.

⌚ 10 minutes

A Team gathering

Define who should participate in the session and send an invite. Share relevant information or pre-work ahead.

B Set the goal

Think about the problem you'll be focusing on solving in the brainstorming session.

C Learn how to use the facilitation tools

Use the Facilitation Superpowers to run a happy and productive session.

[Open article](#) ➔

1


Define your problem statement

What problem are you trying to solve? Frame your problem as a How Might We statement. This will be the focus of your brainstorm.

⌚ 5 minutes

PROBLEM


We are trying to prevent the gas leakage explosion in household things as well as industrial fields



Key rules of brainstorming

To run an smooth and productive session

- Stay in topic.
- Defer judgment.
- Go for volume.
- Encourage wild ideas.
- Listen to others.
- If possible, be visual.



Need some inspiration?

See a finished version of this template to kickstart your work.

[Open example](#) ➔

2

Brainstorm

Write down any ideas that come to mind that address your problem statement.

⌚ 10 minutes

TIP
You can select a sticky note and hit the pencil (switch to sketch) icon to start drawing!

ABDUL AZIZ M

It is one of valuable devices
Less amount of expenditure
Prevents the explosion occurs
It is very effective in nature
Prevents the diseases caused by some toxic gas
Save many lives

AYYANAR S

It's easy to setup and user friendly
It is useful gadget
It's better gas leakage
It works function automatically without any external input
This project is used many components and little bit complex
It indicate to leakage gas and turn automatically

KARTHIK PANDIYAN R

This leakage monitoring device is not water proof and stick the device.
This spot the water in the bucket fully damage in device
But, this device does not works for with electricity
Gas leakage is less maintenance for home and family security
But the device being and maintenance for are low cost
When gas has leakage in a household, it's better to use a gas leak detector or the LPG gas.

JEGAN J

Its low maintenance
It helps to avoid fire accidents
It works as both online and offline
It's not only used for home all gas industries
If gas has leak alert by LED indicating
It's more compact device everyone has to take and go it.

3

Group ideas

Take turns sharing your ideas while clustering similar or related notes as you go. In the last 10 minutes, give each cluster a sentence-like label. If a cluster is bigger than six sticky notes, try and see if you can break it up into smaller sub-groups.

⌚ 20 minutes


1.Prevents the diseases caused by some toxic gas

2.its indicate to leakage gas and turn automatically

3.Gas leakage is low maintenance at home and family security.

TIP
Add customizable tags to sticky notes to make it easier to find, browse, organize, and categorize important ideas or themes within your mural.

4.If gas has leak alert by LED indicating



Regardless of their importance, which tasks are more feasible than others? (Cost, time, effort, complexity, etc.)



Proposed Solution:

S.NO	Parameter	Description
1.	Problem Statement (Problem to be solved)	This monitoring is used to prevent fire accidents due flammable gas leakage in house from cylinders,industries,hospitals, hotels etc.
2.	Idea / Solution description	This monitoring system uses cloud and iot based hard wares and sensors.The sensors in the system detects flammable gaseous components in the environment and temperature using iot system and send indication via alarms and lights.
3.	Novelty / Uniqueness	The uniqueness of this system is that it uses cloud due to this, the alarm can be to the person via sms to his mobile when he is not in home.
4.	Social Impact / Customer Satisfaction	It helps in many ways to the society it prevents fire accidents due careless handle of gas cylinders . this is a real-time systems so it is faster and accidents can be prevented very easily.
5.	Business Model (Revenue Model)	This is a cloud based real time system ,that collects the data from the environment very quickly i.e. temperature,humidity and oxygen composition. using

		sensors and indicate via alarms and lights.
6.	Scalability of the Solution	<input type="checkbox"/> Accuracy. <input type="checkbox"/> Low cost. <input type="checkbox"/> Less maintenance. <input type="checkbox"/> Reliability.

Problem Solution Fit:

Project Title: Gas Leakage Monitoring and Alerting System

Project Design Phase-I: Solution Fit Template

Team ID: PNT2022TMD45387

Define CS, fit into CC	1. CUSTOMER SEGMENT(S) CS Government is our primary customer.	6. CUSTOMER CONSTRAINTS Only one gas can be measured with each instrument. spending power, budget, no cash, network connection, available devices.	5. AVAILABLE SOLUTION AS Apply soapy water to the entire hose assembly, including the tank's valve and regulator, using a spray bottle or sponge. Pressurise the system without turning on any appliances. If you see bubbles or smell rotten eggs, you have a leak.	Explore AS, difference

Identify strong TR & EM	2. JOBS-TO-BE-DONE / PROBLEMS J&P Gas detectors can be used to detect combustible, flammable and toxic gases, and oxygen depletion. This type of device is used widely in industry and can be found in locations, such as on oil rigs, to monitor manufacturing processes and emerging technologies such as photovoltaic.	9. PROBLEM ROOT CAUSE RC Overloading of gas causes the gas leakage. This leads to affect the customers or workers. The leakage of the gas will be detected and help to resolve this problem.	7. BEHAVIOUR BE Our Customer uses All-Purpose Leak Detector is designed to form large bubbles to indicate even the smallest leaks in many types of piping applications	Focus on J&P, TR, BE, understand RC Identify strong TR & EM

<p>3. TRIGGERS TR</p> <p>Some of the accidents at industry or home due to gas leakage and is very dangerous to the lives around the surroundings. This triggers the customers to insert this system.</p>	<p>10. YOUR SOLUTION SL</p> <p>If you install the gas leakage detector, it will ensure the human's life. We can work without any fear.</p>	<p>8. CHANNELS of BEHAVIOUR CH</p> <p>8.1 ONLINE We can transmit the information of leakage of gas from the home or industry to the mobile phone of the customer through the message by GSM Module.</p> <p>8.2 OFFLINE After receiving the message, Customer should take immediate action by block the leakage.</p>
<p>4. EMOTIONS: BEFORE / AFTER EM</p> <p>Customer feels insecure and fears before the installation of this device. But, after installation they feel secure and safe</p>		

4. . REQUIREMENT ANALYSIS

Functional Requirement:


FR No.	Functional Requirement (EPIC)	Sub Requirement (Story / Sub-Task)
FR-1	Create cloud account	Registration through Form Registration through G mail Registration through Link
FR-2	User Confirmation	Confirmation via Email Confirmation via OT
FR-3	User Login	User Login Via Mail id And Password
FR-4	Cloud registration	Connect the hardware device
FR-5	Connect to mobile	Connect the cloud with the mobile phone
FR-6	Connect Hardware	Connect hardware to the gas cylinders or in the wall

Non-functional Requirements:

FR No.	Non-Functional Requirement	Description
NFR-1	Usability	<ul style="list-style-type: none"> ● It is user friendly ● Easy to handle ● Process is simple
NFR-2	Security	<ul style="list-style-type: none"> ● The device is highly secure. ● Privacy is maintained
NFR-3	Reliability	<ul style="list-style-type: none"> ● The device is more reliable ● The device is more trustable in tough conditions
NFR-4	Performance	<ul style="list-style-type: none"> ● The performance is more accurate. ● It is a real time application
NFR-5	Availability	<ul style="list-style-type: none"> ● It can be available easily. ● It requires very few hardware components.
NFR-6	Scalability	<ul style="list-style-type: none"> ● Less maintenance. ● Low cost. ● Compact.


5. PROJECT DESIGN:**Data Flow Diagrams:**

Data Flow Diagram:



Solution & Technical Architecture:

Solution Architecture Diagram:



User Stories:

User Type	Functional Requirement (Epic)	User Story Number	User Story / Task	Acceptance criteria	Priority	Release
Customer (Mobile user)	Registration	USN-1	As a user, I can register for the application by entering my email, password, and confirming my password.	I can access my account / dashboard	High	Sprint-1
		USN-2	As a user, I will receive confirmation email once I have registered for the application	I can receive confirmation email & click confirm	High	Sprint-1
		USN-3	As a user, I can register for the application through Facebook	I can register & access the dashboard with Facebook Login	High	Sprint-2
		USN-4	As a user, I can register for the application through Gmail	I can access by message	Medium	Sprint-1
	Login	USN-5	As a user, I can log into the application by entering email & password	No need to login mail id	High	Sprint-1
Customer (Web user)	Dashboard					
Customer Care Executive	Registraion	USN-1	User want to use sim card and gsm module	Message reciver for arduino connected sim	High	Sprint-1
		USN-1	Sensor and module	All component is connected to	High	Sprint-1

				arduino		
Administrator	DATA	USN-1	What is Main component in this project	Arduino	High	Sprint-2
power	Dc	USN-1	How much power is required	9v is enff	High	Sprint-1

6. PROJECT PLANNING AND SCHEDULING:

Sprint Planning & Estimation:

Sprint	Functional Requirement (Epic)	User Story Number	User Story / Task	Story Points	Priority	Team Members
Sprint-1	Data Preparation & Data Visualization	USN-1	As a user, I provide Safety to the customers	5	High	Karthick pandiyan R
Sprint-1		USN-2	As an Analyst, I collect the data & Provide meaningful insights through IBM Cloud	3	High	Jegan J
Sprint-2	Dashboard	USN-3	As a user, I want to make sure the safe environment.	3	High	Ayyanar S
Sprint-2		USN-4	As an Analyst, I will upload the data in IBM Cloud to createa interactive dashboard	3	Medium	Abdul Aziz M
Sprint-3	Report	USN-5	As a user, I want to secure the lives and data of each	3	Medium	Karthick pandiyan R

			employee that report a particular event			
Sprint-3		USN-6	As an Analyst, I will use IBM Cloud to generate a report	3	Medium	Jegan J
Sprint-4	Story	USN-7	As a user, I can only understand the Analysis in animated presentation of dataset	5	Medium	Ayyanar S
Sprint-4		USN-8	As an Analyst, I use IBM to create an animated presentation (Story) of the dataset	3	High	Abdul Aziz M

.2 Sprint Delivery Schedule:


Sprint	Total Story Points	Duration	Sprint Start Date	Sprint End Date (Planned)	Story Points Completed (as on Planned End Date)	Sprint Release Date (Actual)
Sprint-1	5	6 Days	24 Oct 2022	24 Oct 2022	5	29 Oct 2022
Sprint-2	5	6 Days	31 Oct 2022	05 Nov 2022	5	05 Nov 2022
Sprint-3	5	6 Days	07 Nov 2022	12 Nov 2022	5	12 Nov 2022
Sprint-4	5	6 Days	14 Nov 2022	19 Nov 2022	5	15 Nov 2022

Velocity:


We have an 6-day sprint duration, and the velocity of the team is 4 (points per sprint). To

calculate the team's average velocity (AV) per iteration unit (story points per day)

$$AV = \frac{\text{SPRINT DURATION}}{\text{VELOCITY}} = \frac{6}{4} = 1.5$$



7. CODING AND SOLUTIONING:



Feature 2: (Python Output)

The screenshot displays a Windows desktop environment. On the left, a code editor window titled 'new python code.py - C:\Users\AZIZ MRK\OneDrive\Desktop\new python code.py (3.7.0)' shows a Python script. The script defines a callback function for IoT sensor data, initializes GPIO, and connects to an IBM IoT device. It then enters a loop to generate random temperature, humidity, and gas data, publishing it to the cloud. On the right, a 'Python 3.7.0 Shell' window shows the execution output. The output includes a restart message, connection status, and a series of published sensor data points (Temperature, Humidity, Gas) to IBM Watson IoT. The taskbar at the bottom shows the system clock as 00:07 on 19/11/2022.

```

new python code.py - C:\Users\AZIZ MRK\OneDrive\Desktop\new python code.py (3.7.0)
File Edit Format Run Options Window Help
authToken = "XeJFia7_@t-s@eq_?"

# Initialize GPIO
def myCommandCallback(cmd):
    print("Command received: %s" % cmd.data['command'])
    status=cmd.data['command']
    if status=="lighton":
        print ("led is on")
    elif status == "lightoff":
        print ("led is off")
    else :
        print ("please send proper command")

try:
    deviceOptions = {"org": organization, "type": deviceType, "id": deviceId, "auth":
deviceCli = ibmiotf.device.Client(deviceOptions)
    #.....

except Exception as e:
    print("Caught exception connecting device: %s" % str(e))
    sys.exit()

# Connect and send a datapoint "hello" with value "world" into the cloud as an event of
deviceCli.connect()

while True:
    #Get Sensor Data from DHT11
    temp=random.randint(0,110)
    Humid=random.randint(0,100)
    gas=random.randint(0,100)

    data = { 'temp': temp, 'Humid': Humid, 'gas': gas }
    #print data
    def myOnPublishCallback():
        print ("Published Temperature = %s C" % temp, "Humidity = %s %" % Humid, "Gas = %s %" % gas)

    success = deviceCli.publishEvent("IoTSensor", "json", data, qos=0, on_publish=myOnPublishCallback)
    if not success:
        print("Not connected to IoT")
    time.sleep(10)
  
```

```

Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Type "copyright", "credits" or "license()" for more information.
>>>
===== RESTART: C:\Users\AZIZ MRK\OneDrive\Desktop\new python code.py =====
2022-11-19 00:02:56,974 ibmiotf.device.Client INFO Connected successfully: d:5py6q9:Weather_now:Weather1234
Published Temperature = 94 C Humidity = 77 % gas = 77 % to IBM Watson
Published Temperature = 91 C Humidity = 98 % gas = 75 % to IBM Watson
Published Temperature = 101 C Humidity = 69 % gas = 85 % to IBM Watson
Published Temperature = 102 C Humidity = 76 % gas = 92 % to IBM Watson
Published Temperature = 104 C Humidity = 63 % gas = 94 % to IBM Watson
Published Temperature = 97 C Humidity = 69 % gas = 71 % to IBM Watson
Published Temperature = 107 C Humidity = 78 % gas = 99 % to IBM Watson
Published Temperature = 91 C Humidity = 88 % gas = 83 % to IBM Watson
Published Temperature = 108 C Humidity = 64 % gas = 92 % to IBM Watson
Published Temperature = 107 C Humidity = 92 % gas = 95 % to IBM Watson
Published Temperature = 103 C Humidity = 94 % gas = 92 % to IBM Watson
Published Temperature = 92 C Humidity = 99 % gas = 83 % to IBM Watson
Published Temperature = 101 C Humidity = 90 % gas = 81 % to IBM Watson
Published Temperature = 101 C Humidity = 74 % gas = 85 % to IBM Watson
Published Temperature = 94 C Humidity = 92 % gas = 78 % to IBM Watson
Published Temperature = 98 C Humidity = 99 % gas = 95 % to IBM Watson
Published Temperature = 102 C Humidity = 98 % gas = 78 % to IBM Watson
Published Temperature = 108 C Humidity = 85 % gas = 72 % to IBM Watson
Published Temperature = 93 C Humidity = 90 % gas = 88 % to IBM Watson
Published Temperature = 97 C Humidity = 77 % gas = 92 % to IBM Watson
Published Temperature = 103 C Humidity = 88 % gas = 94 % to IBM Watson
Published Temperature = 93 C Humidity = 89 % gas = 87 % to IBM Watson
Published Temperature = 95 C Humidity = 81 % gas = 100 % to IBM Watson
Published Temperature = 93 C Humidity = 100 % gas = 82 % to IBM Watson
Published Temperature = 90 C Humidity = 64 % gas = 88 % to IBM Watson
===== RESTART: C:\Users\AZIZ MRK\OneDrive\Desktop\new python code.py =====
2022-11-19 00:07:04,988 ibmiotf.device.Client INFO Connected successfully: d:5py6q9:Weather_now:Weather1234
Published Temperature = 0 C Humidity = 28 % gas = 7 % to IBM Watson
Published Temperature = 39 C Humidity = 86 % gas = 55 % to IBM Watson
Published Temperature = 41 C Humidity = 47 % gas = 39 % to IBM Watson
Published Temperature = 34 C Humidity = 4 % gas = 98 % to IBM Watson
Published Temperature = 32 C Humidity = 15 % gas = 100 % to IBM Watson
  
```

8. TESTING:


Test cases:

User Acceptance Testing:

9. RESULTS:

Performance Testing:

10. WEB APPLICATION DASHBOARD:



11. ANTAGES AND DISADVANTAGES

Advantages:

- Detect the concentration of the gases
- The sensor-enabled solution helps prevent the high risk of gas explosions and affecting any casualties within and outside the premises.
- Get real-time alerts about the gaseous presence in the atmosphere
- Prevent fire hazards and explosions
- Ensure worker's health
- Real-time updates about leakages
- Cost-effective installation
- Measure oxygen level accuracy
- Get immediate gas leak alerts

Disadvantage:

- Get immediate gas leak alerts
- When heavy dust, steam or fog blocks the laser beam, the system will not be able to take measurements

12. MOBILE APPLICATION:

I

10:09 | 1.6KB/s

4G

50%

Gas Leakage Detection and Aleting

Monitoring Layout Temperature

80

Humidity

19

Gas

68

Light on

Light off

Sprinkle on

Sprinkle off

13. LUSION:

Gas leakage leads to severe accidents resulting in material losses and human injuries. Gas leakage occurs due to poor maintenance of equipment and inadequate awareness of the people. Hence, gas leakage detection is essential to prevent accidents and to save human lives. This paper presented LPG leakage detection and alert system. This system triggers buzzer and notification to alert people when gas leakage is detected. This system is basic yet reliable.

14. FUTURE SCOPE:

Major cities of India are pushing Smart Home application, gas monitoring system is a part of SmartHome application. Enhancing Industrial Safety using IoT. This system can be implemented in Industries, Hotels and wherever the gas cylinders are used. This system can be used in industries involving applications such as Furnace, Boilers, Gas welding, Gas cutting, Steel Plants, Metallurgical industries, Food processing Industries, Glass Industries, Plastic industries, Pharmaceuticals, Aerosol manufacturing. As hospitals require to provide maximum possible safety to patients, this system can be used to keep track of all the cylinders used in it. Some of the cylinders used are Oxygen cylinder, Carbon dioxide cylinder, Nitrous oxide cylinder. As many students are naive the risk of causing accidents is high. Hence, our system can also be used in schools, colleges. Many colleges have well established labs including chemistry lab and pharmaceutical labs where gas burners are used. Several medical equipment requires gas cylinders.

15. APPENDIX:

Source Code:

- [Source code](#)

GitHub and Project Demo Link:

- [GitHub link](#)
- [Project Demo Link](#)