IBM ASSIGNMENT -4

QUESTION:-

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events.

CHINNAN S

CONNECTION

CLICK HERE TO(WOKWI)



PROGRAM :-

```
#include <WiFi.h>
#include <PubSubClient.h>
#include <ArduinoJson.h>

WiFiClient wifiClient;
///Organization ID illza1
//Device Type assignment4
//Device ID chinnan
//Authentication Method use-token-auth
//Authentication Token 87654321
```

```
#define ORG "illza1"
#define DEVICE_TYPE "assignment4"
#define DEVICE_ID "chinnan"
#define TOKEN "87654321"
#define speed 0.034

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/iot/fmt/json";
char topic[] = "iot-2/cmd/home/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
PubSubClient client(server, 1883, wifiClient);
void publishData();

const int trigpin=2;
const int echopin=15;
String command;
String data="";
String lat="14.167589";
String lon="80.248510";
String name="point2";
String icon="";

long duration;
int dist;

void setup()
{
  Serial.begin(115200);
  pinMode(trigpin, OUTPUT);
  pinMode(echopin, INPUT);
  wifiConnect();
  mqttConnect();
}

void loop() {

  publishData();
  delay(500);
```

```
  if (!client.loop()) {
    mqttConnect();
  }
}

void wifiConnect() {
  Serial.print("Connecting to "); Serial.print("Wifi");
  WiFi.begin("Wokwi-GUEST", "", 6);
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
}

void mqttConnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting MQTT client to "); Serial.println(server);
    while (!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(1000);
    }
    initManagedDevice();
    Serial.println();
  }
}

void initManagedDevice() {
  if (client.subscribe(topic)) {
     Serial.println(client.subscribe(topic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void publishData()
{
  digitalWrite(trigpin,LOW);
```

```
  digitalWrite(trigpin,HIGH);
  delayMicroseconds(10);
  digitalWrite(trigpin,LOW);
  duration=pulseIn(echopin,HIGH);
  dist=duration*speed/2;

  if(dist<100){
    dist=100-dist;
    icon="fa-trash";
  }else{
    dist=0;
    icon="fa-trash-o";
  }
  DynamicJsonDocument doc(1024);
  String payload;
  doc["Name"]=name;
  doc["Latitude"]=lat;
  doc["Longitude"]=lon;
  doc["Icon"]=icon;
  doc["FillPercent"]=dist;
  serializeJson(doc, payload);
  delay(3000);
  Serial.print("\n");
  Serial.print("Sending payload: ");
  Serial.println(payload);
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish OK");
  } else {
    Serial.println("Publish FAILED");
  }
}
```

IBM SCREENSHOT'S




```
#include <WiFi.h>
#include <PubSubClient.h>
#include <ArduinoJson.h>

WiFiClient wifiClient;
///Organization ID illza1
//Device Type assignment4
//Device ID chinnan
//Authentication Method use-token-auth
//Authentication Token 87654321

#define ORG "illza1"
#define DEVICE_TYPE "assignment4"
#define DEVICE_ID "chinnan"
#define TOKEN "87654321"
#define speed 0.034

char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/iot/fmt/json";
char topic[] = "iot-2/cmd/home/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
PubSubClient client(server, 1883, wifiClient);
void publishData();

const int trigpin=2;
const int echopin=15;
String command;
String data="";
String lat="14.167589";
String lon="80.248510";
```




IBM Watson IoT Platform
ASSIGNMENT -4
Line chart
100
50
0
15:47
15:47:30
1 minute
now
distance