

| | |
|---------------------|---|
| Assignment Date | 15 October 2022 |
| Student Name | MANIMARAN A |
| Student Roll Number | E1195028 |
| Maximum Marks | 2marks |
| Team ID | PNT2022TMID45335 |
| Project | AI BASED DISCOURSE FOR BAKING INDUSTRY |

ASSIGNMENT-4

SMS SPAM CLASSIFICATION

Import required library

Solution:

```
import os
import re
import pandas as pd
import numpy as np
import nltk
from nltk.corpus import stopwords
from nltk.stem import WordNetLemmatizer
from wordcloud import WordCloud
import matplotlib.pyplot as plt
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense, LSTM, Dropout, Embedding
from tensorflow.keras.callbacks import EarlyStopping
from tensorflow.keras.preprocessing.text import Tokenizer
import keras
from sklearn.preprocessing import LabelEncoder
```

```
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.model_selection import train_test_split
from google.colab import drive
```

Import required library

```
In [1]: import os
import re
import pandas as pd
import numpy as np
import nltk
from nltk.corpus import stopwords
from nltk.stem import WordNetLemmatizer
from wordcloud import WordCloud
import matplotlib.pyplot as plt
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import Dense, LSTM, Dropout, Embedding
from tensorflow.keras.callbacks import EarlyStopping
from tensorflow.keras.preprocessing.text import Tokenizer
import keras
from sklearn.preprocessing import LabelEncoder
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.model_selection import train_test_split
from google.colab import drive
```

Read dataset

Solution:

```
df = pd.read_csv(filepath_or_buffer='/content/spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

```
df.shape
```

```
df.drop(["Unnamed: 2", "Unnamed: 3", "Unnamed: 4"], axis=1, inplace=True)
df.columns
```

```
df.describe()
df.isna().sum()
df.duplicated().sum()
df = df.drop_duplicates()
df.duplicated().sum()
df['v1'].hist(bins=3)
```

```
df = pd.read_csv(filepath_or_buffer='/content/spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

| | v1 | v2 | Unnamed: 2 | Unnamed: 3 | Unnamed: 4 |
|---|------|---|------------|------------|------------|
| 0 | ham | Go until jurong point, crazy.. Available only ... | NaN | NaN | NaN |
| 1 | ham | Ok lar... Joking wif u oni... | NaN | NaN | NaN |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | NaN | NaN | NaN |
| 3 | ham | U dun say so early hor... U c already then say... | NaN | NaN | NaN |
| 4 | ham | Nah I don't think he goes to usf, he lives aro... | NaN | NaN | NaN |

```
: df.shape
```

```
: (5572, 5)
```

```
: df.drop(["Unnamed: 2", "Unnamed: 3", "Unnamed: 4"], axis=1, inplace=True)
df.columns
```

```
: Index(['v1', 'v2'], dtype='object')
```

```
: df.describe()
```

```
:
      v1      v2
count 5572    5572
unique    2    5169
top  ham  Sorry, I'll call later
freq 4825     30
```

```
df.isna().sum()
```

```
v1    0  
v2    0  
dtype: int64
```

```
df.duplicated().sum()
```


```
403
```

```
df = df.drop_duplicates()  
df.duplicated().sum()
```

```
0
```

```
df['v1'].hist(bins=3)
```

```
<matplotlib.axes._subplots.AxesSubplot at 0x7f73a64e7850>
```




Add Layers (LSTM, Dense-(Hidden Layers), Output)

Solution:

```
def wordcloud_vis(column):  
    most_common = nltk.FreqDist(df[column]).most_common(100)  
    word_cloud = WordCloud(width=1600, height=800,  
background_color='white').generate(str(most_common))  
    fig = plt.figure(figsize=(30,10), facecolor='white')  
    plt.imshow(wordcloud)
```

```
plt.axis('off')
plt.show()
wordcloud_vis('v2')
```

```
def wordcloud_vis(column):
    mostcommon = nltk.FreqDist(df[column]).most_common(100)
    wordcloud = WordCloud(width=1600, height=800, background_color='white').generate(str(mostcommon))
    fig = plt.figure(figsize=(30,10), facecolor='white')
    plt.imshow(wordcloud)
    plt.axis('off')
    plt.show()
```



```
df['alpha_text'] = df['v2'].apply(lambda x: re.sub(r'[^a-zA-Z ]+', ' ', x.lower()))
df.head()
```

```
df['alpha_text'] = df['v2'].apply(lambda x: re.sub(r'^a-zA-Z+', '', x.lower()))
df.head()
```

| | v1 | v2 | alpha_text |
|---|--|---|------------|
| 0 | ham Go until jurong point, crazy.. Available only ... | go until jurong point crazy available only in ... | |
| 1 | ham Ok lar... Joking wif u oni... | ok lar joking wif u oni | |
| 2 | spam Free entry in 2 a wkly comp to win FA Cup fina... | free entry in a wkly comp to win fa cup final... | |
| 3 | ham U dun say so early hor... U c already then say... | u dun say so early hor u c already then say | |
| 4 | ham Nah I don't think he goes to usf, he lives aro... | nah i dont think he goes to usf he lives aroun... | |

```

nltk.download('stopwords')
df['imp_text'] = df['alpha_text'].apply(lambda x : ' '.join([word for word in x.split() if not word in
set(stopwords.words('english'))]))
df.head()

```

```

nltk.download('stopwords')
df['imp_text'] = df['alpha_text'].apply(lambda x : ' '.join([word for word in x.split() if not word in set(stopwords.words('english'))]))
df.head()

```

[nltk_data] Downloading package stopwords to /root/nltk_data...

[nltk_data] Unzipping corpora/stopwords.zip.

| | v1 | v2 | alpha_text | imp_text |
|---|------|---|---|---|
| 0 | ham | Go until jurong point, crazy.. Available only ... | go until jurong point crazy available only in ... | go jurong point crazy available bugis n great ... |
| 1 | ham | Ok lar... Joking wif u oni... | ok lar joking wif u oni | ok lar joking wif u oni |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | free entry in a wkly comp to win fa cup final... | free entry wkly comp win fa cup final tks st ... |
| 3 | ham | U dun say so early hor... U c already then say... | u dun say so early hor u c already then say | u dun say early hor u c already say |
| 4 | ham | Nah I don't think he goes to usf, he lives aro... | nah i dont think he goes to usf he lives aroun... | nah dont think goes usf lives around though |

```

def tokenize(data):
    generated_token = list(data.split())
    return generated_token
df['token_text'] = df['imp_text'].apply(lambda x: tokenize(x))
df.head()

```

```

def tokenize(data):
    generated_token = list(data.split())
    return generated_token
df['token_text'] = df['imp_text'].apply(lambda x: tokenize(x))
df.head()

```

| | v1 | v2 | alpha_text | imp_text | token_text |
|---|------|---|---|---|---|
| 0 | ham | Go until jurong point, crazy.. Available only ... | go until jurong point crazy available only in ... | go jurong point crazy available bugis n great ... | [go, jurong, point, crazy, available, bugis, n... |
| 1 | ham | Ok lar... Joking wif u oni... | ok lar joking wif u oni | ok lar joking wif u oni | [ok, lar, joking, wif, u, oni] |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | free entry in a wkly comp to win fa cup final... | free entry wkly comp win fa cup final tks st ... | [free, entry, wkly, comp, win, fa, cup, final,... |
| 3 | ham | U dun say so early hor... U c already then say... | u dun say so early hor u c already then say | u dun say early hor u c already say | [u, dun, say, early, hor, u, c, already, say] |
| 4 | ham | Nah I don't think he goes to usf, he lives aro... | nah i dont think he goes to usf he lives aroun... | nah dont think goes usf lives around though | [nah, dont, think, goes, usf, lives, around, t... |

```

nltk.download('wordnet')
nltk.download('omw-1.4')
lemmatizer = WordNetLemmatizer()
def lemmatization(list_of_words):
    lemmatized_list = [lemmatizer.lemmatize(word) for word in list_of_words]
    return lemmatized_list
df['lemmatized_text'] = df['token_text'].apply(lambda x: lemmatization(x))
df.head()

```

```

nltk.download('wordnet')
nltk.download('omw-1.4')
lemmatizer = WordNetLemmatizer()
def lemmatization(list_of_words):
    lemmatized_list = [lemmatizer.lemmatize(word) for word in list_of_words]
    return lemmatized_list
df['lemmatized_text'] = df['token_text'].apply(lambda x: lemmatization(x))
df.head()

```

```

[nltk_data] Downloading package wordnet to /root/nltk_data...
[nltk_data] Downloading package omw-1.4 to /root/nltk_data...

```

| | v1 | v2 | alpha_text | imp_text | token_text | lemmatized_text |
|---|------|---|---|---|---|---|
| 0 | ham | Go until jurong point, crazy.. Available only ... | go until jurong point crazy available only in ... | go jurong point crazy available bugis n great ... | [go, jurong, point, crazy, available, bugis, n... | [go, jurong, point, crazy, available, bugis, n... |
| 1 | ham | Ok lar... Joking wif u oni... | ok lar joking wif u oni | ok lar joking wif u oni | [ok, lar, joking, wif, u, oni] | [ok, lar, joking, wif, u, oni] |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | free entry in a wkly comp to win fa cup final... | free entry wkly comp win fa cup final tkts st ... | [free, entry, wkly, comp, win, fa, cup, final,... | [free, entry, wkly, comp, win, fa, cup, final,... |
| 3 | ham | U dun say so early hor... U c already then say... | u dun say so early hor u c already then say | u dun say early hor u c already say | [u, dun, say, early, hor, u, c, already, say] | [u, dun, say, early, hor, u, c, already, say] |
| 4 | ham | Nah I dont think he goes to usf, he lives aro... | nah i dont think he goes to usf he lives aroun... | nah dont think goes usf lives around though | [nah, dont, think, goes, usf, lives, around, t... | [nah, dont, think, go, usf, life, around, though] |

```

df['clean'] = df['lemmatized_text'].apply(lambda x: ' '.join(x))
df.head()

```

```

df['clean'] = df['lemmatized_text'].apply(lambda x: ' '.join(x))
df.head()

```

| | v1 | v2 | alpha_text | imp_text | token_text | lemmatized_text | clean |
|---|------|---|---|---|---|---|---|
| 0 | ham | Go until jurong point, crazy.. Available only ... | go until jurong point crazy available only in ... | go jurong point crazy available bugis n great ... | [go, jurong, point, crazy, available, bugis, n... | [go, jurong, point, crazy, available, bugis, n... | go jurong point crazy available bugis n great ... |
| 1 | ham | Ok lar... Joking wif u oni... | ok lar joking wif u oni | ok lar joking wif u oni | [ok, lar, joking, wif, u, oni] | [ok, lar, joking, wif, u, oni] | ok lar joking wif u oni |
| 2 | spam | Free entry in 2 a wkly comp to win FA Cup fina... | free entry in a wkly comp to win fa cup final... | free entry wkly comp win fa cup final tkts st ... | [free, entry, wkly, comp, win, fa, cup, final,... | [free, entry, wkly, comp, win, fa, cup, final,... | free entry wkly comp win fa cup final tkts st ... |
| 3 | ham | U dun say so early hor... U c already then say... | u dun say so early hor u c already then say | u dun say early hor u c already say | [u, dun, say, early, hor, u, c, already, say] | [u, dun, say, early, hor, u, c, already, say] | u dun say early hor u c already say |
| 4 | ham | Nah I dont think he goes to usf, he lives aro... | nah i dont think he goes to usf he lives aroun... | nah dont think goes usf lives around though | [nah, dont, think, goes, usf, lives, around, t... | [nah, dont, think, go, usf, life, around, though] | nah dont think go usf life around though |

pre-processing

Solution:

```

wordcloud_vis('clean')
df1 = df.loc[df['v1'] == 'spam']
df2 = df.loc[df['v1'] == 'ham']

spam = set()
df1['clean'].str.lower().str.split().apply(spam.update)
print("Number of unique words in spam", len(spam))

ham = set()

```



```
df1 = df.loc[df['v1'] == 'spam']
df2 = df.loc[df['v1'] == 'ham']

spam = set()
df1['clean'].str.lower().str.split().apply(spam.update)
print("Number of unique words in spam", len(spam))

ham = set()
df2['clean'].str.lower().str.split().apply(ham.update)
print("Number of unique words in ham", len(ham))
```

Number of unique words in spam 2037
 Number of unique words in ham 6738

```
print("Number of overlapping words between spam and ham: ", len(spam & ham))
```

Number of overlapping words between spam and ham: 895

```
df['clean'].apply(lambda x:len(str(x).split())).max()
```

80

```
x = df['clean']
y = df['v1']
```

```
le = LabelEncoder()
y = le.fit_transform(y)
y
```

array([0, 0, 1, ..., 0, 0, 0])

X.shape

y.shape

```
|: X.shape
```

```
|: (5169,)
```

```
|: y.shape
```

```
|: (5169,)
```

TEST THE MODEL

Solution:

#Split the data into train, test

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.15, random_state=42,
stratify=y)
```

```
tokenizer = Tokenizer(num_words=1000)
```

```
tokenizer.fit_on_texts(X_train)
```

```
tokenized_train = tokenizer.texts_to_sequences(X_train)
```

```
X_train = tf.keras.utils.pad_sequences(tokenized_train, maxlen=100)
tokenized_test = tokenizer.texts_to_sequences(X_test)
X_test = tf.keras.utils.pad_sequences(tokenized_test, maxlen=100)
```

```
#Split the data into train, test
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.15, random_state=42, stratify=y)
```

```
tokenizer = Tokenizer(num_words=1000)
tokenizer.fit_on_texts(X_train)
tokenized_train = tokenizer.texts_to_sequences(X_train)
X_train = tf.keras.utils.pad_sequences(tokenized_train, maxlen=100)
```

```
tokenized_test = tokenizer.texts_to_sequences(X_test)
X_test = tf.keras.utils.pad_sequences(tokenized_test, maxlen=100)
```

CREATE THE MODEL

Solution:

```
model = Sequential()
model.add(Embedding(1000, output_dim=50, input_length=100))
model.add(LSTM(units=64, return_sequences = True, dropout = 0.2))
model.add(LSTM(units=32, dropout = 0.1))
model.add(Dense(units = 64, activation = 'relu'))
model.add(Dense(units = 32, activation = 'relu'))
model.add(Dense(1, activation='sigmoid'))
model.summary()
```

```
model = Sequential()
```

```
model.add(Embedding(1000, output_dim=50, input_length=100))
model.add(LSTM(units=64, return_sequences = True, dropout = 0.2))
model.add(LSTM(units=32, dropout = 0.1))
model.add(Dense(units = 64, activation = 'relu'))
model.add(Dense(units = 32, activation = 'relu'))
model.add(Dense(1, activation='sigmoid'))
```

```
model.summary()
```

Model: "sequential"

| Layer (type) | Output Shape | Param # |
|--------------------------|-----------------|---------|
| embedding (Embedding) | (None, 100, 50) | 50000 |
| lstm (LSTM) | (None, 100, 64) | 29440 |
| lstm_1 (LSTM) | (None, 32) | 12416 |
| dense (Dense) | (None, 64) | 2112 |
| dense_1 (Dense) | (None, 32) | 2080 |
| dense_2 (Dense) | (None, 1) | 33 |
| Total params: 96,081 | | |
| Trainable params: 96,081 | | |
| Non-trainable params: 0 | | |

COMPILE THE MODEL

Solution:

```
model.compile(optimizer='adam', loss='binary_crossentropy', metrics=['accuracy'])
```

COMPILE THE MODEL

```
: model.compile(optimizer='adam', loss='binary_crossentropy', metrics=['accuracy'])
```

FIT THE MODEL

Solution:

```
model.fit(X_train, y_train,
batch_size=128,epochs=10,validation_split=0.2,callbacks=[EarlyStopping(monitor='val_loss',patience=2)])
```

FIT THE MODEL

```
model.fit(X_train, y_train, batch_size=128,epochs=10,validation_split=0.2,callbacks=[EarlyStopping(monitor='val_loss',patience=2)])
```

< >

```
Epoch 1/10
28/28 [=====] - 14s 318ms/step - loss: 0.4842 - accuracy: 0.8731 - val_loss: 0.3761 - val_accuracy: 0.8760
Epoch 2/10
28/28 [=====] - 8s 275ms/step - loss: 0.3816 - accuracy: 0.8731 - val_loss: 0.3734 - val_accuracy: 0.8760
Epoch 3/10
28/28 [=====] - 8s 276ms/step - loss: 0.3755 - accuracy: 0.8731 - val_loss: 0.3593 - val_accuracy: 0.8760
Epoch 4/10
28/28 [=====] - 8s 274ms/step - loss: 0.2798 - accuracy: 0.8731 - val_loss: 0.1819 - val_accuracy: 0.9647
Epoch 5/10
28/28 [=====] - 8s 274ms/step - loss: 0.1161 - accuracy: 0.9772 - val_loss: 0.0802 - val_accuracy: 0.9761
Epoch 6/10
28/28 [=====] - 8s 277ms/step - loss: 0.0618 - accuracy: 0.9838 - val_loss: 0.0720 - val_accuracy: 0.9807
Epoch 7/10
28/28 [=====] - 8s 273ms/step - loss: 0.0458 - accuracy: 0.9849 - val_loss: 0.0696 - val_accuracy: 0.9772
Epoch 8/10
28/28 [=====] - 8s 275ms/step - loss: 0.0315 - accuracy: 0.9900 - val_loss: 0.0699 - val_accuracy: 0.9784
Epoch 9/10
28/28 [=====] - 8s 275ms/step - loss: 0.0241 - accuracy: 0.9915 - val_loss: 0.0862 - val_accuracy: 0.9716

<keras.callbacks.History at 0x7f739f0aff50>
```

SAVE THE MODEL

Solution:

```
model.save('spam-classifier.h5')
print("Accuracy of the model on Testing Data is - " , model.evaluate(X_test,y_test)[1]*100
, "%")
```

SAVE THE MODEL

```
model.save('spam-classifier.h5')
```

```
print("Accuracy of the model on Testing Data is - " , model.evaluate(X_test,y_test)[1]*100 , "%")
```

```
25/25 [=====] - 1s 29ms/step - loss: 0.0746 - accuracy: 0.9781
Accuracy of the model on Testing Data is - 97.80927896499634 %
```