Assignment 3

CNN MODEL FOR FLOWER CLASSIFICATION

Found 4317 images belonging to 5 classes.

```
Pre-Requisites
from google.colab import drive
drive.mount('/content/drive')
Drive already mounted at /content/drive; to attempt to forcibly
remount, call drive.mount("/content/drive", force_remount=True).
STEP 1 UNZIP FILES
cd/content/drive/MyDrive/AI_IBM
/content/drive/MyDrive/AI IBM
!unzip Flowers-Dataset.zip
Archive: Flowers-Dataset.zip
replace flowers/daisy/100080576 f52e8ee070 n.jpg? [y]es, [n]o, [A]ll,
[N]one, [r]ename: N
STEP 2 Image Augumentation
from tensorflow.keras.preprocessing.image import ImageDataGenerator
train datagen=ImageDataGenerator(rescale=1./255,
zoom range=0.2,horizontal flip=True,vertical flip=False)
test datagen=ImageDataGenerator(rescale=1./255)
x train=train datagen.flow from directory(r"/content/drive/MyDrive/
AI IBM/
flowers", target size=(64,64), class mode='categorical', batch size=24)
Found 4317 images belonging to 5 classes.
x test=test datagen.flow from directory(r"/content/drive/MyDrive/
AI IBM/
flowers", target size=(64,64), class mode='categorical', batch size=24)
```

```
x_train.class_indices
{'daisy': 0, 'dandelion': 1, 'rose': 2, 'sunflower': 3, 'tulip': 4}
```

Step -3 Initializing CNN And Create Model

from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import
Dense,Convolution2D,MaxPooling2D,Flatten

Step -4 Add layers

model=Sequential()

4.1 Input Layers (Convolution ,MaxPooling,Flatten)

```
model.add(Convolution2D(32,
  (3,3),input_shape=(64,64,3),activation='relu'))
model.add(MaxPooling2D(pool_size=(2,2)))
model.add(Flatten())
model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 62, 62, 32)	896
<pre>max_pooling2d (MaxPooling2D)</pre>	(None, 31, 31, 32)	0
flatten (Flatten)	(None, 30752)	0

Total params: 896 Trainable params: 896 Non-trainable params: 0

4.2 Hidden Layers

```
model.add(Dense(300,activation='relu'))
model.add(Dense(150,activation='relu'))
```

```
4.3 Output Lavers
model.add(Dense(5,activation='softmax'))
model.compile(loss='categorical crossentropy',optimizer='adam',metrics
=['accuracy'])
len(x train)
180
Step -5 Train the Model
model.fit generator(x train,steps per epoch=len(x train),
validation_data=x_test, validation_steps=len(x test), epochs= 30)
/usr/local/lib/python3.7/dist-packages/ipykernel launcher.py:1:
UserWarning: `Model.fit generator` is deprecated and will be removed
in a future version. Please use `Model.fit`, which supports
generators.
 """Entry point for launching an IPython kernel.
Epoch 1/30
- accuracy: 0.4714 - val loss: 1.1275 - val accuracy: 0.5532
Epoch 2/30
1.0600 - accuracy: 0.5854 - val loss: 0.9406 - val accuracy: 0.6301
Epoch 3/30
0.9678 - accuracy: 0.6247 - val loss: 0.9603 - val_accuracy: 0.6203
Epoch 4/30
0.8884 - accuracy: 0.6546 - val loss: 0.8187 - val accuracy: 0.6938
Epoch 5/30
0.8358 - accuracy: 0.6787 - val loss: 0.7393 - val accuracy: 0.7225
Epoch 6/30
0.7924 - accuracy: 0.6965 - val loss: 0.8389 - val accuracy: 0.6928
Epoch 7/30
0.7521 - accuracy: 0.7158 - val loss: 0.8503 - val accuracy: 0.6789
Epoch 8/30
0.7048 - accuracy: 0.7313 - val loss: 0.6492 - val accuracy: 0.7521
Epoch 9/30
0.6502 - accuracy: 0.7521 - val loss: 0.6458 - val accuracy: 0.7438
Epoch 10/30
```

```
0.6182 - accuracy: 0.7684 - val loss: 0.5721 - val accuracy: 0.7818
Epoch 11/30
0.5662 - accuracy: 0.7931 - val loss: 0.5968 - val accuracy: 0.7725
Epoch 12/30
0.5600 - accuracy: 0.7908 - val loss: 0.6907 - val accuracy: 0.7612
Epoch 13/30
0.5064 - accuracy: 0.8138 - val loss: 0.5185 - val accuracy: 0.8117
Epoch 14/30
0.4830 - accuracy: 0.8249 - val loss: 0.3613 - val accuracy: 0.8673
Epoch 15/30
0.4650 - accuracy: 0.8196 - val loss: 0.3396 - val accuracy: 0.8768
Epoch 16/30
0.4117 - accuracy: 0.8559 - val loss: 0.3472 - val accuracy: 0.8738
Epoch 17/30
0.3892 - accuracy: 0.8631 - val loss: 0.3314 - val accuracy: 0.8826
Epoch 18/30
0.3441 - accuracy: 0.8726 - val_loss: 0.4008 - val_accuracy: 0.8589
0.3467 - accuracy: 0.8719 - val loss: 0.2484 - val accuracy: 0.9060
Epoch 20/30
0.3327 - accuracy: 0.8758 - val loss: 0.2234 - val accuracy: 0.9210
Epoch 21/30
0.2807 - accuracy: 0.9009 - val loss: 0.2830 - val accuracy: 0.9036
Epoch 22/30
0.2751 - accuracy: 0.9013 - val loss: 0.2392 - val accuracy: 0.9141
Epoch 23/30
0.2549 - accuracy: 0.9097 - val loss: 0.2221 - val accuracy: 0.9189
Epoch 24/30
0.2412 - accuracy: 0.9243 - val loss: 0.2029 - val accuracy: 0.9291
Epoch 25/30
0.2360 - accuracy: 0.9199 - val_loss: 0.1965 - val_accuracy: 0.9307
Epoch 26/30
0.2199 - accuracy: 0.9201 - val loss: 0.1919 - val accuracy: 0.9331
Epoch 27/30
```

```
0.2008 - accuracy: 0.9363 - val loss: 0.1218 - val accuracy: 0.9560
Epoch 28/30
0.1889 - accuracy: 0.9310 - val_loss: 0.2838 - val_accuracy: 0.9108
Epoch 29/30
0.2046 - accuracy: 0.9275 - val_loss: 0.2116 - val accuracy: 0.9307
Epoch 30/30
0.1886 - accuracy: 0.9372 - val loss: 0.2091 - val accuracy: 0.9280
<keras.callbacks.History at 0x7f3e15438e50>
Step -6 Save The model
model.save('Flowers classification model1.h5')
Step -7 Test The model
ls
flowers/ Flowers classification model1.h5 Flowers-Dataset.zip
video.mp4
import numpy as np
from tensorflow.keras.models import load model
from tensorflow.keras.preprocessing import image
# Load the model
model=load model('Flowers classification model1.h5')
img=image.load img(r"/content/s3.jpg",target size=(64,64))
x=image.img to array(img)
x=np.expand dims(x,axis=0)
y=np.argmax(model.predict(x),axis=1)
# x train.class indices
index=['daisy','dandelion','rose','sunflower','tulip']
index[y[0]]
{"type": "string"}
```

We Achieved 93 percent of accuracy with this model