ASSIGNME NT 4

Ultrasonic sensor simulation in Wokwi

Date	14 November 2022
Team ID	PNT2022TMID29912

Question-1:

Write a code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100cms send an "Alert" to IBM cloud and display in the device recent events.

Code:


```
#include <WiFi.h> #include <PubSubClient.h> void
callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "kotoq5"//IBM ORGANITION ID
#define DEVICE_TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform #define
DEVICE ID "12345"//Device ID mentioned in ibm watson IOT Platform #define TOKEN "12345678"
//Token
String
             data3;
                                      server[]
                          char
                                                              ORG
".messaging.internetofthings.ibmcloud.com"; char publishTopic[] =
"iot-2/evt/Data/fmt/json";
char subscribetopic[] = "iot-2/cmd/test/fmt/String"; char authMethod[]
= "use-token-auth";
```

```
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback, wifiClient); const int trigPin =
5; const int echoPin = 18; #define SOUND_SPEED 0.034 long duration;
float distance; void setup() { Serial.begin(115200); pinMode(trigPin,
OUTPUT); pinMode(echoPin, INPUT); wificonnect(); mqttconnect();
void loop()
digitalWrite(trigPin, LOW);
delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW); duration =
pulseIn(echoPin, HIGH); distance =
duration * SOUND_SPEED/2;
Serial.print("Distance (cm): ");
Serial.println(distance); if(distance<100)
Serial.println("ALERT!!");
delay(1000); PublishData(distance);
delay(1000);
if (!client.loop())
{ mgttconnect();
delay(1000);
void PublishData(float dist)
{ mqttconnect();
```

```
String payload = "{\"Distance\":"; payload
+= dist;
payload += ",\"ALERT!!\":""\"Distance less than 100cms\""; payload +=
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) {
Serial.println("Publish ok");
} else {
Serial.println("Publish failed");
void
         mqttconnect()
                                    if
                                          (!client.connected())
Serial.print("Reconnecting client to "); Serial.println(server); while
(!!!client.connect(clientId, authMethod, token)) {Serial .print(".");
delay(500);
initManagedDevice();
Serial.println();
void wificonnect()
Serial.println(); Serial.print("Connecting to ");
WiFi.begin("Wokwi-GUEST", "", 6); while
(WiFi.status() != WL_CONNECTED) { delay(500);
Serial.print(".");
```

```
Serial.println(""); Serial.println("WiFi connected");
Serial.println("IP address: ");
Serial.println(WiFi.localIP());
void initManagedDevice() { if
(client.subscribe(subscribetopic))
{ Serial.println((subscribetopic)); Serial.println("subscribe to cmd
OK");
} else {
Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic); for (int i =
0; i < payloadLength; i++) {
//Serial.print((char)payload[i]); data3 +=
(char)payload[i];
Serial.println("data: "+ data3); data3="";
Diagram.json:
   "version": 1, "author":
   "srihariharasudhan",
                            "editor":
```

Circuit Diagram:




Output:

Wokwi output:

```
Connecting to ....
WiFi connected
IP address:
10.10.0.2
Reconnecting client to ytluse.messaging.internetofthings.ibmcloud.com
iot-2/cmd/test/fmt/String
subscribe to cmd OK

Distance (cm): 399.92
Distance (cm): 399.96
Distance (cm): 399.94
Distance (cm): 399.98
Distance (cm): 399.94
Distance (cm): 399.92
Distance (cm): 399.92
Distance (cm): 399.94
```

IBM cloud output:



Wokwi simulation link:

https://wokwi.com/projects/348299375616721491