

Emerging Methods for Early Detection of Forest Fires

MODEL BUILDING

TRAINING THE MODEL

Team ID	PNT2022TMID48861
Project Name	Emerging Methods for Early Detection of Forest Fires

TRAINING THE MODEL:

At this point, we have training data and a fully configured neural network to train. All that is left is to pass the data to the model for the training process to commence, a process that is completed by iterating on the training data. Training begins by calling the fit () method.

The arguments are the batch size as you are using “Adam” (bath gradient descent and epochs: no: of times the model should get trained). steps_per_epoch:

- It specifies the total number of steps taken from the generator as soon as one epoch is finished and the next epoch has started. We can calculate the value of steps_per_epoch as the total number of samples in your training folder divided by the batch size.
- Epochs:an integer and number of epochs we want to train our model for.
- Validation_data can be either input and targets list generator inputs, targets, and sample_weights list which can be used to evaluate.

The loss and metrics for any model after any epoch has ended.

- Validation_steps:

Only if the validation_data is a generator then only this argument can be used. It specifies the total number of steps taken from the generator before it is stopped at every epoch and its value is calculated as the total number of validation data points in your dataset divided by the validation batch size.

APPLYING ImageDataGenerator to train dataset:

`flow_from_directory()` method for Train folder.

```

Defining the Parameters

[11] train_datagen=ImageDataGenerator(rescale=1./255, shear_range=0.2, rotation_range=180, zoom_range=0.2, horizontal_flip=True)
test_datagen=ImageDataGenerator(rescale=1./255)

<keras.preprocessing.image.ImageDataGenerator at 0x7fb7448ac110>

Applying ImageDataGenerator functionality to train dataset

[10] from google.colab import drive
drive.mount('/content/drive')

Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).

[17] x_train=train_datagen.flow_from_directory('/content/drive/MyDrive/IBM PROJECT/dataset/DATA SET/archive/Dataset/Dataset/train_set', target_size=(128,128), batch_size=32, class_mode='binary_crossentropy')

Found 436 Images belonging to 2 classes.
```

TRAINING THE MODEL:

Training the model

```
model.fit_generator(x_train, steps_per_epoch=14, epochs=10, validation_data=x_test, validation_steps=7)
```

```
Epoch 1/10
14/14 [=====] - 322s 19s/step - loss: 1.5998 - accuracy: 0.71
Epoch 2/10
14/14 [=====] - 26s 2s/step - loss: 0.3427 - accuracy: 0.8625
Epoch 3/10
14/14 [=====] - 32s 2s/step - loss: 0.2979 - accuracy: 0.8857
Epoch 4/10
14/14 [=====] - 29s 2s/step - loss: 0.2585 - accuracy: 0.8929
Epoch 5/10
14/14 [=====] - 29s 2s/step - loss: 0.1926 - accuracy: 0.9243
Epoch 6/10
14/14 [=====] - 30s 2s/step - loss: 0.1971 - accuracy: 0.9264
Epoch 7/10
14/14 [=====] - 32s 2s/step - loss: 0.1781 - accuracy: 0.9286
Epoch 8/10
14/14 [=====] - 30s 2s/step - loss: 0.1796 - accuracy: 0.9243
Epoch 9/10
14/14 [=====] - 31s 2s/step - loss: 0.2306 - accuracy: 0.8964
Epoch 10/10
14/14 [=====] - 27s 2s/step - loss: 0.2593 - accuracy: 0.8857
<keras.callbacks.History at 0x7fd537101390>
```