Assignment – 4
Team ID: PNT2022TMID06631

STUDENT NAME	Saravanan K
STUDENT ROLL NUMBER	61072011906
MAXIMUM MARKS	2

Problem Statement: Abalone Age Prediction

Description:- Predicting the age of abalone from physical measurements. The age of abalone is determined by cutting the shell through the cone, staining it, and counting the number of rings through a microscope -- a boring and time-consuming task. Other measurements, which are easier to obtain, are used to predict age. Further information, such as weather patterns and location (hence food availability) may be required to solve the problem.

Building a Regression Model

1. Download the dataset
2. Load the dataset into the tool.
3. Perform Below Visualizations.

   · Univariate Analysis

   · Bi-Variate Analysis

   · Multi-Variate Analysis
4. Perform descriptive statistics on the dataset.
5. Check for Missing values and deal with them.
6. Find the outliers and replace them outliers
7. Check for Categorical columns and perform encoding
8. Split the data into dependent and independent variables.
9. Scale the independent variables
10. Split the data into training and testing
11. Build the Model
12. Train the Model
13. Test the Model
14. Measure the performance using Metrics.

1. **Download the dataset :**

```
#import libraries
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sb
import plotly.express as px
```

2. **Load the dataset into the tool :**

```
data = pd.read_csv('/content/drive/My Drive/abalone.csv')
data
```

Out[13]:

	Sex	Length	Diameter	Height	Whole weight	Shucked weight	Viscera weight	Shell weight	Rings
0	M	0.455	0.365	0.095	0.5140	0.2245	0.1010	0.1500	15
1	M	0.350	0.265	0.090	0.2255	0.0995	0.0485	0.0700	7
2	F	0.530	0.420	0.135	0.6770	0.2565	0.1415	0.2100	9
3	M	0.440	0.365	0.125	0.5160	0.2155	0.1140	0.1550	10
4	I	0.330	0.255	0.080	0.2050	0.0895	0.0395	0.0550	7
...	...	...	...	...	...	...	...	...	...
4172	F	0.565	0.450	0.165	0.8870	0.3700	0.2390	0.2490	11
4173	M	0.590	0.440	0.135	0.9660	0.4390	0.2145	0.2605	10
4174	M	0.600	0.475	0.205	1.1760	0.5255	0.2875	0.3080	9
4175	F	0.625	0.485	0.150	1.0945	0.5310	0.2610	0.2960	10
4176	M	0.710	0.555	0.195	1.9485	0.9455	0.3765	0.4950	12

4177 rows × 9 columns

```
In [12]: from google.colab import drive
drive.mount('/content/drive')
```

3. Perform Below Visualizations :

Univariate Analysis

In [14]: data['Rings'].value_counts()
data.hist()

Out[14]: array([[,
 ,
 ],
 [,
 ,
 ],
 [,
 ,
 ]],
 dtype=object)

Bi-Variate Analysis

In [15]: plt.scatter(data.Rings, data.Sex)
plt.title('The Gender of Abalone vs Number of Rings')
plt.xlabel('No. of Rings')
plt.ylabel('Gender')

Out[15]: Text(0, 0.5, 'Gender')

Multi-Variate Analysis

In [16]: sb.heatmap(data.corr(),annot=**True**)

4. Perform descriptive statistics on the dataset :

data.info()

```
RangeIndex: 4177 entries, 0 to 4176
Data columns (total 9 columns):
 #   Column          Non-Null Count  Dtype
---  ------          --------------  -----
 0   Sex             4177 non-null   object
 1   Length          4177 non-null   float64
 2   Diameter        4177 non-null   float64
 3   Height          4177 non-null   float64
 4   Whole weight    4177 non-null   float64
 5   Shucked weight  4177 non-null   float64
 6   Viscera weight  4177 non-null   float64
 7   Shell weight    4177 non-null   float64
 8   Rings           4177 non-null   int64
dtypes: float64(7), int64(1), object(1)
memory usage: 293.8+ KB
```

In [17]: data.describe()

Out[17]:

	Length	Diameter	Height	Whole weight	Shucked weight	Viscera weight	Shell weight	Rings
count	4177.000000	4177.000000	4177.000000	4177.000000	4177.000000	4177.000000	4177.000000	4177.000000

	Length	Diameter	Height	Whole weight	Shucked weight	Viscera weight	Shell weight	Rings
mean	0.523992	0.407881	0.139516	0.828742	0.359367	0.180594	0.238831	9.933684
std	0.120093	0.099240	0.041827	0.490389	0.221963	0.109614	0.139203	3.224169
min	0.075000	0.055000	0.000000	0.002000	0.001000	0.000500	0.001500	1.000000
25%	0.450000	0.350000	0.115000	0.441500	0.186000	0.093500	0.130000	8.000000
50%	0.545000	0.425000	0.140000	0.799500	0.336000	0.171000	0.234000	9.000000
75%	0.615000	0.480000	0.165000	1.153000	0.502000	0.253000	0.329000	11.000000
max	0.815000	0.650000	1.130000	2.825500	1.488000	0.760000	1.005000	29.000000

5. Check for Missing values and deal with them:

There is no missing values

In [19]: data.isnull().any()

```
Out[19]:    Sex             False
            length          False
            Diameter        False
            Height          False
            Whole weight    False
            Shucked weight  False
            Viscera weight  False
            Shell weight    False
            Rings           False
            dtype: bool
```

6. Find the outliers and replace them outliers:

The dataset does not have a outliers

In [20]: fig = px.histogram(data, x='Whole weight')
fig.show()

7. Check for Categorical columns and perform encoding:

There is one Categorical column SEX is replaced by an Integer

In [21]: **from** sklearn.preprocessing **import** LabelEncoder
le = LabelEncoder()

```
data["Sex"] = le.fit_transform(data["Sex"])
data["Sex"]
```

```
Out[21]: 0      2
         1      2
         2      0
         3      2
         4      1
              ..
         4172   0
         4173   2
         4174   2
         4175   0
         4176   2
         Name: Sex, Length: 4177, dtype: int64
```

8. Split the data into dependent and independent variables:

```
x=data.iloc[:,0:8].values
y=data.iloc[:,8:9].values
```

```
In [23]: x
Out[23]:
array([[2.    , 0.455 , 0.365 , ..., 0.2245, 0.101 , 0.15  ],
       [2.    , 0.35  , 0.265 , ..., 0.0995, 0.0485, 0.07  ],
       [0.    , 0.53  , 0.42  , ..., 0.2565, 0.1415, 0.21  ],
       ...,
       [2.    , 0.6   , 0.475 , ..., 0.5255, 0.2875, 0.308 ],
       [0.    , 0.625 , 0.485 , ..., 0.531 , 0.261 , 0.296 ],
       [2.    , 0.71  , 0.555 , ..., 0.9455, 0.3765, 0.495 ]])
In [24]:y
Out[24]:array([[15],
       [ 7],
       [ 9],
       ...,
       [ 9],
       [10],
       [12]])
```

9. Scale the independent variables:

```
x=data.iloc[:,0:8]
print(x.head())
   Sex  Length  Diameter  Height  Whole weight  Shucked weight  \
0    2   0.455     0.365   0.095        0.5140          0.2245
1    2   0.350     0.265   0.090        0.2255          0.0995
2    0   0.530     0.420   0.135        0.6770          0.2565
3    2   0.440     0.365   0.125        0.5160          0.2155
4    1   0.330     0.255   0.080        0.2050          0.0895
   Viscera weight  Shell weight
0          0.1010         0.150
1          0.0485         0.070
2          0.1415         0.210
3          0.1140         0.155
4          0.0395         0.055
```

10. Split the data into training and testing:

```
from sklearn.model_selection import train_test_split
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.3,random_state=0)
```

```
In [27]: x_train.shape
Out[27]: (2923, 8)
In [28]: x_test.shape
Out[28]: (1254, 8)
```

11. Build the Model:

```
from sklearn.linear_model import LinearRegression
lr = LinearRegression()
```

12. Train the Model:

```
lr.fit(x_train, y_train)
Out[30]:    LinearRegression()
```

13. Test the Model:

```
y_pred = lr.predict(x_test)
print((y_test)[0:6])
print((y_pred)[0:6])
[[13]
 [ 8]
 [11]
 [ 5]
 [12]
 [11]]
[[13.11640829]
 [ 9.65691091]
 [10.35350972]
 [ 5.63648715]
 [10.67436485]
 [11.95341338]]
```

14. Measure the performance using Metrics:

```
# RMSE(Root Mean Square Error)

from sklearn.metrics import mean_squared_error
mse = mean_squared_error(y_test, y_pred)
rmse = np.sqrt(mse)
print("RMSE value : {:.2f}".format(rmse))
```

```
from sklearn.model_selection import cross_val_score
cv_scores = cross_val_score(lr, x, y, cv=5)
sco=cv_scores.round(4)
print(cv_scores.round(4))
print("Average",sco.sum()/5)
```