

Project Development Phase Sprint 3-Test Cases

| | |
|---------------|---|
| Date | 12 Nov 2022 |
| Team ID | PNT2022TMID11425 |
| Project Name | Virtual Eye - Life Guard for Swimming Pools To Detect Active Drowning |
| Maximum Marks | 4Marks |

Init.py

```
from .object_detection import detect_common_objects
```

Object_detect.py

```
#import necessary packages
import cv2 import os import
numpy as np
from .utils import download_file

initialize = True net
= None
dest_dir = os.path.expanduser('~') + os.path.sep + '.cvlib' + os.path.sep +
'object_detection' + os.path.sep + 'yolo' + os.path.sep + 'yolov3' classes =
None
#colors are BGR instead of RGB in python COLORS =
[0,0,255], [255,0,0]
def populate_class_labels():

    #we are using a pre existent classifier which is more reliable and more
efficient than one
    #we could make using only a laptop
    #The classifier should be downloaded automatically when you run this script
    class_file_name = 'yolov3_classes.txt'
    class_file_abs_path = dest_dir + os.path.sep + class_file_name
url =
'https://github.com/Nico31415/DrowningDetector/raw/master/yolov3.txt'
if not os.path.exists(class_file_abs_path):
    download_file(url=url, file_name=class_file_name, dest_dir=dest_dir)
f = open(class_file_abs_path, 'r')
    classes = [line.strip() for line in f.readlines()]

    return classes
```

```

def get_output_layers(net):
    #the number of output layers in a neural network is the number of possible
    #things the network can detect, such as a person, a dog, a tie, a phone...
    layer_names = net.getLayerNames()

    output_layers = [layer_names[i[0] - 1] for i in
net.getUnconnectedOutLayers()]

    return output_layers
def draw_bbox(img, bbox, labels, confidence, Drowning,
write_conf=False):
    global COLORS
global classes
    if classes is
None:
        classes = populate_class_labels()
    for i, label in
enumerate(labels):

        #if the person is drowning, the box will be drawn red instead of blue
if label == 'person' and Drowning:
            color = COLORS[0]
label = 'DROWNING'        else:
            color = COLORS[1]

        if
write_conf:
            label += ' ' + str(format(confidence[i] * 100, '.2f')) + '%'

        #you only need to points (the opposite corners) to draw a rectangle.
These points
        #are stored in the variable bbox
        cv2.rectangle(img, (bbox[i][0],bbox[i][1]), (bbox[i][2],bbox[i][3]),
color, 2)
        cv2.putText(img, label, (bbox[i][0],bbox[i][1]-
10), cv2.FONT_HERSHEY_SIMPLEX, 0.5, color, 2)

    return img
def detect_common_objects(image, confidence=0.5,
nms_thresh=0.3):

    Height, Width = image.shape[:2]
scale = 0.00392
    global classes
global dest_dir

```

```

    #all the weights and the neural network algorithm are already
preconfigured
    #as we are using YOLO

    #this part of the script just downloads the YOLO files
    config_file_name = 'yolov3.cfg'
    config_file_abs_path = dest_dir + os.path.sep + config_file_name

    weights_file_name = 'yolov3.weights'
    weights_file_abs_path = dest_dir + os.path.sep + weights_file_name

    url = 'https://github.com/Nico31415/Drowning-
Detector/raw/master/yolov3.cfg'
    if not
os.path.exists(config_file_abs_path):
        download_file(url=url, file_name=config_file_name, dest_dir=dest_dir)

    url = 'https://pjreddie.com/media/files/yolov3.weights'
    if not
os.path.exists(weights_file_abs_path):
        download_file(url=url, file_name=weights_file_name,
dest_dir=dest_dir)

    global initialize
global net
    if
initialize:
        classes = populate_class_labels()
        net = cv2.dnn.readNet(weights_file_abs_path, config_file_abs_path)
initialize = False

    blob = cv2.dnn.blobFromImage(image, scale, (416,416), (0,0,0), True,
crop=False)

    net.setInput(blob)

    outs = net.forward(get_output_layers(net))
    class_ids = []
    confidences = []
    boxes = []
    for out in outs:
for detection in out:
        scores = detection[5:]
class id = np.argmax(scores)
max_conf = scores[class_id]
if max_conf > confidence:

```

```

        center_x = int(detection[0] * Width)
center_y = int(detection[1] * Height)
w = int(detection[2] * Width)          h =
int(detection[3] * Height)             x =
center_x - w / 2                       y = center_y - h / 2
class_ids.append(class_id)
confidences.append(float(max_conf))
        boxes.append([x, y, w, h])

indices = cv2.dnn.NMSBoxes(boxes, confidences, confidence, nms_thresh)
bbox = []
label = []
conf = []
    for i in indices:
i = i[0]          box =
boxes[i]          x =
box[0]            y =
box[1]            w =
box[2]            h =
box[3]
        bbox.append([round(x), round(y), round(x+w), round(y+h)])
label.append(str(classes[class_ids[i]]))
conf.append(confidences[i])

    return bbox, label, conf

```

Utils.py

```

import requests import
progressbar as pb import
os
    def download_file(url, file_name,
dest_dir):
        if not
os.path.exists(dest_dir):
            os.makedirs(dest_dir)

        full_path_to_file = dest_dir + os.path.sep + file_name
        if os.path.exists(dest_dir + os.path.sep + file_name):
            return full_path_to_file

        print("Downloading " + file_name + " from " + url)

try:
    r = requests.get(url, allow_redirects=True, stream=True)
except:

```

```
        print("Could not establish connection. Download failed")
return None

    file_size = int(r.headers['Content-Length'])
chunk_size = 1024
    numBars = round(file_size / chunk_size)

    bar = pb.ProgressBar(maxval=numBars).start()
        if r.status_code !=
requests.codes.ok:
            print("Error occurred while downloading file")
return None
```

```

        count = 0
        with
open(full_path_to_file, 'wb') as file:
    for chunk in r.iter_content(chunk_size=chunk_size):
        file.write(chunk)
bar.update(count)
count +=1

    return full_path_to_file

```

App.py:

```

import time
import cv2
import numpy as np
from cloudant.client import Cloudant
from flask import Flask, request, render_template, redirect, url_for
from playsound import playsound

import cvlib as cv
from cvlib.object_detection import draw_bbox

# Loading the model

# Authenticate using an IAM API key
client = Cloudant('5a1ffd26-d995-410e-af77-546fb6498fd8-
bluemix','5rUgrIfVeYtIyTqJ0hAvTOvIYvJDNIklr-sDUHQRClnN', connect=True)

# Create a database using an initialized client
my_database = client.create_database('my_database')
app=Flask(__name__)

#default home page or route
@app.route('/')
def index():
    return render_template('index.html')

```

```
@app.route('/index.html')
def home():
    return render_template("index.html")
```

```
#registration page
@app.route('/register') def
register():
    return render_template('register.html')
```

```
@app.route('/afterreg', methods=['POST'])
def afterreg():
    x = [x for x in request.form.values()]
    print(x)    data = {
        '_id': x[1], # Setting _id is optional
        'name': x[0],
        'psw':x[2]
    }
    print(data)

    query = {'_id': {'$eq': data['_id']}}

    docs = my_database.get_query_result(query)
    print(docs)

    print(len(docs.all()))

    if(len(docs.all())==0):
        url = my_database.create_document(data)
        #response = requests.get(url)
        return render_template('register.html', pred="Registration
Successful, please login using your details")    else:
        return render template('register.html', pred="You are already
a member, please login using your details")

#login page
@app.route('/login')
def login():
    return render_template('login.html')

@app.route('/afterlogin',methods=['POST'])
def afterlogin():
    user = request.form['_id']
    passw = request.form['psw']
    print(user,passw)
```

```

query = {'_id': {'$eq': user}}

docs = my_database.get_query_result(query)
print(docs)

print(len(docs.all()))

if(len(docs.all())==0):
    return render_template('login.html', pred="The username is not
found.")
    else:
        if((user==docs[0][0]['_id'] and
passw==docs[0][0]['psw'])):
            return redirect(url_for('prediction'))
        else:
            print('Invalid User')

```

```

@app.route('/logout')
def logout():
    return render_template('logout.html')

@app.route('/prediction')
def prediction():
    return render_template('prediction.html')

@app.route('/result',methods=["GET","POST"])
def res():
    webcam = cv2.VideoCapture('drowning.mp4')
    if not
webcam.isOpened():
        print("Could not open webcam")
exit()

    t0 = time.time() #gives time in seconds after 1970
    #variable dcount stands for how many seconds the person has been standing
still for
    centre0 = np.zeros(2)
    isDrowning = False

    #this loop happens approximately every 1 second, so if a person doesn't
move,
    #or moves very little for 10seconds, we can say they are drowning
    #loop through frames
while webcam.isOpened():
    # read frame from webcam
status, frame = webcam.read()

```



```
        if not
status:
    print("Could not read frame")
exit()

    # apply object detection
    bbox, label, conf = cv.detect_common_objects(frame)
#simplifying for only 1 person

    #s = (len(bbox), 2)
if (len(bbox)>0):
bbox0 = bbox[0]
    #centre = np.zeros(s)
centre = [0,0]
    #for i in range(0, len(bbox)):
        #centre[i]
=[ (bbox[i][0]+bbox[i][2])/2, (bbox[i][1]+bbox[i][3])/2 ]

    centre = [ (bbox0[0]+bbox0[2])/2, (bbox0[1]+bbox0[3])/2 ]
    #make vertical and horizontal movement variables
    hmov = abs(centre[0]-centre0[0])
    vmov = abs(centre[1]-centre0[1])
```

```

#there is still need to tweek the threshold
#this threshold is for checking how much the centre has moved

x=time.time()
threshold = 10
if(hmov>threshold or vmov>threshold):
    print(x-t0, 's')
t0 = time.time()
isDrowning = False

else:
    print(x-t0, 's')
if((time.time() - t0) > 10):
    isDrowning = True

    #print('bounding box: ', bbox, 'label: ' label , 'confidence: '
    conf[0], 'centre: ', centre)
    #print(bbox,label ,conf, centre)
    print('bbox: ', bbox, 'centre:', centre, 'centre0:', centre0)
print('Is he drowning: ', isDrowning)

    centre0 = centre
    # draw bounding box over detected objects

    out = draw_bbox(frame, bbox, label, conf,isDrowning)

    #print('Seconds since last epoch: ', time.time()-t0)
    # display output
    cv2.imshow("Real-time object detection", out)
if(isDrowning == True):
    playsound('alarm.mp3')
    webcam.release()
    cv2.destroyAllWindows()
    return render_template('prediction.html',prediction="Emergency
!!! The Person is drowining")
    #return render_template('base.html')

    # press "Q" to stop
    if
cv2.waitKey(1) & 0xFF == ord('q'):
    break

```

```

        # release resources
webcam.release()
cv2.destroyAllWindows()
        #return render_template('prediction.html',)

```

```

""" Running our application """ if
__name__ == "__main__":
app.run(debug=True)

```

Detect.py:

```

import cvlib as cv
from cvlib.object_detection import draw_bbox
import cv2 import time import numpy as np
from playsound import playsound
#for PiCamera
#from picamera Import PiCamera
#camera = PiCamera
#camera.start_preview()
# open webcam
webcam = cv2.VideoCapture(0)
    if not
webcam.isOpened():
    print("Could not open webcam")
exit()

t0 = time.time() #gives time in seconds after 1970

#variable dcount stands for how many seconds the person has been standing
still for
centre0 = np.zeros(2)
isDrowning = False
#this loop happens approximately every 1 second, so if a person doesn't move,
#or moves very little for 10seconds, we can say they are drowning
#loop through frames
while webcam.isOpened():

    # read frame from webcam
status, frame = webcam.read()

```

```

        if not
status:
    print("Could not read frame")
exit()

    # apply object detection
    bbox, label, conf = cv.detect_common_objects(frame)
#simplifying for only 1 person

    #s = (len(bbox), 2)
    if(len(bbox)>0):
bbox0 = bbox[0]
#centre = np.zeros(s)
centre = [0,0]

        #for i in range(0, len(bbox)):
            #centre[i]
            =[ (bbox[i][0]+bbox[i][2])/2, (bbox[i][1]+bbox[i][3])/2 ]

            centre =[ (bbox0[0]+bbox0[2])/2, (bbox0[1]+bbox0[3])/2 ]
            #make vertical and horizontal movement variables
hmov = abs(centre[0]-centre0[0])          vmov =
abs(centre[1]-centre0[1])

            #there is still need to tweek the threshold
            #this threshold is for checking how much the centre has moved

            x=time.time()
            threshold = 10
if(hmov>threshold or vmov>threshold):
    print(x-t0, 's')
t0 = time.time()
isDrowning = False

else:
    print(x-t0, 's')
if((time.time() - t0) > 10):
    isDrowning = True

    #print('bounding box: ', bbox, 'label: ' label , 'confidence: '
conf[0], 'centre: ', centre)

```

```

        #print(bbox,label ,conf, centre)
        print('bbox: ', bbox, 'centre:', centre, 'centre0:', centre0)
print('Is he drowning: ', isDrowning)

        centre0 = centre
        # draw bounding box over detected objects
        out = draw_bbox(frame, bbox, label,
conf,isDrowning)

        #print('Seconds since last epoch: ', time.time()-t0)
        # display output
        cv2.imshow("Real-time object detection", out)
if(isDrowning == True):
    playsound('alarm.mp3')

        # press "Q" to stop        if
cv2.waitKey(1) & 0xFF == ord('q'):
            break # release
resources
webcam.release()
cv2.destroyAllWindows()

```

