

ASSIGNMENT 4

SMS SPAM CLASSIFICATION

Assignment Date	15 October 2022
Student Name	Miss. G.K.Ishwarya
Student Roll Number	910619104029
Maximum Marks	

1.Download the dataset

2.Import required library

```
In [ ]: import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras_preprocessing import sequence
from keras.utils import to_categorical
from keras.models import load_model
```

```
In [ ]: # Count of Spam and Ham values
df.groupby(['v1']).size()
```

```
Out[ ]: v1
ham      4825
spam      747
dtype: int64
```

```
In [ ]: # Label Encoding target column
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
In [ ]: # Test and train split
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
In [ ]: # Tokenisation function
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)

sequences_matrix = sequence.pad_sequences(sequences,maxlen=max_len)
```

6.Compile the model

```
In [ ]: model = Model(inputs=inputs,outputs=layer)
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

Model: "model_2"

Layer (type)	Output Shape	Param #
=====		
InputLayer (InputLayer)	[(None, 150)]	0
embedding_2 (Embedding)	(None, 150, 50)	50000
lstm_2 (LSTM)	(None, 64)	29440
FullyConnectedLayer1 (Dense)	(None, 256)	16640
activation_4 (Activation)	(None, 256)	0
dropout_2 (Dropout)	(None, 256)	0
OutputLayer (Dense)	(None, 1)	257
activation_5 (Activation)	(None, 1)	0
=====		
Total params: 96,337		
Trainable params: 96,337		
Non-trainable params: 0		

7.Fit the Model

```
In [ ]: model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
                validation_split=0.2)
```

Epoch 1/10

30/30 [=====] - ETA: 0s - loss: 0.3374 - accuracy: 0.8712

8.Save the Model

```
In [ ]: model.save("model_1")
```

WARNING:absl:Function `_wrapped_model` contains input name(s) InputLayer with unsupported characters which will be renamed to inputlayer in the SavedModel.

WARNING:absl:Found untraced functions such as lstm_cell_1_layer_call_fn, lstm_cell_1_layer_call_and_return_conditional_losses while saving (showing 2 of 2). These functions will not be directly callable after loading.

9. Test the model

```
In [ ]: test_sequences = tok.texts_to_sequences(X_test)
        test_sequences_matrix = sequence.pad_sequences(test_sequences,maxlen=max_len)
```

```
In [ ]: accuracy = model.evaluate(test_sequences_matrix,Y_test)
print('Accuracy: {:.3f}'.format(accuracy[1]))
```

```
27/27 [=====] - 1s 36ms/step - loss: 0.1163 - accuracy: 0.9856
Accuracy: 0.986
```

```
In [ ]: y_pred = model.predict(test_sequences_matrix)
print(y_pred[25:40].round(3))
```

```
27/27 [=====] - 1s 20ms/step
[[0. ]
[0. ]
[0. ]
[0. ]
[0. ]
[0.002]
[0. ]
[0.024]
[0. ]
[0. ]
[0. ]
[0. ]
[0. ]
[0. ]
[0. ]]
```

```
In [ ]: print(Y_test[25:40])
```

[illegible]